

This is a preview - click here to buy the full publication



IEC/PAS 62593

Edition 1.0 2008-11

PUBLICLY AVAILABLE SPECIFICATION

PRE-STANDARD

Measurement method of a half-wavelength voltage for Mach-Zehnder optical modulators in wireless communication and broadcasting systems

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE



ICS 33.060.20

ISBN 978-2-88910-812-1

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	5
1 Scope.....	6
2 Normative references	6
3 Terms, definitions and acronyms	6
3.1 Terms and definitions	6
4 Electro-optic material based Mach-Zehnder optical modulator	8
4.1 Type.....	8
4.2 Structure	8
4.3 Requirements for Mach-Zehnder optical modulators	8
5 Sampling.....	9
5.1 Sampling	9
5.2 Sampling frequency.....	9
6 Measurement method of half wavelength voltage.....	9
6.1 Circuit diagram	9
6.2 Circuit description and requirement	9
6.3 Measurement condition	10
6.4 Principle of measurement method	10
6.5 Measurement procedure.....	13
Annex A (normative) Conventional Measurement method of Optical Modulation Index	17
Annex B (informative) Calculation method of intermodulation distortions from driving voltages and half-wavelength voltage for Mach-Zehnder optical modulator	19
Annex C (informative) Characteristics of Mach-Zehnder optical modulator	27
Annex D (informative) Points to consider for measurement	29
Bibliography.....	35
Figure 1 – A transfer curve of a Mach-Zehnder optical modulator	7
Figure 2	8
Figure 3 – Circuit diagram.....	9
Figure 4	11
Figure 5 – The schematic block diagram of the measurement setup.....	12
Figure 6 – Driving voltage measurement setup	14
Figure 7	15
Figure 8 a) – The amplitude of the optical signal is almost zero	16
Figure 8 b) – The optical signal is modulated in phase with S2 element	16
Figure 8 c) – The optical signal is modulated in opposite phase with S2 element	16
Figure A.1.....	17
Figure A.2.....	18
Figure B.1 Mach-Zehnder interferometer type optical modulator	19
Figure B.2 – Quadrature points of a transfer curve for a Mach-Zehnder optical modulator	23

Figure B.2 – Dependency of IM2 on NOMI and Bias voltage of a Mach-Zehnder optical modulator	24
Figure B.4 – Relation between IM3 and OMI of a Mach-Zehnder optical modulator	24
Figure B.5.....	25
Figure B.6 – IMD2 and IMD3.....	26
Figure D.1 – Errors of half-wavelength voltage measurements caused by limitations from the resolution of RF power supply	31
Figure D.2 – Relative errors of half-wavelength voltage measurement caused by limitations from the resolution of RF power	32
Figure D.3 – Relation between NOMI and IM3 for the Mach-Zehnder modulator (sample #1)	33
Figure D.4 – Relation between NOMI and IM3 for the Mach-Zehnder modulator (sample #2)	33
Figure D.5 – Relation between NOMI and IM2 for the Mach-Zehnder modulator (sample #1)	34
Table 1 – Acronyms	7
Table C.1	27
Table C.2.....	28
Table D.1.....	29
Table D.2 – Measurement results of half-wave voltages for Mach-Zehnder modulators	32

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MEASUREMENT METHOD OF A HALF-WAVELENGTH VOLTAGE
FOR MACH-ZEHNDER OPTICAL MODULATORS IN WIRELESS
COMMUNICATION AND BROADCASTING SYSTEMS**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

A PAS is a technical specification not fulfilling the requirements for a standard, but made available to the public.

IEC-PAS 62593 has been processed by IEC technical committee 103: Transmitting equipment for radio communication.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document

Draft PAS	Report on voting
103/74/PAS	103/81/RVD

Following publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned may transform it into an International Standard.

This PAS shall remain valid for an initial maximum period of 3 years starting from the publication date. The validity may be extended for a single 3-year period, following which it shall be revised to become another type of normative document, or shall be withdrawn.

INTRODUCTION

A variety of microwave-photonic devices are used in wireless communication and broadcasting systems. An optical modulator is an interface which converts an electronic signal into an optical signal. In the field of optical fibre communication systems, the IEC 62007 series "Semiconductor optoelectronic devices for fibre optic system applications" has been published. In the field of wireless systems, specifications of inter-modulation and composite distortion of modulators have been an important issue and have typically been negotiated between users and suppliers. During an International Meeting on Microwave Photonics, a proposal was announced to address standardizations for key-devices for Radio over Fibre (RoF) systems.

The RoF system is comprised mainly of two parts; one is the RF to photonic converter (E/O), and the other is photonic to RF converter (O/E). Radio waves are converted into an optical signal at E/O, and the signal is transferred into the optical fibre, and then the radio waves are regenerated at O/E. The nonlinear distortion characteristics of both E/O and O/E are important for the performance of the system. Semiconductor photodiodes are commonly used for O/E. Several types of optical modulator are used for E/O, such as Mach-Zehnder modulators, electro-absorption modulators and directly modulated LDs.

This PAS has been prepared in order to provide industry standard measurement methods for evaluating electro-optic material based Mach-Zehnder optical modulators to be used in wireless communication and broadcasting systems. When the optical modulation index (OMI) is calculated from the half-wavelength voltage measurement results, the intermodulation distortion of the Mach-Zehnder optical modulator can be obtained. In this PAS, the measurement method of the half-wavelength voltage for Mach-Zehnder optical modulators is described. The details of calculations of the second order intermodulation distortion (IM2) and the third order intermodulation distortion (IM3) are described in Annex B.

MEASUREMENT METHOD OF A HALF-WAVELENGTH VOLTAGE FOR MACH-ZEHNDER OPTICAL MODULATORS IN WIRELESS COMMUNICATION AND BROADCASTING SYSTEMS

1 Scope

This PAS gives a measurement method of half-wavelength voltage applicable to Mach-Zehnder optical modulators in wireless communication and broadcasting systems. In addition, this method is also effective for the estimation of the intermodulation distortion of Mach-Zehnder optical modulators.

- Frequency range: 10 MHz to 30 GHz.
- Wavelength band: 0,8 μm , 1,0 μm , 1,3 μm and 1,5 μm .
- Electro-optic material based Mach-Zehnder optical modulators and their modules.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62007-1, *Semiconductor optoelectronic devices for fibre optic system applications - Part 1: Specification template for essential ratings and characteristics*

IEC 62007-2 *Semiconductor optoelectronic devices for fibre optic system applications - Part 2: Measuring methods*