



# TECHNICAL REPORT



---

**Communication networks and systems for power utility automation –  
Part 90-14: Using IEC 61850 for FACTS (flexible alternate current transmission  
systems), HVDC (high voltage direct current) transmission and power  
conversion data modelling**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 33.200

ISBN 978-2-8322-4524-8

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

|   |    |
|---|----|
| FOREWORD.....   | 11 |
| INTRODUCTION.....   | 13 |
| 1 Scope.....  | 14 |
| 1.1 Namespace name and version .....  | 14 |
| 1.2 Code Component distribution .....   | 15 |
| 2 Normative references .....  | 16 |
| 3 Terms, definitions, variable symbols and abbreviated terms .....  | 17 |
| 3.1 Terms and definitions.....  | 17 |
| 3.2 Variable symbols .....  | 17 |
| 3.3 Abbreviated terms.....  | 18 |
| 4 FACTS Controllers and power conversion definition and specific requirements –<br>Definitions of FACTS and power conversions ..... | 20 |
| 4.1 Flexible AC transmission system.....  | 20 |
| 4.1.1 General .....   | 20 |
| 4.1.2 Examples of FACTS for shunt compensation .....  | 20 |
| 4.1.3 Examples of series compensation.....  | 20 |
| 4.2 Power conversions systems .....   | 21 |
| 5 Scope clarification and definition .....  | 21 |
| 5.1 General.....  | 21 |
| 5.2 Communication requirements and data flow .....  | 22 |
| 5.2.1 General .....   | 22 |
| 5.2.2 Mapping to interfaces defined in IEC 61850-5.....   | 23 |
| 5.3 SCL modelling requirements .....  | 24 |
| 6 Shared use cases for FACTS controllers and Power Conversion .....   | 24 |
| 6.1 Commonly used actors.....   | 24 |
| 6.2 Use case: Control system redundancy .....   | 26 |
| 6.2.1 Communication redundancy.....   | 26 |
| 6.2.2 Functional application redundancy.....  | 26 |
| 6.3 Use case: Control location and authority .....  | 27 |
| 6.4 Use case: System status and generic sequence processing.....  | 29 |
| 6.4.1 General .....   | 29 |
| 6.4.2 ASEQ Application Overview.....  | 33 |
| 6.4.3 Application example HVDC.....   | 34 |
| 6.4.4 Application example Shunt connected FACTS device .....  | 37 |
| 6.5 Use case: Cooling system.....   | 40 |
| 6.5.1 General .....   | 40 |
| 6.5.2 List of logical nodes for modelling of a Water based cooling system .....   | 43 |
| 6.5.3 Example of modelling a cooling system .....   | 43 |
| 6.6 Use case: Control and supervision of Harmonic filter .....  | 45 |
| 6.7 Use case: Control of external devices as part of automatic reactive power<br>control .....                                      | 46 |
| 6.7.1 General .....   | 46 |
| 6.7.2 Modelling example for external device control of a FACTS shunt device .....   | 49 |
| 6.8 Use case: Converter status during degraded operation .....  | 50 |
| 6.9 Use case: Power Semiconductor application monitoring.....   | 51 |
| 6.9.1 General .....   | 51 |
| 6.9.2 Equipment Indications and Properties.....   | 55 |

|                       |  |     |
|-----------------------|--|-----|
| 6.9.3                 | Modelling requirements, results, conclusion.....                                     | 56  |
| 6.10                  | Use case: Coordinated control between FACTS and other Power Conversion devices ..... | 56  |
| 6.10.1                | General .....  | 56  |
| 6.10.2                | Use case descriptions.....   | 58  |
| 6.10.3                | Optimized signal list and process information for modelling .....                    | 59  |
| 6.11                  | FACTS and Power Conversion Protection .....  | 60  |
| 6.11.1                | General .....  | 60  |
| 6.11.2                | Use case Protective action .....   | 60  |
| 6.11.3                | Modelling summary.....   | 62  |
| 7                     | FACTS .....  | 62  |
| 7.1                   | General.....   | 62  |
| 7.2                   | Shunt connected FACTS devices .....  | 63  |
| 7.2.1                 | General .....  | 63  |
| 7.2.2                 | Overview .....   | 63  |
| 7.2.3                 | Use cases for Shunt Connected FACTS device .....                                     | 64  |
| 7.3                   | Series connected FACTS devices .....   | 81  |
| 7.3.1                 | Overview .....   | 81  |
| 7.3.2                 | Use case of Series Compensation .....  | 81  |
| 7.3.3                 | Series Capacitors protections .....  | 99  |
| 8                     | Power Conversion .....   | 104 |
| 8.1                   | Power Converters .....   | 104 |
| 8.1.1                 | Overview .....   | 104 |
| 8.1.2                 | Power converter use cases with signal and data item descriptions.....                | 105 |
| 8.2                   | HVDC .....   | 122 |
| 8.2.1                 | Overview .....   | 122 |
| 8.2.2                 | HVDC use cases with signal and data item descriptions .....                          | 123 |
| 8.3                   | SFC – Static Frequency Converter.....  | 147 |
| 8.3.1                 | Overview .....   | 147 |
| 8.3.2                 | SFC use cases with signal and data item descriptions .....                           | 147 |
| 9                     | Data model.....  | 149 |
| 9.1                   | Abbreviated terms used in data object names .....                                    | 149 |
| 9.2                   | Logical node preliminaries .....   | 149 |
| 9.2.1                 | Package LogicalNodes_90_14.....  | 149 |
| 9.3                   | Data object name semantics and enumerations .....                                    | 222 |
| 9.3.1                 | Data semantics.....  | 222 |
| 9.3.2                 | Enumerated data attribute types .....  | 231 |
| 10                    | SCL Extensions .....   | 238 |
| Annex A (informative) | Introduction to FACTS applications .....   | 239 |
| A.1                   | Static Var Compensator overview .....  | 239 |
| A.2                   | Static Synchronous Compensator overview.....   | 241 |
| A.3                   | Fixed series compensation.....   | 243 |
| A.4                   | Mechanically Switched Series Reactor (MSSR).....                                     | 244 |
| A.5                   | Thyristor Controlled Series Capacitor (TCSC).....                                    | 244 |
| Annex B (informative) | Modelling guideline and examples.....  | 247 |
| B.1                   | Indication and control of breakers and switches .....                                | 247 |
| B.2                   | Power transformer .....  | 247 |
| B.3                   | Metering and measured values .....   | 247 |

|           |  |     |
|-----------|--|-----|
| B.4       | Examples of modelling of FACTS Shunt devices .....   | 247 |
| B.5       | Example of modelling of Fixed Series Compensation .....  | 251 |
| B.6       | Examples of modelling of HVDC transmission .....   | 252 |
|           | Bibliography.....  | 253 |
|           |  |     |
| Figure 1  | – Conceptual view of communication paths considered in this report.....                            | 21  |
| Figure 2  | – Levels and logical interfaces in substation automation systems.....                              | 22  |
| Figure 3  | – Data flow of a FACTS / Power Conversion controller.....  | 23  |
| Figure 4  | – Shared use cases for FACTS controllers and Power Conversion.....                                 | 24  |
| Figure 5  | – Hierarchal view of commonly used actors.....   | 26  |
| Figure 6  | – Typical redundant FACTS/Power Conversion control system setup .....                              | 27  |
| Figure 7  | – Authority for control of devices from different control levels and locations .....               | 28  |
| Figure 8  | – Typical scheme for implementation of control authority for function groups .....                 | 29  |
| Figure 9  | – System status / generic sequence processing .....  | 30  |
| Figure 10 | – ASEQ Application Overview (using the most important Data Objects).....                           | 34  |
| Figure 11 | – Exemplary sequence diagram, not applicable to all use cases.....                                 | 35  |
| Figure 12 | – Operating states of a FACTS shunt device .....   | 37  |
| Figure 13 | – Use case diagrams of State use case.....   | 39  |
| Figure 14 | – Cooling control use cases .....  | 41  |
| Figure 15 | – Cooling control modelling example .....  | 44  |
| Figure 16 | – Harmonic filter control and supervision.....   | 45  |
| Figure 17 | – Use case Control of external reactive components .....   | 47  |
| Figure 18 | – Modelling external banks for reactive power optimization. ....                                   | 49  |
| Figure 19 | – Use case Converter status .....  | 50  |
| Figure 20 | – Example of a hierarchical arrangement of power electronic units.....                             | 51  |
| Figure 21 | – Arrangement of 12 thyristor valves in a 12-pulse converter configuration .....                   | 52  |
| Figure 22 | – Use cases for semiconductor application monitoring .....   | 53  |
| Figure 23 | – Schematic view of two SVC devices connected in parallel.....                                     | 56  |
| Figure 24 | – Coordination between two FACTS / Power Conversion.....   | 57  |
| Figure 25 | – Use case diagram for coordinated FACTS device operation .....                                    | 57  |
| Figure 26 | – Coordination signals between two SVCs .....  | 58  |
| Figure 27 | – Optimized signal list for IEC 61850 .....  | 59  |
| Figure 28 | – Use cases for Control System Protective Actions .....  | 61  |
| Figure 29 | – V-I diagram of a generic SVC.....  | 63  |
| Figure 30 | – V-I diagram of a generic STATCOM .....   | 64  |
| Figure 31 | – Use cases for substation control of a shunt connected FACTS device.....                          | 64  |
| Figure 32 | – Example of operating states of a FACTS shunt device .....  | 66  |
| Figure 33 | – Example of control modes of a shunt connected FACTS device visualized<br>as a state machine..... | 66  |
| Figure 34 | – Use cases for changing states of FACTS device .....  | 67  |
| Figure 35 | – Change of control mode use case .....  | 68  |
| Figure 36 | – Sub-use cases of Configuration use case.....   | 70  |
| Figure 37 | – Automatic Reactive Power Control use case .....  | 72  |
| Figure 38 | – Non-automatic control mode use case.....   | 73  |

|  |     |
|--|-----|
| Figure 39 – Simplified fixed reactive power regulator block diagram .....  | 74  |
| Figure 40 – Simplified voltage regulator block diagram of automatic voltage control mode for an SVC .....              | 74  |
| Figure 41 – Shunt connected FACTS device operating characteristic with slow susceptance/reactive power regulator ..... | 76  |
| Figure 42 – Example of automatic voltage control system with additional reference signal for POD .....                 | 77  |
| Figure 43 – Activation of Gain Optimizer Function .....  | 78  |
| Figure 44 – Reset Gain Command Interaction Diagram .....   | 78  |
| Figure 45 – Series Compensation Use case .....   | 82  |
| Figure 46 – Use cases for Fixed Series Capacitors .....  | 83  |
| Figure 47 – Use case for Capacitor Discharge function .....  | 84  |
| Figure 48 – Use case for By-passing .....  | 85  |
| Figure 49 – Sub use cases for Lock-out use case .....  | 87  |
| Figure 50 – Sub use cases for auto reinsertion .....   | 89  |
| Figure 51 – Interaction of Automatic Reinsertion function with other functions .....                                   | 90  |
| Figure 52 – Example of states in Automatic reinsertion function .....  | 91  |
| Figure 53 – SLD of Fast Protective Equipment .....   | 93  |
| Figure 54 – Use case for Fast Protective equipment .....   | 94  |
| Figure 55 – SLD symbol for Metal Oxide Varistor .....  | 95  |
| Figure 56 – Zink Oxide Varistor use case .....   | 96  |
| Figure 57 – MSSR Use case diagram .....  | 97  |
| Figure 58 – Additional use cases for TCSC .....  | 99  |
| Figure 59 – SC Protection function Interface .....   | 101 |
| Figure 60 – Varistor Overload Protection use case .....  | 104 |
| Figure 61 – Varistor Failure Protection use case .....   | 104 |
| Figure 62 – Generic application of Power Conversion .....  | 105 |
| Figure 63 – Use Active / reactive power operation mode selection .....   | 106 |
| Figure 64 – Active power control use case .....  | 108 |
| Figure 65 – P-f characteristic .....   | 110 |
| Figure 66 – P-V characteristic .....   | 111 |
| Figure 67 – Example: Simple 4-point P-DCVol characteristic .....   | 112 |
| Figure 68 – Example: Sophisticated 9-point P-DCVol characteristic .....  | 113 |
| Figure 69 – P_Fixed .....  | 114 |
| Figure 70 – Reactive power control use case .....  | 115 |
| Figure 71 – Q-V characteristic .....   | 116 |
| Figure 72 – Q_Fixed .....  | 117 |
| Figure 73 – Phi_Fixed .....  | 118 |
| Figure 74 – V_Band .....   | 119 |
| Figure 75 – Use case .....   | 121 |
| Figure 76 – Typical HVDC setup .....   | 123 |
| Figure 77 – Use case Power direction change .....  | 124 |
| Figure 78 – Use case Run-up/Run-back modules .....   | 126 |
| Figure 79 – General AEPC functional characteristic .....   | 128 |

|  |     |
|--|-----|
| Figure 80 – Use case Automatic Emergency Power Control .....                                     | 129 |
| Figure 81 – DC Line fault recovery sequence.....   | 133 |
| Figure 82 – Examples for typical HVDC DC-Yard configurations .....                               | 136 |
| Figure 83 – DC Yard configuration .....  | 137 |
| Figure 84 – Coordinated mode switchover .....  | 138 |
| Figure 85 – Function mode switchover .....   | 140 |
| Figure 86 – Tap changer control and supervision.....   | 145 |
| Figure 87 – Typical SFC setup.....   | 147 |
| Figure 88 – Control by external reference .....  | 148 |
| Figure 89 – Class diagram LogicalNodes_90_14::LogicalNodes_90_14 .....                           | 150 |
| Figure 90 – Class diagram AbstractLNs::AbstractLNs .....   | 151 |
| Figure 91 – Class diagram LNGroupA::LNGroupANew.....   | 155 |
| Figure 92 – Class diagram LNGroupA::LNGroupAExt.....   | 156 |
| Figure 93 – Class diagram LNGroupC::LNGroupCNew .....  | 174 |
| Figure 94 – Class diagram LNGroupF::LNGroupFNew .....  | 184 |
| Figure 95 – Class diagram LNGroupP::LNGroupPNew.....   | 186 |
| Figure 96 – Class diagram LNGroupR::LNGroupRNew .....  | 194 |
| Figure 97 – Class diagram LNGroupS::LNGroupSNew.....   | 198 |
| Figure 98 – Class diagram LNGroupT::LNGroupT .....   | 204 |
| Figure 99 – Class diagram LNGroupX::LNGroupXNew.....   | 206 |
| Figure 100 – Class diagram LNGroupZ::LNGroupZNew .....   | 210 |
| Figure 101 – Class diagram LNGroupZ::LNGroupZNew2 .....  | 211 |
| Figure A.1 – Example SVC circuit diagram of an SVC.....  | 239 |
| Figure A.2 – SLD of example SVC with reference designations.....                                 | 240 |
| Figure A.3 – Simplified STATCOM Circuit diagram.....   | 241 |
| Figure A.4 – Example of SLD for a STATCOM with reference designations.....                       | 242 |
| Figure A.5 – Hybrid solution with two VSC, TSC and TCR branch.....                               | 243 |
| Figure A.6 – Single Line Diagram of a one segment Series Capacitor.....                          | 243 |
| Figure A.7 – Generic SLD of MSSR/OLC FACTS device .....  | 244 |
| Figure A.8 – SLD of TCSC and transmitted power vs. transmission angle .....                      | 245 |
| Figure A.9 – Generic TCSC control system.....  | 246 |
| Figure B.1 – Logical nodes representing SLD equipment SVC .....                                  | 248 |
| Figure B.2 – Modelling example of SVC functionality .....  | 249 |
| Figure B.3 – Logical nodes representing SLD equipment, STATCOM.....                              | 250 |
| Figure B.4 – Logical nodes representing SLD equipment, Control and Protection, Fixed<br>SC ..... | 251 |
| Figure B.5 – Logical Nodes representing HVDC specific equipment and functionality.....           | 252 |
| Table 1 – Attributes of (Tr)IEC 61850-90-14:2020A namespace .....                                | 15  |
| Table 2 – Tracking information of (Tr)IEC 61850-90-14:2020A namespace building-up.....           | 15  |
| Table 3 – Actors used in use cases.....  | 25  |
| Table 4 – Use case: System status and generic sequence processing .....                          | 31  |
| Table 5 – Use case: State.....   | 40  |

|   |    |
|---|----|
| Table 6 – Use case: Cooling system .....  | 41 |
| Table 7 – Logical nodes for modelling a water-based cooling system.....                         | 43 |
| Table 8 – Use case: Control and supervision of Harmonic filter.....                             | 46 |
| Table 9 – Use case: Control of external banks mode .....  | 48 |
| Table 10 – Process data for Control of external banks mode.....                                 | 49 |
| Table 11 – Use case: Get Converter Status .....   | 51 |
| Table 12 – Use case: Semiconductor application monitoring .....                                 | 53 |
| Table 13 – Thyristor controlled reactive components.....  | 55 |
| Table 14 – Process information for Thyristor controlled reactive component .....                | 55 |
| Table 15 – Coordinated FACTS device operation use case .....                                    | 58 |
| Table 16 – Process information for coordinated control mode .....                               | 60 |
| Table 17 – Use cases for Control System Protective Actions .....                                | 61 |
| Table 18 – Classification of FACTS Controllers.....   | 63 |
| Table 19 – Main use cases of FACTS Shunt device .....   | 65 |
| Table 20 – Changing states of FACTS device use cases.....                                       | 68 |
| Table 21 – Main control functions .....   | 69 |
| Table 22 – Supplementary control functions.....   | 69 |
| Table 23 – Additional control mode functions .....  | 69 |
| Table 24 – Use case: Control Mode selection .....   | 69 |
| Table 25 – Change Control mode process data.....  | 70 |
| Table 26 – Use case: Configuration of control mode .....  | 71 |
| Table 27 – Automatic Reactive Power Control process data.....                                   | 72 |
| Table 28 – Non-automatic control mode use case .....  | 73 |
| Table 29 – Non-automatic control mode setpoints.....  | 73 |
| Table 30 – Reactive power control mode process data .....                                       | 74 |
| Table 31 – Additional functions in Automatic Voltage Control mode .....                         | 75 |
| Table 32 – Voltage Control mode process data .....  | 75 |
| Table 33 – Process data for slow susceptance regulator mode or reactive power<br>regulator..... | 76 |
| Table 34 – POD mode settings and controls .....   | 77 |
| Table 35 – Use case: Gain.....  | 79 |
| Table 36 – Gain Supervision mode data objects.....  | 79 |
| Table 37 – Gain Optimizer mode data objects.....  | 79 |
| Table 38 – Protective Control Functions of SVC use cases .....                                  | 80 |
| Table 39 – Protective Control Functions of a VSC use cases .....                                | 81 |
| Table 40 – Use case: Series Compensation.....   | 82 |
| Table 41 – Use case: Fixed Series compensation .....  | 84 |
| Table 42 – Use case: Capacitor Discharge Function .....   | 85 |
| Table 43 – Bypassing of series capacitor .....  | 86 |
| Table 44 – Use case: Lock-out and temporary block insertion.....                                | 87 |
| Table 45 – Use case: Auto reinsertion .....   | 90 |
| Table 46 – Transition description for Figure 55 .....   | 92 |
| Table 47 – Use case: Fast Protective Equipment .....  | 95 |

|  |     |
|--|-----|
| Table 48 – Use case: Zink Oxide Varistor .....   | 97  |
| Table 49 – Use case: MSSR .....  | 98  |
| Table 50 – Indications and measurements .....  | 98  |
| Table 51 – Use case: TCSC.....   | 99  |
| Table 52 – Overview of typical series capacitor bank protections, based on IEC 60143-2 ... | 100 |
| Table 53 – Use case: SC protection functions.....  | 102 |
| Table 54 – Series protections modelling guideline .....                                    | 103 |
| Table 55 – Use case: Active / reactive power operation mode selection.....                 | 106 |
| Table 56 – Use case: Active power control .....  | 109 |
| Table 57 – New data items for P-f-characteristics .....                                    | 111 |
| Table 58 – New data items for P-V.....   | 112 |
| Table 59 – New data items for P-DCVol.....   | 113 |
| Table 60 – New data items for fixed active power .....                                     | 114 |
| Table 61 – New data items for fixed DC current .....                                       | 114 |
| Table 62 – New data items for Active power (general) .....                                 | 114 |
| Table 63 – Reactive Power control use case (Power Conversion) .....                        | 116 |
| Table 64 – New data items for Q-V .....  | 117 |
| Table 65 – New data items for Q_fixed .....  | 117 |
| Table 66 – New data items for Q_Band.....  | 118 |
| Table 67 – New data items for Phi_Fixed.....   | 118 |
| Table 68 – New data items for V_Band .....   | 119 |
| Table 69 – New data items for Reactive power (general), .....                              | 119 |
| Table 70 – Use case Reactive power (Power Conversion) .....                                | 120 |
| Table 71 – Intermediate DC circuit use case .....  | 122 |
| Table 72 – Use case Power direction change.....  | 125 |
| Table 73 – Use case Run-up/Run-back modules .....  | 127 |
| Table 74 – Use case Automatic Emergency Power Control .....                                | 129 |
| Table 75 – AEPC data modelling example .....   | 131 |
| Table 76 – Use case: DC Line fault recovery sequence .....                                 | 134 |
| Table 77 – Use case: DC Yard configuration.....  | 137 |
| Table 78 – Use case: Coordinated mode switchover .....                                     | 139 |
| Table 79 – Use case: Function mode switchover.....   | 141 |
| Table 80 – Use case: Tap changer control and supervision.....                              | 145 |
| Table 81 – Use case: Control by external reference .....                                   | 148 |
| Table 82 – Normative abbreviations for data object names .....                             | 149 |
| Table 83 – Data objects of FACTSandPowerConversionLN.....                                  | 152 |
| Table 84 – Data objects of ReactiveComponentInterfaceLN .....                              | 153 |
| Table 85 – Data objects of EmergencyPowerControl_PowerRunUpRunBackLN .....                 | 154 |
| Table 86 – Data objects of ARCOExt .....   | 157 |
| Table 87 – Data objects of AFLK.....   | 159 |
| Table 88 – Data objects of AMSR .....  | 160 |
| Table 89 – Data objects of APOD .....  | 162 |
| Table 90 – Data objects of AEPC .....  | 163 |



|  |     |
|--|-----|
| Table 91 – Data objects of ARUB.....   | 165 |
| Table 92 – Data objects of ASEQ.....   | 166 |
| Table 93 – Data objects of ATCCExt.....                                      | 168 |
| Table 94 – Data objects of ARPC.....   | 171 |
| Table 95 – Data objects of AVCOExt.....                                      | 172 |
| Table 96 – Data objects of CCGRExt.....                                      | 175 |
| Table 97 – Data objects of CCAP.....   | 177 |
| Table 98 – Data objects of CJCL.....   | 178 |
| Table 99 – Data objects of CFPC.....   | 180 |
| Table 100 – Data objects of CREL.....  | 183 |
| Table 101 – Data objects of FFUN.....  | 184 |
| Table 102 – Data objects of PLFR.....  | 187 |
| Table 103 – Data objects of PMHE.....  | 189 |
| Table 104 – Data objects of PMHT.....  | 190 |
| Table 105 – Data objects of PMOV.....  | 192 |
| Table 106 – Data objects of PFPE.....  | 193 |
| Table 107 – Data objects of RBPF.....  | 195 |
| Table 108 – Data objects of RRIN.....  | 196 |
| Table 109 – Data objects of SCND.....  | 199 |
| Table 110 – Data objects of SFLW.....  | 200 |
| Table 111 – Data objects of SFPE.....  | 201 |
| Table 112 – Data objects of SPES.....  | 203 |
| Table 113 – Data objects of TCND.....  | 205 |
| Table 114 – Data objects of XFPE.....  | 207 |
| Table 115 – Data objects of XDCC.....  | 209 |
| Table 116 – Data objects of ZCONExt.....                                     | 211 |
| Table 117 – Data objects of ZHAF.....  | 213 |
| Table 118 – Data objects of ZLINEExt.....                                    | 215 |
| Table 119 – Data objects of ZMOV.....  | 217 |
| Table 120 – Data objects of ZTCRExt.....                                     | 218 |
| Table 121 – Data objects of ZCAPEExt.....                                    | 220 |
| Table 122 – Data objects of ZREAExt.....                                     | 221 |
| Table 123 – Attributes defined on classes of LogicalNodes_90_14 package..... | 222 |
| Table 124 – Literals of ActivePowerModKind.....                              | 232 |
| Table 125 – Literals of AutoReinsertionKind.....                             | 232 |
| Table 126 – Literals of ChargingDCCircuitStateKind.....                      | 233 |
| Table 127 – Literals of ConfigurationDCCircuitStateKind.....                 | 233 |
| Table 128 – Literals of ConnectionDCStateKind.....                           | 233 |
| Table 129 – Literals of ConverterTypKind.....                                | 234 |
| Table 130 – Literals of EPCModKind.....                                      | 234 |
| Table 131 – Literals of EPCTypKind.....                                      | 234 |
| Table 132 – Literals of ForcedOperationControlModKind.....                   | 235 |
| Table 133 – Literals of GenerationDCStateKind.....                           | 235 |

|   |     |
|---|-----|
| Table 134 – Literals of HarmonicFilterTypKind .....               | 235 |
| Table 135 – Literals of OperationCommandKind .....                | 236 |
| Table 136 – Literals of OperationModKind .....                    | 236 |
| Table 137 – Literals of OperationStateKind .....                  | 236 |
| Table 138 – Literals of PowerDirectionalModKind .....             | 237 |
| Table 139 – Literals of ReactivePowerModKind .....                | 237 |
| Table 140 – Literals of RubModKind .....                          | 237 |
| Table 141 – Literals of RubTypKind .....                          | 238 |
| Table 142 – Literals of SequenceStateKind.....                    | 238 |
| Table 143 – Literals of ThyristorBranchFunctionKind .....         | 238 |
| Table B.1 – Suggested modelling of measured and meter values..... | 247 |

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

### COMMUNICATION NETWORKS AND SYSTEMS FOR POWER UTILITY AUTOMATION –

#### **Part 90-14: Using IEC 61850 for FACTS (flexible alternate current transmission systems), HVDC (high voltage direct current) transmission and power conversion data modelling**

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TR 61850-90-14 has been prepared by working group 10: Power system IED communication and associated data models, of IEC technical committee 57: Power systems management and associated information exchange. It is a Technical Report.

The text of this Technical Report is based on the following documents:

|             |                  |
|-------------|------------------|
| Draft       | Report on voting |
| 57/2232/DTR | 57/2273/RVDTR    |

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs). The main document types developed by IEC are described in greater detail at [www.iec.ch/standardsdev/publications](http://www.iec.ch/standardsdev/publications).

The language used for the development of this Technical Report is English.

A list of all parts in the IEC 61850 series, published under the general title *Communication networks and systems for power utility automation*, can be found on the IEC website.

This IEC standard includes Code Components i.e. components that are intended to be directly processed by a computer.

Such content is any text found between the markers and, or otherwise is clearly labelled in this standard as a Code Component.

The purchase of this IEC standard carries a copyright license for the purchaser to sell software containing Code Components from this standard to end users either directly or via distributors, subject to IEC software licensing conditions, which can be found at: <http://www.iec.ch/CCv1>

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

## INTRODUCTION

The IEC 61850 series was established to focus on the main primary equipment and functionality of conventional AC substations. By now it has been widely deployed and has become state of the art in that area.

Soon after, ambitions emerged to make IEC 61850 applicable to a largely widened range of equipment and functionality. Even completely new domains, like wind or hydro power generation, have created extensions to the series in order to match their applications.

Thanks to the very generic basic information and communication structures of IEC 61850 and the integrated services provided, most domain requirements can be easily adopted and fulfilled with IEC 61850 core functionality. Most of the extension work thus just needs to focus on creating a domain specific data modelling, which allows the semantic description of domain specific signals.

Due to the latest boom in deploying an exponentially increasing number of power electronics and semiconductor based equipment directly in the area of medium, high and ultra-high voltage transmission networks, the call for integrating those direct current related processes and control systems into IEC 61850 is only logical and consecutive.

Two main groups of DC based types of applications exist: FACTS devices (shunt and series connected) that mainly influence the network at a definite point of connection and Power Converters (e.g. HVDC, SFC) that additionally allow the transmission of active power between two different points of connection.

The benefits of those technologies are clear: as methods to influence conventional AC networks are limited, DC based technologies provide the possibility to actively adjust power flow and network parameters like frequency and voltage within just milliseconds. They help to support network stability, performance and quality, increase transmission capacity. They enable transmission tasks that would otherwise be technically borderline or impossible, moreover doing so mostly with unprecedented efficiency respectively low losses.

FACTS and Power Conversion are thus indispensable to secure power supply and represent a vital component within the backbone of efficient, reliable and resilient future smart grids. This technical report finally enables those technologies to also become an integral part of the IEC 61850 world.

## COMMUNICATION NETWORKS AND SYSTEMS FOR POWER UTILITY AUTOMATION –

### Part 90-14: Using IEC 61850 for FACTS (flexible alternate current transmission systems), HVDC (high voltage direct current) transmission and power conversion data modelling

#### 1 Scope

This part of IEC 61850, which is a technical report, specifies the information model of devices and functions related to systems of power utility automation, specifically related to FACTS (Flexible AC Transmission Systems) and Power Conversion applications.

The IEC 61850-90-14 information model standard utilizes existing IEC 61850-7-4 logical nodes where possible, but also defines specific logical nodes where needed.

Specifically, the scope of this document:

- Covers communication between control system of FACTS, HVDC and Power Conversion and SCADA and HMI systems
- Includes the data model for FACTS, HVDC and Power conversion devices
- Does not cover Protection relays
- Does not cover process bus
- Does not cover valve communication

#### 1.1 Namespace name and version

This new subclause is mandatory for any IEC 61850 namespace (as defined by IEC 61850-7-1:2011).

Table 1 shows all attributes of (Tr)IEC 61850-90-14:2020A namespace.

**Table 1 – Attributes of (Tr)IEC 61850-90-14:2020A namespace**

| Attribute                            | Content   |
|--------------------------------------|---|
| <b>Namespace nameplate</b>           |   |
| Namespace Identifier                 | (Tr)IEC 61850-90-14   |
| Version                              | 2020  |
| Revision                             | A   |
| Release                              | 3   |
| Full Namespace Name                  | (Tr)IEC 61850-90-14:2020A   |
| Namespace Type                       | transitional  |
| <b>Namespace dependencies</b>        |   |
| extends                              | IEC 61850-7-4:2007B version:2007 revision:B   |
| <b>Namespace transitional status</b> |   |
| Future handling of namespace content | The name space (Tr)IEC 61850-90-14:2020A is considered as "transitional" since the models are expected to be included in further editions of IEC 61850-7-4xx. Potential extensions/modifications may happen if/when the models are moved to the International Standard status |

The table below provides an overview of all published versions of this namespace.

| Edition     | Publication date | Webstore                | Namespace                |
|-------------|------------------|-------------------------|--------------------------|
| Edition 1.0 | 2020-xx          | IEC TR 61850-90-14:2020 | (Tr)IEC 61850-90-14:2020 |

Table 2 shows all tracking information of (Tr)IEC 61850-90-14:2020A namespace building-up.

**Table 2 – Tracking information of (Tr)IEC 61850-90-14:2020A namespace building-up**

| Attribute   | Content   |
|---|---|
| <b>Namespace IEC specific information</b>                               |   |
| Version of the UML model used for generating the document (informative) | wg10built7-wg18built5-wg17built6-jwg25built2-tc17built1-tc38built1_20210122.eap |
| Date of the UML model used for generating the document (informative)    | 2021-01-22  |
| Autogeneration software name and version(informative)                   | j61850DocBuilder 01v12 based on jCleanCim 02v02-NS beta5                        |

## 1.2 Code Component distribution

The Code Components are in light and full version:

- The full version is named: *IEC\_TR\_61850-90-14.NSD.2020A.Full*. It contains definition of the whole data model defined in this standard with the documentation associated and access is restricted to purchaser of this part

- The light version is named: *IEC\_TR\_61850-90-14.NSD.2020A3.Light*. It does not contain any documentations but contains the whole data model as per full version, and this light version is freely accessible on the IEC website for download at: <http://www.iec.ch/tc57/supportdocuments>, but the usage remains under the licensing conditions.

The Code Components for IEC 61850 data models are formatted in compliance with the NSD format defined by the standard IEC 61850-7-7. Each Code Component is a ZIP package containing:

- the electronic representation of the Code Component itself (possibly multiple files),
- the grammar files (XSD) enabling to check the consistency of the associated files against the defined version of NSD, but as well against the IEC 61850 flexibility rules in case of private extensions
- a file describing the content of the package (IECManifest.xml)

The IECManifest file contains different sections giving information on:

- The copyright notice
- The identification of the code component
- The publication related to the code component
- The list of the electronic files which compose the code component
- An optional list of history files to track changes during the evolution process of the code component

The life cycle of a code component is not restricted to the life cycle of the related publication. The publication life cycle goes through two stages, Version (corresponding to an edition) and Revision (corresponding to an amendment). A third publication stage (Release) allows publication of Code Component in case of urgent fixes of InterOp Tissues, thus without need to publish an amendment.

Consequently new release(s) of the Code Component may be released, which supersede(s) the previous release, and will be distributed through the IEC TC57 web site at: <http://www.iec.ch/tc57/supportdocuments>.

The latest version/release of the document will be found by selecting the file named *IEC\_TR\_61850-90-14.NSD.{VersionStateInfo}.Light* with the filed VersionStateInfo of the highest value.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC TS 61850-2, *Communication networks and systems for power utility automation – Part 2: Glossary*

IEC 61850-5:2013, *Communication networks and systems for power utility automation – Part 5: Communication requirements for functions and device models*  
IEC 61850-5:2013/AMD1:2021

IEC 61850-6:2009, *Communication networks and systems for power utility automation – Part 6: Configuration description language for communication in electrical substations related to IEDs*  
IEC 61850-6:2009/AMD1:2018



IEC 61850-7-2:2010, *Communication networks and systems for power utility automation – Part 7-2: Basic information and communication structure – Abstract communication service interface (ACSI)*

IEC 61850-7-2:2010/AMD1:2020

IEC 61850-7-3:2010, *Communication networks and systems for power utility automation – Part 7-3: Basic communication structure – Common data classes*

IEC 61850-7-3:2010/AMD1:2020

IEC 61850-7-4:2010, *Communication networks and systems for power utility automation – Part 7-4: Basic communication structure – Compatible logical node classes and data object classes*

IEC 61850-7-4:2010/AMD1:2020

IEC 60633:2019, *High-voltage direct current (HVDC) transmission – Vocabulary*

IEC TR 61850-7-500:2017, *Communication networks and systems for power utility automation – Part 7-500: Basic information and communication structure – Use of logical nodes for modeling application functions and related concepts and guidelines for substations*