

This is a preview - click here to buy the full publication



IEC TR 62977-1-31

Edition 1.1 2022-03
CONSOLIDATED VERSION

INTERNATIONAL STANDARD



**Electronic displays –
Part 1-31: Generic – Practical information on the use of light measuring devices**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.120; 31.260

ISBN 978-2-8322-4572-9

Warning! Make sure that you obtained this publication from an authorized distributor.

REDLINE VERSION



Electronic displays – Part 1-31: Generic – Practical information on the use of light measuring devices



CONTENTS

FOREWORD	7
INTRODUCTION	9
INTRODUCTION to Amendment 1	9
1 Scope	10
2 Normative references	10
3 Terms, definitions, and abbreviated terms	10
3.1 Terms and definitions	10
3.2 Abbreviated terms	11
4 General information on LMDs for photometry and colorimetry	11
4.1 General	11
4.2 Photometry and colorimetry for electronic displays	11
4.3 LMDs for luminance and chromaticity measurements	12
4.3.1 Configuration of LMDs	12
4.3.2 Input optics of LMDs	15
4.3.3 Electronic system of LMDs	15
4.3.4 Calibration of LMDs	16
4.3.5 Maintenance of LMDs	16
4.4 Setup conditions for measurement	16
4.4.1 LMDs	16
4.4.2 DUTs	16
4.4.3 Environment	16
5 Influence of LMD properties on luminance and chromaticity measurements	16
5.1 General	16
5.2 Repeatability	17
5.2.1 General	17
5.2.2 Example of the repeatability of an LMD	17
5.3 Accuracy	18
5.3.1 General	18
5.3.2 Example of the accuracy of an LMD	18
5.3.3 Linearity	18
5.3.4 Range change	19
5.4 Luminance range	19
5.5 Spectral properties of the spectroradiometer	19
5.5.1 General	19
5.5.2 Wavelength accuracy and spectral bandwidth	19
5.6 Spectral properties of the filter-type luminance meter and colorimeter	26
5.6.1 General	26
5.6.2 Spectral responsivity	27
5.6.3 Methods to reduce the measurement difference	30
5.7 Angular response of LMDs	31
5.7.1 General	31
5.7.2 Subtended angles	31
5.7.3 Consideration of the input optics	32
5.8 Measurement field	33
5.8.1 General	33
5.8.2 Number of pixels within the measurement field	34

5.9	Polarization.....	34
5.9.1	General	34
5.9.2	Polarization dependence of LMDs.....	35
5.10	Temporal synchronization	36
5.10.1	General	36
5.10.2	Temporal synchronization of the LMD and DUT	36
6	Influence of LMD properties on measurements of the optical characteristics of electronic displays	37
6.1	General.....	37
6.2	Contrast ratio	37
6.2.1	General	37
6.2.2	Calculated influence of LMD properties on the contrast ratio measurements	37
6.3	Electro-optical transfer function (EOTF)	40
6.3.1	General	40
6.3.2	Calculated influence of the LMD properties on the EOTF measurements	40
6.4	Chromaticity gamut area	41
6.4.1	General	41
6.4.2	Calculated influence of LMD properties on the chromaticity gamut area measurements	41
6.5	Viewing direction characteristics	43
6.5.1	General	43
6.5.2	Calculated influence of the LMD properties on the viewing direction characteristics measurements	43
6.5.3	Measurement field at an oblique direction	45
6.6	Spatial uniformity	46
6.6.1	General	46
6.6.2	Calculated influence of LMD properties on uniformity and non-uniformity measurements	46
6.7	Response time	48
6.7.1	General	48
6.7.2	Measurement of the response time	48
6.8	Flicker.....	51
6.8.1	General	51
6.8.2	Measurement method of the flicker	51
6.8.3	Low-pass filter of LMDs	52
Annex A (informative)	Photometry and colorimetry	54
A.1	General.....	54
A.2	Photometry	54
A.3	Colorimetry	54
A.3.1	General	54
A.3.2	Standard colorimetric observer	55
A.3.3	Tristimulus values.....	55
A.3.4	Chromaticity diagram and colour space	55
Annex B (informative)	Method for reducing the measurement difference of colorimeters	58
B.1	General.....	58
B.2	Matrix calibration methods for colorimeters	58
B.2.1	Matrix calibration process 1: RGB calibration.....	58
B.2.2	Matrix calibration process 2: RGBW calibration	59

Annex C (informative) Input data in Clause 5 and Clause 6, and calculation methods in 5.8 and 6.5.....	61
C.1 General.....	61
C.2 Characteristics of DUTs	61
C.2.1 Spectral radiances of the DUTs	61
C.2.2 Directional characteristic of the DUT.....	62
C.2.3 Temporal modulation characteristics of the DUT	63
C.2.4 EOTF characteristics of the DUTs.....	63
C.2.5 Uniformity characteristics of the DUTs	64
C.3 Characteristics of the filter-type LMDs	65
C.3.1 Spectral responsivities of the filter-type LMDs	65
C.3.2 Specifications of filter-type LMDs.....	67
C.4 Influence of the number of pixels within the measurement field	69
C.5 Validity of the viewing direction dependence obtained by a simplified method	70
Annex D (informative) Instabilities of DUTs in measurement	72
D.1 General.....	72
D.2 DUT instabilities.....	72
Annex E (informative) Influence of spectral stray light and spectral bandwidth on chromaticity measurements of narrow spectral linewidth light	74
E.1 General.....	74
E.2 Example experimental data on spectral stray light.....	74
E.2.1 Measurement method and conditions.....	74
E.2.2 Measurement and calculation data.....	74
E.2.3 Calculation of chromaticity with increasing background level	76
E.3 Influence of spectral bandwidth.....	77
E.3.1 Calculation of chromaticity with increasing spectral bandwidth.....	77
E.3.2 Additional information on spectral properties of spectroradiometers.....	77
Bibliography.....	79
Figure 1 – Block diagrams of three types of LMDs	13
Figure 2 – Example of configurations for the input optics and detector.....	14
Figure 3 – Example of input optics for the luminance meters.....	15
Figure 4 – Block diagram of a typical electronic system	15
Figure 5 – Examples of the repeatability of an LMD as a function of luminance.....	17
Figure 6 – Examples of the accuracy of an LMD as a function of luminance.....	18
Figure 7 – Calculated relative luminance difference as a function of wavelength error	21
Figure 8 – Calculated relative luminance difference as a function of spectral bandwidth	22
Figure 9 – Calculated chromaticity differences as a function of wavelength error	24
Figure 10 – Calculated chromaticity differences as a function of spectral bandwidth	26
Figure 11 – Calculated relative luminance difference as a function of f_1'	28
Figure 12 – Calculated chromaticity differences as a function of f_1' , xyz	30
Figure 13 – Angular aperture and measurement field angle	32
Figure 14 – Calculated relative luminance difference and chromaticity difference as a function of the angular aperture	32
Figure 15 – Diagram of light rays in object space telecentric and non-telecentric optical design.....	33

Figure 16 – Calculated chromaticity difference as a function of the number of pixels	34
Figure 17 – Measured luminance variation as a function of the rotation angle of the polarizer	35
Figure 18 – Calculated relative luminance differences as a function of sampling period	37
Figure 19 – Total measurement times for 0,3 % repeatability (2σ) in three LMDs	41
Figure 20 – Calculated relative difference, ΔGA_{xy} , by spectroradiometers	42
Figure 21 – Calculated relative difference, ΔGA_{xy} , by colorimeters	43
Figure 22 – Cone of light rays for calculating the tristimulus values measured by an LMD with the angular aperture, α , and an optical axis at an inclination angle, θ_{LMD}	44
Figure 23 – Calculated luminance and chromaticity dependence as a function of the inclination angle for the 2°, 6°, and 10° angular apertures.....	45
Figure 24 – Measurement field and test pattern	46
Figure 25 – Calculated non-uniformity difference by the filter-type colorimeters	48
Figure 26 – Measurement setups for response time measurements	49
Figure 27 – Response curves measured at different sampling rates	49
Figure 28 – Measured response subjected to various low-pass filterings.....	50
Figure 29 – Measured response curves switched from the 10 % to 90 % level	51
Figure 30 – Schematic measured temporal luminance modulation of the LCD with a common voltage offset	52
Figure 31 – Conceptual pseudo-temporal luminance modulation	53
Figure 32 – Simulated luminance modulations with and without high frequency noise	53
Figure C.1 – Spectral radiances.....	62
Figure C.2 – Inclination angle dependence	63
Figure C.3 – Temporal modulation of the luminance	63
Figure C.4 – EOTF characteristics	64
Figure C.5 – Spectral responsivity of the colorimeter	67
Figure C.6 – Repeatability of three LMD models	68
Figure C.7 – Three positions of a circular measurement field relative to the RGB stripes	69
Figure C.8 – Configuration to measure DUT emission by the LMD at the inclination angle, θ_{LMD}	70
Figure C.9 – Inclination angle dependence calculated by two methods using an LMD with an angular aperture of 10°	71
Figure D.1 – Changes of luminance and chromaticity after switching the grey levels.....	72
Figure D.2 – Changes of luminance after switching from the black to grey level.....	73
Figure E.1 – Measured relative spectral irradiance for each primary input signal.....	75
Figure E.2 – Calculated CIE 1931 chromaticities of simulated monochromatic spectra with various wavelengths with increasing background levels (signal-to-noise ratios)	76
Figure E.3 – Calculated CIE 1931 chromaticities of simulated monochromatic spectra for various wavelengths with increasing spectral bandwidths	78
Table 1 – DUT characteristics for the calculations.....	38
Table 2 – Calculated results of the contrast ratio by three LMDs	39
Table 3 – Calculated durations of the EOTF measurements	41
Table 4 – Chromaticity gamut area of three DUTs.....	42

Table 5 – Non-uniformity of DUTs	47
Table 6 – Rise times calculated from a measured response subjected to various low-pass filterings	50
Table 7 – Rise times measured by LMDs of various $V(\lambda)$ fidelities	51
Table C.1 – Measured luminance and chromaticity at the nine positions of DUT-1	64
Table C.2 – Measured luminance and chromaticity at the nine positions of DUT-2	65
Table C.3 – Specifications of filter-type LMDs	68
Table D.1 – Luminance and chromaticity transition	72
Table D.2 – Luminance changes in two measurements	73
Table E.1 – Calculated CIE 1931 chromaticity differences between measurements without and with spectral stray light correction	75

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTRONIC DISPLAYS –

Part 1-31: Generic – Practical information on the use of light measuring devices

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC TR 62977-1-31 edition 1.1 contains the first edition (2021-04) [documents 110/1258/DTR and 110/1281A/RVDTR] and its amendment 1 (2022-03) [documents 110/1380/DTR and 110/1404A/DVDTR].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

IEC TR 62977-1-31 has been prepared by IEC technical committee 110: Electronic displays. It is a Technical Report.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 62977 series, published under the general title *Electronic displays*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under webstore.iec.ch in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Measurements of the optical characteristics of electronic displays are primarily affected by three factors: measuring procedures, displays (devices under test: DUTs), and light measuring devices (LMDs), for which there are many international standards supporting consistent and comparable measurements. Most of them, however, provide only limited information on LMDs, making it difficult to appropriately select and use the LMD for the measurement objective. The purpose of this document is to provide best practices and suggestions which are missing in the standards.

This document addresses how the major properties of a typical LMD affect the measurement results. It is often impractical and unnecessary to consider the influences of all properties of LMDs and all characteristics of DUTs as well as their interactions and influences on the measurement results. Therefore, the multiple interaction effects that exist are beyond the scope of this document. Due to the rapid innovation and abundance of LMDs, covering all types of LMDs is also outside the objectives of this document.

INTRODUCTION to Amendment 1

This document provides additional information to IEC TR 62977-1-31:2021 regarding the influence of spectral stray light and spectral bandwidth of a spectroradiometer on chromaticity measurements. It is described in Annex E.

This document also provides the corrections of editorial errors of IEC TR 62977-1-31:2021. The corrections are:

- Typos are fixed:
 - “fiber” and “ $x(\lambda)$, $y(\lambda)$, $z(\lambda)$ ” is replaced with “fibre” and “ $\bar{x}(\lambda)$, $\bar{y}(\lambda)$, $\bar{z}(\lambda)$ ”, respectively in Figure 2,
 - “(%)” in the label of vertical axis is removed in Figure 9, Figure 10, and Figure 12,
 - “0” label of the tick mark of vertical axis is replaced with “1” in Figure C.4.
- The lists for Formula (A.1) and Formula (B.1) are aligned.

ELECTRONIC DISPLAYS –

Part 1-31: Generic – Practical information on the use of light measuring devices

1 Scope

This part of IEC 62977 provides practical information on light measuring devices (luminance meters, colorimeters, and spectroradiometers) with luminance measuring optics for the characterization of electronic displays.

2 Normative references

There are no normative references in this document.

FINAL VERSION



Electronic displays – Part 1-31: Generic – Practical information on the use of light measuring devices



CONTENTS

FOREWORD	7
INTRODUCTION	9
INTRODUCTION to Amendment 1	9
1 Scope	10
2 Normative references	10
3 Terms, definitions, and abbreviated terms	10
3.1 Terms and definitions	10
3.2 Abbreviated terms	11
4 General information on LMDs for photometry and colorimetry	11
4.1 General	11
4.2 Photometry and colorimetry for electronic displays	11
4.3 LMDs for luminance and chromaticity measurements	12
4.3.1 Configuration of LMDs	12
4.3.2 Input optics of LMDs	14
4.3.3 Electronic system of LMDs	14
4.3.4 Calibration of LMDs	15
4.3.5 Maintenance of LMDs	15
4.4 Setup conditions for measurement	15
4.4.1 LMDs	15
4.4.2 DUTs	15
4.4.3 Environment	15
5 Influence of LMD properties on luminance and chromaticity measurements	15
5.1 General	15
5.2 Repeatability	16
5.2.1 General	16
5.2.2 Example of the repeatability of an LMD	16
5.3 Accuracy	17
5.3.1 General	17
5.3.2 Example of the accuracy of an LMD	17
5.3.3 Linearity	17
5.3.4 Range change	18
5.4 Luminance range	18
5.5 Spectral properties of the spectroradiometer	18
5.5.1 General	18
5.5.2 Wavelength accuracy and spectral bandwidth	18
5.6 Spectral properties of the filter-type luminance meter and colorimeter	23
5.6.1 General	23
5.6.2 Spectral responsivity	24
5.6.3 Methods to reduce the measurement difference	26
5.7 Angular response of LMDs	27
5.7.1 General	27
5.7.2 Subtended angles	27
5.7.3 Consideration of the input optics	28
5.8 Measurement field	29
5.8.1 General	29
5.8.2 Number of pixels within the measurement field	30

5.9	Polarization.....	30
5.9.1	General	30
5.9.2	Polarization dependence of LMDs.....	31
5.10	Temporal synchronization	32
5.10.1	General	32
5.10.2	Temporal synchronization of the LMD and DUT	32
6	Influence of LMD properties on measurements of the optical characteristics of electronic displays	33
6.1	General.....	33
6.2	Contrast ratio	33
6.2.1	General	33
6.2.2	Calculated influence of LMD properties on the contrast ratio measurements	33
6.3	Electro-optical transfer function (EOTF)	36
6.3.1	General	36
6.3.2	Calculated influence of the LMD properties on the EOTF measurements	36
6.4	Chromaticity gamut area	37
6.4.1	General	37
6.4.2	Calculated influence of LMD properties on the chromaticity gamut area measurements	37
6.5	Viewing direction characteristics	39
6.5.1	General	39
6.5.2	Calculated influence of the LMD properties on the viewing direction characteristics measurements	39
6.5.3	Measurement field at an oblique direction	41
6.6	Spatial uniformity	42
6.6.1	General	42
6.6.2	Calculated influence of LMD properties on uniformity and non-uniformity measurements	42
6.7	Response time	44
6.7.1	General	44
6.7.2	Measurement of the response time	44
6.8	Flicker.....	47
6.8.1	General	47
6.8.2	Measurement method of the flicker	47
6.8.3	Low-pass filter of LMDs	48
Annex A (informative)	Photometry and colorimetry	50
A.1	General.....	50
A.2	Photometry	50
A.3	Colorimetry	50
A.3.1	General	50
A.3.2	Standard colorimetric observer	51
A.3.3	Tristimulus values.....	51
A.3.4	Chromaticity diagram and colour space	51
Annex B (informative)	Method for reducing the measurement difference of colorimeters	54
B.1	General.....	54
B.2	Matrix calibration methods for colorimeters	54
B.2.1	Matrix calibration process 1: RGB calibration.....	54
B.2.2	Matrix calibration process 2: RGBW calibration	55

Annex C (informative) Input data in Clause 5 and Clause 6, and calculation methods in 5.8 and 6.5.....	57
C.1 General.....	57
C.2 Characteristics of DUTs	57
C.2.1 Spectral radiances of the DUTs	57
C.2.2 Directional characteristic of the DUT.....	57
C.2.3 Temporal modulation characteristics of the DUT	58
C.2.4 EOTF characteristics of the DUTs.....	58
C.2.5 Uniformity characteristics of the DUTs	59
C.3 Characteristics of the filter-type LMDs	60
C.3.1 Spectral responsivities of the filter-type LMDs	60
C.3.2 Specifications of filter-type LMDs.....	62
C.4 Influence of the number of pixels within the measurement field	64
C.5 Validity of the viewing direction dependence obtained by a simplified method	65
Annex D (informative) Instabilities of DUTs in measurement	67
D.1 General.....	67
D.2 DUT instabilities.....	67
Annex E (informative) Influence of spectral stray light and spectral bandwidth on chromaticity measurements of narrow spectral linewidth light	69
E.1 General.....	69
E.2 Example experimental data on spectral stray light.....	69
E.2.1 Measurement method and conditions.....	69
E.2.2 Measurement and calculation data.....	69
E.2.3 Calculation of chromaticity with increasing background level	71
E.3 Influence of spectral bandwidth.....	72
E.3.1 Calculation of chromaticity with increasing spectral bandwidth.....	72
E.3.2 Additional information on spectral properties of spectroradiometers.....	72
Bibliography.....	74
Figure 1 – Block diagrams of three types of LMDs	13
Figure 2 – Example of configurations for the input optics and detector.....	13
Figure 3 – Example of input optics for the luminance meters.....	14
Figure 4 – Block diagram of a typical electronic system	14
Figure 5 – Examples of the repeatability of an LMD as a function of luminance.....	16
Figure 6 – Examples of the accuracy of an LMD as a function of luminance.....	17
Figure 7 – Calculated relative luminance difference as a function of wavelength error	20
Figure 8 – Calculated relative luminance difference as a function of spectral bandwidth	21
Figure 9 – Calculated chromaticity differences as a function of wavelength error	22
Figure 10 – Calculated chromaticity differences as a function of spectral bandwidth	23
Figure 11 – Calculated relative luminance difference as a function of f_1'	25
Figure 12 – Calculated chromaticity differences as a function of f_1' , xyz	26
Figure 13 – Angular aperture and measurement field angle	28
Figure 14 – Calculated relative luminance difference and chromaticity difference as a function of the angular aperture	28
Figure 15 – Diagram of light rays in object space telecentric and non-telecentric optical design.....	29

Figure 16 – Calculated chromaticity difference as a function of the number of pixels	30
Figure 17 – Measured luminance variation as a function of the rotation angle of the polarizer	31
Figure 18 – Calculated relative luminance differences as a function of sampling period	33
Figure 19 – Total measurement times for 0,3 % repeatability (2σ) in three LMDs	37
Figure 20 – Calculated relative difference, ΔGA_{xy} , by spectroradiometers	38
Figure 21 – Calculated relative difference, ΔGA_{xy} , by colorimeters	39
Figure 22 – Cone of light rays for calculating the tristimulus values measured by an LMD with the angular aperture, α , and an optical axis at an inclination angle, θ_{LMD}	40
Figure 23 – Calculated luminance and chromaticity dependence as a function of the inclination angle for the 2°, 6°, and 10° angular apertures.....	41
Figure 24 – Measurement field and test pattern	42
Figure 25 – Calculated non-uniformity difference by the filter-type colorimeters	44
Figure 26 – Measurement setups for response time measurements	45
Figure 27 – Response curves measured at different sampling rates	45
Figure 28 – Measured response subjected to various low-pass filterings.....	46
Figure 29 – Measured response curves switched from the 10 % to 90 % level	47
Figure 30 – Schematic measured temporal luminance modulation of the LCD with a common voltage offset.....	48
Figure 31 – Conceptual pseudo-temporal luminance modulation	49
Figure 32 – Simulated luminance modulations with and without high frequency noise	49
Figure C.1 – Spectral radiances.....	57
Figure C.2 – Inclination angle dependence	58
Figure C.3 – Temporal modulation of the luminance	58
Figure C.4 – EOTF characteristics	59
Figure C.5 – Spectral responsivity of the colorimeter	62
Figure C.6 – Repeatability of three LMD models	63
Figure C.7 – Three positions of a circular measurement field relative to the RGB stripes	64
Figure C.8 – Configuration to measure DUT emission by the LMD at the inclination angle, θ_{LMD}	65
Figure C.9 – Inclination angle dependence calculated by two methods using an LMD with an angular aperture of 10°	66
Figure D.1 – Changes of luminance and chromaticity after switching the grey levels.....	67
Figure D.2 – Changes of luminance after switching from the black to grey level.....	68
Figure E.1 – Measured relative spectral irradiance for each primary input signal.....	70
Figure E.2 – Calculated CIE 1931 chromaticities of simulated monochromatic spectra with various wavelengths with increasing background levels (signal-to-noise ratios)	71
Figure E.3 – Calculated CIE 1931 chromaticities of simulated monochromatic spectra for various wavelengths with increasing spectral bandwidths	73
Table 1 – DUT characteristics for the calculations.....	34
Table 2 – Calculated results of the contrast ratio by three LMDs	35
Table 3 – Calculated durations of the EOTF measurements	37
Table 4 – Chromaticity gamut area of three DUTs.....	38

Table 5 – Non-uniformity of DUTs	43
Table 6 – Rise times calculated from a measured response subjected to various low-pass filterings	46
Table 7 – Rise times measured by LMDs of various $V(\lambda)$ fidelities	47
Table C.1 – Measured luminance and chromaticity at the nine positions of DUT-1	59
Table C.2 – Measured luminance and chromaticity at the nine positions of DUT-2	60
Table C.3 – Specifications of filter-type LMDs	63
Table D.1 – Luminance and chromaticity transition	67
Table D.2 – Luminance changes in two measurements	68
Table E.1 – Calculated CIE 1931 chromaticity differences between measurements without and with spectral stray light correction	70

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTRONIC DISPLAYS –

Part 1-31: Generic – Practical information on the use of light measuring devices

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC TR 62977-1-31 edition 1.1 contains the first edition (2021-04) [documents 110/1258/DTR and 110/1281A/RVDTR] and its amendment 1 (2022-03) [documents 110/1380/DTR and 110/1404A/DVDTR].

This Final version does not show where the technical content is modified by amendment 1. A separate Redline version with all changes highlighted is available in this publication.

IEC TR 62977-1-31 has been prepared by IEC technical committee 110: Electronic displays. It is a Technical Report.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 62977 series, published under the general title *Electronic displays*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under webstore.iec.ch in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Measurements of the optical characteristics of electronic displays are primarily affected by three factors: measuring procedures, displays (devices under test: DUTs), and light measuring devices (LMDs), for which there are many international standards supporting consistent and comparable measurements. Most of them, however, provide only limited information on LMDs, making it difficult to appropriately select and use the LMD for the measurement objective. The purpose of this document is to provide best practices and suggestions which are missing in the standards.

This document addresses how the major properties of a typical LMD affect the measurement results. It is often impractical and unnecessary to consider the influences of all properties of LMDs and all characteristics of DUTs as well as their interactions and influences on the measurement results. Therefore, the multiple interaction effects that exist are beyond the scope of this document. Due to the rapid innovation and abundance of LMDs, covering all types of LMDs is also outside the objectives of this document.

INTRODUCTION to Amendment 1

This document provides additional information to IEC TR 62977-1-31:2021 regarding the influence of spectral stray light and spectral bandwidth of a spectroradiometer on chromaticity measurements. It is described in Annex E.

This document also provides the corrections of editorial errors of IEC TR 62977-1-31:2021. The corrections are:

- Typos are fixed:
 - “fiber” and “ $x(\lambda)$, $y(\lambda)$, $z(\lambda)$ ” is replaced with “fibre” and “ $\bar{x}(\lambda)$, $\bar{y}(\lambda)$, $\bar{z}(\lambda)$ ”, respectively in Figure 2,
 - “(%)” in the label of vertical axis is removed in Figure 9, Figure 10, and Figure 12,
 - “0” label of the tick mark of vertical axis is replaced with “1” in Figure C.4.
- The lists for Formula (A.1) and Formula (B.1) are aligned.

ELECTRONIC DISPLAYS –

Part 1-31: Generic – Practical information on the use of light measuring devices

1 Scope

This part of IEC 62977 provides practical information on light measuring devices (luminance meters, colorimeters, and spectroradiometers) with luminance measuring optics for the characterization of electronic displays.

2 Normative references

There are no normative references in this document.