



TECHNICAL SPECIFICATION

**Recommendations for renewable energy and hybrid systems for rural electrification –
Part 9-5: Integrated systems – Laboratory evaluation of stand-alone renewable energy products for rural electrification**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 27.160

ISBN 978-2-8322-5693-0

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	15
INTRODUCTION.....	18
1 Scope.....	19
2 Normative references	19
3 Terms and definitions	21
4 Product components and characteristics.....	25
4.1 Components	25
4.1.1 Overview	25
4.1.2 Component categories.....	26
4.1.3 Lighting parts definitions.....	28
4.1.4 Appliance definitions.....	29
4.1.5 Additional system elements	30
4.2 System measurements and observations	30
4.2.1 General	30
4.2.2 Product design, manufacture, and marketing aspects	30
4.2.3 Product durability and workmanship aspects.....	33
4.2.4 Lighting durability aspects	36
4.2.5 Battery performance aspects	36
4.2.6 Solar module aspects	37
4.2.7 Electrical characteristics	38
4.2.8 Performance aspects	39
4.2.9 Light output aspects	41
4.2.10 Self-certification aspects.....	42
4.3 Constructions not specifically covered	43
5 Product specification	43
5.1 General.....	43
5.2 Applications	43
5.3 Quality assurance principles	44
5.4 Product specification framework description.....	44
5.4.1 General	44
5.4.2 Product specification template	45
5.4.3 Tolerances	49
5.4.4 Quality standards criteria.....	50
5.4.5 Warranty requirements criteria.....	55
6 Quality test method	56
6.1 General.....	56
6.2 Applications	56
6.3 Sampling requirements	56
6.4 Laboratory requirements	57
6.5 Testing requirements	57
6.6 Recommended tests programme.....	64
6.6.1 General	64
6.6.2 Test preparation	67
6.6.3 Batch A tests	67
6.6.4 Batch B tests	67
6.6.5 Batch C – potentially destructive tests	67

6.6.6	Report preparation.....	68
6.7	Reporting.....	68
7	Market check method.....	68
7.1	General.....	68
7.2	Applications.....	69
7.3	Sampling requirements.....	69
7.4	Laboratory requirements.....	70
7.5	Testing requirements.....	70
7.6	Recommended tests programme.....	70
7.7	Report requirements.....	70
8	Initial screening method.....	71
8.1	General.....	71
8.2	Applications.....	71
8.3	Sampling requirements.....	71
8.4	Laboratory requirements.....	72
8.5	Testing requirements.....	72
8.6	Recommended tests programme.....	72
8.7	Reporting.....	72
9	Accelerated verification method.....	72
9.1	General.....	72
9.2	Applications.....	73
9.3	Sampling requirements.....	73
9.3.1	General.....	73
9.3.2	Verification entry testing.....	73
9.3.3	Follow-up testing.....	74
9.4	Laboratory requirements.....	74
9.5	Testing requirements.....	74
9.5.1	General.....	74
9.5.2	Verification entry testing.....	75
9.5.3	Follow-up QTM testing.....	75
9.6	Recommended tests programme.....	75
9.7	Report requirements.....	75
10	Pay-as-you-go (PAYG) method.....	76
10.1	General.....	76
10.2	Applications.....	76
10.3	Sampling requirements.....	76
10.4	Laboratory requirements.....	77
10.5	Testing requirements.....	77
10.6	Recommended tests programme.....	78
10.7	Reporting.....	78
Annex A (informative)	Reserved.....	79
Annex B (informative)	Reserved.....	80
Annex C (informative)	Reserved.....	81
Annex D (normative)	Manufacturer self-reported information.....	82
D.1	Background.....	82
D.2	Outcomes.....	82
D.3	Solicited information.....	82
D.3.1	General.....	82

D.3.2	Confidential information (not released publicly).....	82
D.3.3	Public information (may be released publicly)	84
D.4	Reporting	86
Annex E (normative)	Product sampling	87
E.1	Background	87
E.2	Test outcomes	87
E.3	Related tests	87
E.4	Procedure	87
E.4.1	Retail sampling.....	87
E.4.2	Warehouse sampling	88
E.5	Reporting	89
Annex F (normative)	Visual screening.....	91
F.1	Background	91
F.2	Test outcomes	91
F.3	Related tests	91
F.4	Procedure	91
F.4.1	Properties, features, and information	91
F.4.2	Specifications	96
F.4.3	Functionality and internal inspection	99
F.5	Reporting	102
Annex G (normative)	Sample preparation	106
G.1	Background	106
G.2	Test outcomes	106
G.3	Related tests	106
G.4	Procedure	106
G.4.1	General	106
G.4.2	Equipment requirements	106
G.4.3	Test prerequisites	107
G.4.4	Procedure.....	107
G.4.5	Calculations.....	110
G.5	Reporting	110
Annex H (normative)	Power supply setup procedure	111
H.1	Background	111
H.2	Test outcomes	111
H.3	Related tests	111
H.4	Equipment requirements	111
H.5	Setup procedure for photometric measurements and lumen maintenance tests	112
H.5.1	Test setup	112
H.5.2	DC voltage and current levels.....	113
H.5.3	Stabilization period	114
H.5.4	4-wire power supply measurements	114
H.5.5	Filtering electronic noise.....	115
H.5.6	Troubleshooting.....	115
H.6	Reporting	117
Annex I (normative)	Light output test	118
I.1	Background	118
I.2	Test outcomes	118

I.3	Related tests	118
I.4	Luminous flux measurement techniques.....	119
I.4.1	General	119
I.4.2	Calculation for lighting appliances tested according to IEC TS 62257-12-1.....	119
I.4.3	Luminous flux measurements with an integrating sphere or goniophotometer.....	120
I.4.4	Luminous flux measurements using the multi-plane method.....	120
I.5	Correlated colour temperature (CCT) measurement	123
I.6	Colour rendering index (CRI) measurement	123
I.7	Reporting	123
Annex J (normative)	Lumen maintenance test.....	124
J.1	Background	124
J.2	Test outcomes	124
J.3	Related tests	125
J.4	Procedure	125
J.4.1	General	125
J.4.2	Equipment requirements	126
J.4.3	Test prerequisites	127
J.4.4	Test methods.....	127
J.5	Calculations	128
J.6	Alternate method for testing lumen maintenance using IESNA LM-80-08	128
J.6.1	Background	128
J.6.2	Equipment requirements	129
J.6.3	Test prerequisites	129
J.6.4	Procedure.....	129
J.6.5	DUT preparation and LED thermocouple attachment guidelines.....	130
J.6.6	Calculations.....	130
J.7	Reporting	130
Annex K (normative)	Battery test	133
K.1	Background	133
K.2	Test outcomes	133
K.3	Related tests	133
K.4	Procedure.....	133
K.4.1	General	133
K.4.2	Lead-acid battery test.....	134
K.4.3	Nickel-metal hydride battery test.....	137
K.4.4	Lithium-ion battery test	138
K.4.5	Lithium iron phosphate battery test.....	139
K.5	Reporting	140
Annex L (informative)	Battery testing recommended practices	141
L.1	Background	141
L.2	Deep discharge protection specifications by battery type	141
L.3	Overcharge protection specifications by battery type	142
Annex M (normative)	Full-battery run time test.....	143
M.1	Background	143
M.2	Test outcomes	143

M.3	Related tests	144
M.4	Equipment requirements	144
M.5	Test prerequisites	145
M.6	Apparatus	145
M.7	Procedure	146
M.8	Calculations	149
M.9	Reporting	151
Annex N (normative)	Full discharge preparation	153
N.1	Background	153
N.2	Test outcomes	153
N.3	Related tests	153
N.4	Procedure	153
N.4.1	General	153
N.4.2	Equipment requirements	153
N.4.3	Test prerequisites	153
N.4.4	Procedure	154
N.4.5	Calculations	155
N.5	Reporting	155
Annex O (normative)	Grid charge test	156
O.1	Background	156
O.2	Test outcomes	156
O.3	Related tests	156
O.4	Procedure	156
O.4.1	General	156
O.4.2	Equipment requirements	156
O.4.3	Test prerequisites	157
O.4.4	Apparatus	157
O.4.5	Procedure	157
O.4.6	Calculations	157
O.5	Reporting	158
Annex P (normative)	Electromechanical charge test	159
P.1	Background	159
P.2	Test outcomes	159
P.3	Related tests	159
P.4	Procedure	159
P.4.1	General	159
P.4.2	Equipment requirements	159
P.4.3	Test prerequisites	160
P.4.4	Apparatus	160
P.4.5	Procedure	160
P.4.6	Calculations	160
P.4.7	Modifications for atypical products	160
P.5	Reporting	161
Annex Q (normative)	Photovoltaic module I-V characteristics test	162
Q.1	Background	162
Q.2	Test outcomes	162
Q.3	Related tests	163
Q.4	Procedure	163

Q.4.1	Substitution of IEC 61215-2 test results	163
Q.4.2	Test programme using a solar simulator	164
Q.4.3	Outdoor photovoltaic module I-V characteristics test.....	166
Q.5	Reporting	171
Annex R (normative)	Solar charge test.....	172
R.1	Background	172
R.2	Test outcomes	172
R.3	Related tests	172
R.4	Procedure	173
R.4.1	General	173
R.4.2	Test method using a resistor network	173
R.4.3	Test method using a solar array simulator (SAS)	180
R.4.4	Calculations.....	181
R.4.5	Alternative method to measure battery-charging circuit efficiency	189
R.5	Reporting	190
Annex S (normative)	Charge controller behaviour test	193
S.1	Background	193
S.2	Test outcomes	193
S.3	Related tests	194
S.4	Procedure	194
S.4.1	Active deep discharge protection test	194
S.4.2	Active overcharge protection test.....	196
S.4.3	Passive deep discharge protection test.....	200
S.4.4	Passive overcharge protection test	202
S.4.5	Standby loss measurement.....	204
S.5	Reporting	205
Annex T (normative)	Light distribution test	207
T.1	Background	207
T.2	Test outcomes	207
T.3	Related tests	208
T.4	Substitution of results from IEC TS 62257-12-1.....	208
T.5	Approved test methods	208
T.5.1	General	208
T.5.2	Goniophotometer	211
T.5.3	Multi-plane method	211
T.5.4	Illuminance on a plane method	215
T.5.5	Turntable method	218
T.5.6	Illuminance on a desktop method.....	220
T.6	Reporting	221
Annex U (normative)	Physical and water ingress protection test	226
U.1	Background	226
U.2	Test outcomes	226
U.3	Related tests	227
U.4	Procedure	227
U.4.1	General	227
U.4.2	IP testing at a laboratory that has been accredited to test according to IEC 60529	227
U.4.3	Simplified IP inspection for ingress of solid foreign objects	228

U.4.4	Simplified IP preliminary inspection for ingress of water with harmful effects	229
U.5	Reporting	232
Annex V (normative)	Level of water protection	233
V.1	Background	233
V.2	Test outcomes	233
V.3	Related tests	234
V.4	Laboratory requirements	234
V.5	Procedure	234
V.5.1	General	234
V.5.2	Level of water protection for enclosure only	235
V.5.3	Level of water protection from technical aspects	235
V.5.4	Overall level of water protection	238
V.6	Reporting	239
Annex W (normative)	Mechanical durability test	241
W.1	Background	241
W.2	Test outcomes	241
W.3	Related tests	242
W.4	Procedures	242
W.4.1	Drop test	242
W.4.2	Switch and connector test	244
W.4.3	Gooseneck and moving part test	245
W.4.4	Strain relief test	246
W.5	Reporting	248
Annex X (informative)	Reserved	250
Annex Y (informative)	Photometer box for relative luminous flux measurements	251
Y.1	Background	251
Y.2	Plans	252
Y.3	Instructions for construction	255
Annex Z (informative)	Reserved	256
Annex AA (informative)	Reserved	257
Annex BB (normative)	Battery durability test	258
BB.1	Background	258
BB.2	Test outcomes	258
BB.3	Related tests	258
BB.4	Procedure	258
BB.4.1	Durability storage test for valve-regulated lead-acid batteries	258
BB.4.2	Durability storage test for flooded lead-acid batteries	259
BB.4.3	Durability storage test for nickel-metal hydride batteries	260
BB.4.4	Durability storage test for lithium-ion batteries	261
BB.4.5	Durability storage test for lithium iron phosphate batteries	262
BB.5	Reporting	263
Annex CC (normative)	Equipment requirements	264
CC.1	Overview	264
CC.2	Requirements and recommendations for equipment and materials	264
CC.3	Guidelines for electrical power measurements	275
CC.3.1	Background	275
CC.3.2	Overview of DC power measurement	275

CC.3.3	Power measurement accuracy recommendations.....	277
CC.3.4	Additional guidelines and corrective measures	278
Annex DD (normative)	Protection tests	279
DD.1	Background	279
DD.2	Test outcomes	279
DD.3	Related tests	280
DD.4	Procedure	280
DD.4.1	Miswiring protection test	280
DD.4.2	Output overload protection test.....	283
DD.4.3	PV overvoltage protection test.....	286
DD.5	Reporting.....	290
Annex EE (normative)	Assessment of DC ports	294
EE.1	Background	294
EE.2	Test outcomes	294
EE.3	Related tests	295
EE.4	Procedure	295
EE.4.1	Preparation.....	295
EE.4.2	Measurement of steady-state port characteristics	296
EE.4.3	Dynamic measurement	306
EE.4.4	Summary calculations.....	310
EE.4.5	Pass/fail tests for functionality and truth in advertising.....	310
EE.5	Reporting.....	314
Annex FF (normative)	Appliance tests.....	316
FF.1	Background	316
FF.2	Appliance testing requirements	316
FF.3	Test outcomes	318
FF.4	Related tests	319
FF.5	Setup and determination of appliance operating voltage	319
FF.5.1	General	319
FF.5.2	Procedure using the power control unit.....	320
FF.5.3	Procedure using a power supply	321
FF.6	Power consumption test.....	322
FF.6.1	General	322
FF.6.2	General equipment requirements	322
FF.6.3	Procedure for appliances that have been previously tested according to a recognized test method.....	322
FF.6.4	Test procedure for LED or CFL lighting appliances without an internal battery.....	324
FF.6.5	Test procedure for television sets without internal batteries	325
FF.6.6	Test procedure for radios without internal batteries.....	326
FF.6.7	Test procedure for fans, motor-driven appliances, and other appliances without internal batteries.....	327
FF.6.8	Test procedure for appliances with an internal battery	328
FF.7	Charging efficiency test	330
FF.7.1	General	330
FF.7.2	Equipment requirements.....	330
FF.7.3	Test prerequisites	330
FF.7.4	Procedure.....	330
FF.7.5	Calculations.....	331

FF.8	Appliance operating voltage range test	331
FF.8.1	General	331
FF.8.2	Equipment requirements	332
FF.8.3	Test prerequisites	332
FF.8.4	Simultaneous testing for multiple products and applicability of previous test results	332
FF.8.5	Procedure for appliances without batteries that have been tested according to a recognized test method	333
FF.8.6	Procedure for appliances without an internal battery	335
FF.8.7	Procedure for appliances with internal batteries	336
FF.9	Appliance full-battery run time test with deep discharge protection measurement	337
FF.9.1	General	337
FF.9.2	Equipment requirements	337
FF.9.3	Test prerequisites	337
FF.9.4	Apparatus	337
FF.9.5	Procedure	338
FF.9.6	Calculations	340
FF.10	Reporting	341
Annex GG (normative)	Energy service calculations	343
GG.1	Background	343
GG.2	Test outcomes	344
GG.3	Related tests	345
GG.4	Procedure	346
GG.4.1	Full-battery run time energy service calculations	346
GG.4.2	Solar run time energy service calculations	360
GG.4.3	Grid or electromechanical run time energy service calculations	377
GG.4.4	Solar charging time calculation	377
GG.5	Reporting	378
Annex HH (normative)	Generic appliances	380
HH.1	Background	380
HH.2	Test outcomes	380
HH.3	Related tests	380
HH.4	Equipment requirements	380
HH.5	Procedures	381
HH.5.1	Constructing generic appliances	381
HH.5.2	Appliance reference values	383
HH.6	Reporting	383
Bibliography	384
Figure 1	– Fixed indoor components and PV module – Example	26
Figure 2	– Fixed outdoor components with an indoor light point – Example	27
Figure 3	– Portable separate components – Example	27
Figure 4	– Portable integrated components – Example	28
Figure 5	– Division of a product into subsystems – Illustrative example	29
Figure 6	– Recommended sequence of testing for QTM for products without ports	65
Figure 7	– Recommended sequence of testing for QTM for products with ports	66
Figure G.1	– Connections with secondary set of wires to avoid battery disconnection	110

Figure H.1 – Power supply setup for powering a power control unit.....	112
Figure H.2 – Power supply setup for directly powering an appliance	112
Figure H.3 – 4-wire test configuration with input filter capacitors	115
Figure I.1 – Conceptual schematic of the light output test setup, including the 11 × 11 grid, Cartesian coordinate axes for rotation reference, and the DUT	121
Figure J.1 – Example lumen maintenance plot	132
Figure M.1 – Interior view of photometer box with suspended light.....	146
Figure M.2 – Plot of example results for a product with lighting appliances	150
Figure Q.1 – PV module I-V curve testing rack.....	167
Figure R.1 – Schematic of the power supply and DUT connection for the solar charge test .	175
Figure R.2 – Example "true" and simulated I-V curves plotted with the deviation ratio.....	179
Figure R.3 – Example plots of current vs. time for four different DUT batteries	183
Figure R.4 – Example time series plot of the solar charging cycle showing the maximum power available from the PV simulator, actual power supplied by the PV simulator, and power delivered to the batteries	191
Figure R.5 – Example time series plot of the solar charging cycle showing the instantaneous battery-charging circuit efficiency and solar operation efficiency	192
Figure S.1 – Schematic of the DC power supply-DUT connection using a series protection resistor.....	197
Figure T.1 – Horizontal plane for determining FWHM angle and radial illuminance distribution, for an omnidirectional light point	209
Figure T.2 – Horizontal plane for determining FWHM angle and radial illuminance distribution, for a directed light point	210
Figure T.3 – Radial illuminance distributions in the horizontal plane for two example products, showing the calculation of the horizontal FWHM angle	214
Figure T.4 – Radial illuminance distribution in the vertical plane for an example omnidirectional ambient light with vertical FWHM = 108°	215
Figure T.5 – Schematic of a task light suspended above an illuminance meter.....	216
Figure T.6 – Schematic of turntable setup, with the DUT shown.....	219
Figure T.7 – Side view of desktop light measuring setup.....	221
Figure T.8 – Example plot of usable area as a function of minimum illuminance.....	223
Figure T.9 – Example of resulting surface plot of light distribution from the brightest "face" of the multi-plane method or illuminance on a plane method	224
Figure T.10 – Example of a polar plot of the radial illuminance distribution	225
Figure U.1 – Side view of the apparatus for testing an external solar module for protection against water ingress	231
Figure W.1 – Three-dimensional Cartesian coordinate system for drop test reference.....	243
Figure W.2 – Cable strain angle (γ) schematics for a PV module junction box (left) and a separate light point (right)	247
Figure Y.1 – Interior view of a completed photometer box	251
Figure Y.2 – Exterior view of completed photometer box.....	252
Figure Y.3 – Photometer box dimensions.....	253
Figure Y.4 – Photometer box assembly pieces and list of materials	254
Figure EE.1 – Schematic of the example DUT with DC port and USB port and variable resistors connected for the measurement of steady-state port characteristics	299
Figure EE.2 – Example of the plots of port characteristics	305

Figure EE.3 – Schematic of the DUT with DC port and USB port and variable resistors connected for the dynamic measurement	307
Figure EE.4 – Illustration of stepped current waveform for procedure 2.....	309
Figure EE.5 – Example time series plot of voltage and current showing a step increase in current and the resulting voltage undershoot.....	309
Figure EE.6 – Example time series plot of voltage and current showing a step decrease in current and the resulting voltage overshoot.....	310
Figure EE.7 – Illustration of functionality assessment	312
Figure EE.8 – Typical configuration of USB port data lines	314
Figure EE.9 – Pin configuration of type A receptacle.....	314
Figure FF.1 – Illustration of calculation of minimum and maximum values of port voltage for the appliance operating voltage range test	334
Figure GG.1 – Conceptual energy flow diagram for energy service estimates	344
Table 1 – Applications of product specifications	44
Table 2 – Qualification as separate PV module	45
Table 3 – Truth-in-advertising tolerance.....	46
Table 4 – Safety and durability standards	47
Table 5 – End user support standards.....	48
Table 6 – End user support requirements.....	49
Table 7 – Truth-in-advertising criteria for quality standards	51
Table 8 – Remarks on common truth-in-advertising aspects.....	52
Table 9 – Safety and durability criteria for quality standards	53
Table 10 – Recommended level of water protection by product category.....	55
Table 11 – End user support criteria for quality standards.....	55
Table 12 – Criteria for warranty standards	55
Table 13 – Applications of QTM results.....	56
Table 14 – QTM testing requirements	59
Table 15 – Applications of MCM results	69
Table 16 – Applications of ISM results	71
Table 17 – Applications of AVM results	73
Table 18 – Applications of PAYG method results	76
Table 19 – PAYG testing requirements	78
Table D.1 – Manufacturer self-reported information outcomes	82
Table E.1 – Product sampling outcomes	87
Table F.1 – Visual screening test outcomes.....	91
Table G.1 – Recommended minimum conductor sizes for copper wire	107
Table H.1 – Power supply setup test outcome.....	111
Table H.2 – Standard operating voltage for several common battery types	113
Table H.3 – Voltage and current reporting requirements	117
Table I.1 – Light output test outcomes	118
Table J.1 – Lumen maintenance test outcomes.....	125
Table J.2 – Measurement schedule for full screening test.....	126
Table J.3 – Measurement schedule for initial screening test	126

Table K.1 – Battery test outcomes	133
Table K.2 – Recommended battery testing parameters	134
Table L.1 – Recommended battery deep discharge protection voltage specifications	142
Table L.2 – Recommended battery overcharge protection voltage and temperature specifications	142
Table M.1 – Full-battery run time test outcomes	144
Table O.1 – Grid charge test outcomes	156
Table P.1 – Mechanical charge test outcomes	159
Table Q.1 – Photovoltaic module I-V characteristics test outcomes	162
Table R.1 – Solar charge test outcomes	172
Table R.2 – Simulated solar day power supply settings	179
Table S.1 – Charge controller behaviour test outcomes	194
Table T.1 – Light distribution test outcomes	207
Table T.2 – Summary of testing options for characterizing lamp distributions	208
Table T.3 – Table of example illuminance measurements on the brightest "face" of the 1 m ² grid and usable area as a function of minimum illuminance	223
Table U.1 – Water exposure and physical ingress protection test outcomes	226
Table V.1 – Water exposure and physical ingress protection test outcomes	234
Table V.2 – Enclosure-only level of water protection requirements	235
Table V.3 – Adjusted level of water protection for products with additional technical water protection	236
Table V.4 – Example detailed assessment supporting technical level of water protection	238
Table V.5 – Overall level of water protection requirements	238
Table W.1 – Mechanical durability test outcomes	241
Table BB.1 – Battery durability test outcomes	258
Table CC.1 – Symbols used in test method column of Table CC.2	264
Table CC.2 – Specifications for all required test equipment	265
Table DD.1 – Protection test outcomes	279
Table DD.2 – Allowable port voltage limit by nominal voltage	287
Table DD.3 – Example table of miswiring protection test results	292
Table DD.4 – Example table of PV overvoltage test results	293
Table EE.1 – DC ports assessment outcomes	294
Table EE.2 – Current pairs for dynamic test	308
Table EE.3 – Recommended voltage and current ranges for port functionality assessment	311
Table FF.1 – Appliance testing requirements	317
Table FF.2 – Appliance test outcomes	318
Table FF.3 – Example table of appliance operating voltage, measured voltage, measured current, and calculated power	342
Table GG.1 – Energy service calculations outcomes	345
Table GG.2 – Examples of advertised combinations involving mobile devices	348
Table GG.3 – Required inputs to estimate the full-battery run time(s)	350
Table GG.4 – Example usage profile	352
Table GG.5 – Required inputs to estimate the solar run time	361

Table GG.6 – Representative case for appliance usage when solar charging	362
Table HH.1 – Power consumption chart for generic appliances	381
Table HH.2 – Energy capacity of generic appliances with internal batteries	383

INTERNATIONAL ELECTROTECHNICAL COMMISSION

RECOMMENDATIONS FOR RENEWABLE ENERGY AND HYBRID SYSTEMS FOR RURAL ELECTRIFICATION –

Part 9-5: Integrated systems – Laboratory evaluation of stand-alone renewable energy products for rural electrification

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a Technical Specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical Specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC 62257-9-5, which is a Technical Specification, has been prepared by IEC technical committee 82: Solar photovoltaic energy systems.

This fourth edition cancels and replaces the third edition issued in 2016. It constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) Replaced the term "stand-alone lighting kits" with "stand-alone renewable energy products" throughout the document (including the title) to reflect that the revised document is applicable to a broader range of products with a more diverse set of capabilities.
- b) Removed the distinction between Class A, Class B, and Class C procedures.
- c) Added an option for the AVM method in which the AVM-VE test can be conducted with a sample size of 6 and the follow-up test can be conducted with a sample size of 2.
- d) Provided guidance on how to accept test results from other approved test methods.
- e) Added test methods for flooded lead-acid batteries.
- f) Significantly revised the protection tests, assessment of DC ports, appliance tests, and energy service calculations based on field experience.
- g) Revised the voltage operating points at which testing is carried out to better reflect actual operation and to simplify the procedures for testing products without lights.
- h) Revised the energy service calculations to include the effect of multiple simultaneously connected loads on the port voltage and battery-to-port efficiency and to accommodate products with grid or electromechanical charging.
- i) Removed the restriction that all connections shall be "plug-and-play."
- j) Added discussion of measurement error and accuracy for DC power measurements.

This part of IEC 62257 is to be used in conjunction with IEC 62257 (all parts).

The text of this Technical Specification is based on the following documents:

Enquiry draft	Reports on voting
82/1346/DTS	82/1385A/RVDTS

Full information on the voting for the approval of this Technical Specification can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62257 series, published under the general title *Recommendations for renewable energy and hybrid systems for rural electrification*, can be found on the IEC website.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- transformed into an International standard,
- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

IEC 62257 (all parts) provides support and strategies for institutions involved in rural electrification projects. It documents technical approaches for designing, building, testing, and maintaining off-grid renewable energy and hybrid systems with AC nominal voltage below 500 V, DC nominal voltage below 750 V and nominal power below 100 kVA.

These documents are recommendations to support buyers who want to connect with good quality options in the market:

- to choose the right system for the right place,
- to design the system, and
- to operate and maintain the system.

These documents are focused only on technical aspects of rural off-grid electrification concentrating on, but not specific to, developing countries. They are not considered as all inclusive to rural electrification. The documents do not describe a range of factors that can determine project or product success: environmental, social, economic, service capabilities, and others. Further developments in this field could be introduced in future steps.

This consistent set of documents is best considered as a whole with different parts corresponding to items for safety, sustainability of systems, and costs. The main objectives are to support the capabilities of households and communities that use small renewable energy and hybrid off-grid systems and inform organizations and institutions in the off-grid power market.

The purpose of this document is to specify laboratory test methods for evaluating the quality assurance of stand-alone renewable energy products. This document is specifically related to renewable energy products that are packaged and made available to end-use consumers at the point of purchase as single, stand-alone products that do not require additional system components to function.

The term "stand-alone renewable energy product" is used in this document to describe this class of products. Other equivalent terms, including "off-grid solar" or "rechargeable," are often used by manufacturers, distributors, and other stakeholders to describe these products. Many of these systems meet the definition of type T₂I (individual electrification systems with energy storage) in IEC TS 62257-2.

The intended users of this document are:

- Market support programmes that support the off-grid lighting market with financing, consumer education, awareness, and other services;
- Manufacturers and distributors that need to verify the quality and performance of products;
- Bulk procurement programmes that facilitate or place large orders of products; and,
- Trade regulators such as government policymakers and officials who craft and implement trade and tax policy.

This document establishes the framework for creating a product specification, the basis for evaluating quality for a particular context. Product specifications include minimum requirements for quality standards and warranty requirements. Products are compared to specifications based on test results and other information about the product. The product specification framework is flexible and can accommodate the goals of diverse organizations and institutions. The tests and inspections are designed to be widely applicable across different markets, countries, and regions.

RECOMMENDATIONS FOR RENEWABLE ENERGY AND HYBRID SYSTEMS FOR RURAL ELECTRIFICATION –

Part 9-5: Integrated systems – Laboratory evaluation of stand-alone renewable energy products for rural electrification

1 Scope

This part of IEC 62257, which is a Technical Specification, applies to stand-alone renewable energy products having the following characteristics:

- All components required to provide basic energy services are sold/installed as a kit or integrated into a single component, including at a minimum:
 - A battery/batteries or other energy storage device(s)
 - Power generating device, such as a solar panel, capable of charging the battery/batteries or other energy storage device(s)
 - Cables, switches, wiring, connectors and protective devices sufficient to connect the power generating device, power control unit(s) and energy storage device(s)
 - Loads (optional), such as lighting, load adapter cables (e.g., for mobile devices), and appliances (television, radio, fan, etc.).
- The PV module maximum power point voltage and the working voltage of any other components in the kit do not exceed 35 V. Exceptions are made for AC-to-DC converters that meet appropriate safety standards.

NOTE This voltage limit corresponds to the definition of decisive voltage classification A (DVC-A) for wet locations in Table 6 of IEC 62109-1:2010.

- The peak power rating of the PV module or other power generating device is less than or equal to 350 W.
- No design expertise is required to choose appropriate system components.

This document was written primarily for off-grid renewable energy products with batteries and solar modules with DC system voltages not exceeding 35 V and peak power ratings not exceeding 350 W. The tests contained herein are capable in many cases of adequately assessing systems at higher voltages and/or power ratings. In situations where the specifying organization agrees to apply these tests to products with higher voltages and power ratings, the test laboratory is responsible for ensuring that adequate safety measures are employed to protect technicians and test equipment. The specifying organization is also responsible for defining the consumer safety requirements of these products.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60529, *Degrees of protection provided by enclosures (IP Code)*

IEC 60891:2009, *Photovoltaic devices – Procedures for temperature and irradiance corrections to measured I-V characteristics*

IEC 60904-1:2006, *Photovoltaic devices – Part 1: Measurement of photovoltaic current-voltage characteristics*

IEC 61056-1:2012, *General purpose lead-acid batteries (valve-regulated types) – Part 1: General requirements, functional characteristics – Methods of test*

IEC 61215 (all parts), *Terrestrial photovoltaic (PV) modules – Design qualification and type approval*

IEC 61215-2, *Terrestrial photovoltaic (PV) modules – Design qualification and type approval – Part 2: Test procedures*

IEC 61427-1:2013, *Secondary cells and batteries for renewable energy storage – General requirements and methods of test – Part 1: Photovoltaic off-grid application*

IEC 61951-2:2017, *Secondary cells and batteries containing alkaline or other non acid electrolytes – Secondary sealed cells and batteries for portable applications – Part 2: Nickel-metal hydride*

IEC 61960-3:2017, *Secondary cells and batteries containing alkaline or other non-acid electrolytes – Secondary lithium cells and batteries for portable applications – Part 3: Prismatic and cylindrical lithium secondary cells and batteries made from them*

IEC 62087-2:2015, *Audio, video, and related equipment – Determination of power consumption – Part 2: Signals and media*

IEC 62087-3:2015, *Audio, video, and related equipment – Determination of power consumption – Part 3: Television sets*

IEC 62087-6:2015, *Audio, video, and related equipment – Determination of power consumption – Part 6: Audio equipment*

IEC TS 62257-12-1:2015, *Recommendations for renewable energy and hybrid systems for rural electrification – Part 12-1: Selection of lamps and lighting appliances for off-grid electricity systems*

IEC 62509:2010, *Battery charge controllers for photovoltaic systems – Performance and functioning*

CIE 15:2004, *Colorimetry*

CIE 084, *The measurement of luminous flux*

CIE 13.3, *Method of measuring and specifying colour rendering properties of light sources*

CIE 127, *Measurement of LEDs*

CIE 177, *Colour rendering of white LED light sources*

IESNA LM-78-07, *IESNA approved method for total luminous flux measurement of lamps using an integrating sphere photometer*

IESNA LM-79-08, *IES approval method for electrical and photometric measurements of solid state lighting products*

IESNA LM-80-08, *Approved method: measuring lumen maintenance of LED light sources*