



TECHNICAL SPECIFICATION



**Nanomanufacturing – Key control characteristics –
Part 6-13: Graphene-based material – Oxygen functional group content: Boehm
titration method**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 07.120

ISBN 978-2-8322-8726-2

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	4
INTRODUCTION	6
1 Scope	7
2 Normative references	7
3 Terms, definitions, symbols and abbreviated terms	7
3.1 Terms and definitions	8
3.1.1 General terms	8
3.1.2 Key control characteristics measured according to this document	9
oxygen functional group	9
3.1.3 Terms related to the measurement method	9
3.2 Symbols and abbreviated terms	9
4 General	10
4.1 Measurement principle	10
4.2 Sample preparation method	10
4.3 Description of measurement equipment / apparatus	11
4.3.1 Analytical balance, readability is 0,1 mg.	11
4.3.2 Electric thermostatic drying oven	11
4.3.3 Numerical control magnetic agitator/oscillator	11
4.3.4 Automatic potentiometer, with pH electrode and accurate to 0,1 mV.	11
4.3.5 HDPE bottles, the volume are 1 000 mL and 100 mL, with stopper.	11
4.4 Supporting materials	11
4.5 Ambient conditions during measurement	11
5 Measurement procedure	11
5.1 Detailed protocol of the measurement procedure	11
5.1.1 Preparation of solutions	11
5.1.2 Reactions between graphene and bases	13
5.1.3 Instrument preparation	13
5.1.4 Titration of the filtrate	13
5.2 Measurement uncertainty	14
5.3 Operation procedure, key control steps and case study	14
6 Data analysis / interpretation of results	14
6.1 Normalized base consumption	14
6.2 Oxygen functional group content	15
7 Results to be reported	15
7.1 General	15
7.2 Product/sample identification	15
7.3 Test results	15
Annex A (informative) Operation procedure and key control steps	16
A.1 Operation procedure	16
A.2 Key control steps	17
Annex B (informative) Influence of CO ₂	18
B.1 Effect of CO ₂ on titration of base concentration	18
B.2 Effect of CO ₂ on base consumption	19
Annex C (informative) Lower limit of determination	20

C.1	Experiment of lower mass of reacted sample A	20
C.2	Determination of detection limits	20
Annex D (informative)	Test report	23
D.1	Example of a test record	23
D.2	Format of the test report	23
Annex E (informative)	Case study	25
E.1	Preparation of solution	25
E.2	Sample preparation.....	25
E.3	Reactions between graphene and bases	25
E.4	Titration of the filtrate.....	26
E.5	Calculation.....	28
E.6	Test report.....	30
Bibliography.....		31
Figure 1	– Test principle of Boehm titration.....	10
Figure A.1	– Operation procedure	16
Figure A.2	– Key control steps	17
Figure B.1	– Titration curves of NaOH solution	18
Figure C.1	– The normalized base consumption of different amounts of sample A	20
Figure E 1	– Titration curves of A0 filtrate (upper left), B0 filtrate (upper right), C0 filtrate (lower left), and D0 filtrate (lower right).....	27
Table 1	– Four types of oxygen functional group and their structures.....	10
Table 2	– Reagents used in this document.....	11
Table B.1	– Titration results of back titration and direct titration of NaOH solution	19
Table B.2	– Results of base consumption of NaOH with and without bubbling N ₂	19
Table C.1	– Base consumption result of sample A	21
Table C.2	– Oxygen functional group content result	22
Table C.3	– Detection limits for different sample amounts.....	22
Table D.1	– Data for calibration of titrant acid	23
Table D.2	– Data for Boehm titration	23
Table D.3	– Product identification (according to IEC 62565-3-1)	24
Table D.4	– General material description (according to IEC 62565-3-1)	24
Table D.5	– Measurement results	24
Table E.1	– Measurement data	27
Table E.2	– Normalized base consumption of sample 1	29
Table E.3	– Product identification of sample 1	30
Table E.4	– General material description of sample 1	30
Table E.5	– Measurement results of sample 1.....	30

INTERNATIONAL ELECTROTECHNICAL COMMISSION

NANOMANUFACTURING – KEY CONTROL CHARACTERISTICS –

Part 6-13: Graphene-based material – Oxygen functional group content: Boehm titration method

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a Technical Specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical Specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC TS 62607-6-13, which is a Technical Specification, has been prepared by IEC technical committee 113: Nanotechnology for electrotechnical products and systems.

The text of this Technical Specification is based on the following documents:

Draft TS	Report on voting
113/455/DTS	113/486/RVDTS

Full information on the voting for the approval of this Technical Specification can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 62607 series, published under the general title *Nanomanufacturing – Key control characteristics*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

The contents of the corrigendum of October 2020 have been included in this copy.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

In recent years, graphene has attracted extensive attention from academia and industry, due to the extraordinary physical and chemical properties for promising applications in energy conversion and storage, electronics, composites and catalysis, etc. In the case of most graphene available in the laboratory or on the market, oxygen functional groups are inevitable, especially for the powder form products. These oxygen functionalities, which exist mainly in the form of carboxyl groups, lactones or lactols, phenolic hydroxyl groups, reactive carbonyl groups and epoxide groups, etc., are located on the surface or edge of the two-dimensional carbon lattice. They affect many crucial properties of graphene, including wettability, electrical and thermal conductivity, electron density, acidity and reactivity, etc. [1][2][3][4]¹, and so determine the performance of graphene for downstream applications. For example, in an energy storage device such as lithium ion battery or supercapacitor, the oxygen heteroatoms will introduce irreversible reaction to exhaust the organic electrolyte and emit small molecules, which will reduce the cycling stability and even cause safety problems to the final products [5][6]. Besides, the oxygen functional groups will significantly decrease the electrical conductivity of graphene, which has a negative impact on the rate capacity of the cell, due to the increase of internal resistance for the electrode [7][8]. Furthermore, the different oxygen containing functional groups will play very different roles in affecting the properties of graphene. For example, in catalysis, graphene has been employed as an effective solid acid catalyst for hydrocarbon chemistry, as many oxygen functionalities show acidic properties [9][10][11]. However, the acidity strength of different oxygen species is distinct, as the acidity sequence is carboxyl, lactone, hydroxyl, and carbonyl. Besides, it is proved that ketonic carbonyl groups, with higher electron density, are the catalytic active sites for oxidative dehydrogenation reactions [12][13]. So, the type and proportion of oxygen groups will significantly influence the catalytic activity and selectivity of graphene. Therefore, the qualification of different oxygen functional groups on the surface of graphene is a key control characteristic for the production, application and trading of graphene and related products.

The most common methods for identification and quantification of oxygen functional groups on graphene are FT-IR, XPS, EELS and Boehm titration. Moreover, other recent methods such as SAED, MS and FLOSS are springing up. However, some of these methods have difficulty quantifying oxygen functional groups on graphene, and there is no standard method to quantify the oxygen functional groups. Boehm titration, dating from 1962, is an efficient, repeatable and easy to operate method with low cost. More importantly, the Boehm titration method can provide absolute values of the surface concentration of oxygen functional groups and avoid the ambiguity and subjectivity brought by spectroscopies, which shows its unique advantage in quantification of many oxygen functional groups on graphene [14][15][16][17][18][19][20]. Note that Boehm titration cannot determine the total oxygen content of a powder, as it only measures those functional groups that can dissociate under the conditions of the test.

Boehm titration has been applied to determine the oxygen functional groups of many traditional carbonaceous materials for decades, such as activated carbon and carbon black. In recent years, it was applied to graphene [21][22]. Because the physical properties of graphene are very different from those of other carbonaceous materials, the operation-specific details in this document are suitable for powders of graphene oxide, reduced graphene oxide, graphene and related materials only. When applying Boehm titration to graphene dispersions, the dispersion medium needs to be removed. This document can be used as the reference for other carbonaceous materials.

This document focuses on the determination of oxygen functional groups and standardization of the operation method. Due to various steps such as agitation, end-point determination, etc. required in Boehm titration, significant measurement errors can be introduced if not properly addressed.

¹ Numbers in square brackets refer to the Bibliography.

NANOMANUFACTURING – KEY CONTROL CHARACTERISTICS –

Part 6-13: Graphene-based material – Oxygen functional group content: Boehm titration method

1 Scope

This part of IEC TS 62607 establishes a standardized method to determine the chemical key control characteristic

- oxygen functional group content
for powder consisting of graphene-based material like graphite oxide, graphene oxide, reduced graphene oxide and other types of functionalized graphene by
- Boehm titration method.

In this document, the measured functional groups are carboxyl groups (also in the form of their cyclic anhydrides), lactone groups, hydroxyl groups and reactive carbonyl groups. Oxygen functional groups that exhibit no reactivity such as epoxides cannot be measured.

The oxygen functional group content is derived by the difference between NaHCO_3 , Na_2CO_3 , NaOH and $\text{C}_2\text{H}_5\text{ONa}$ consumption of dispersed graphene powders.

- The oxygen functional group content determined according to this document is listed as key control characteristic in the blank detail specification for graphene IEC 62565-3-1.
- The method is applicable for graphene powder and graphene related carbon 2D materials such as graphene oxide powder and reduced graphene oxide powder, which can be separated from the water and ethanol by centrifugation or filtration. This document is not applicable for sulfonate modified graphene.
- In this document, the lower limits of detection (Annex C) for carboxyl groups, lactone groups, hydroxyl and carbonyl are 0,015 mmol/g, 0,037 mmol/g, 0,014 mmol/g, and 0,072 mmol/g, respectively.
- This document targets graphene manufacturers and downstream users to guide their material design, production and quality control.

2 Normative references

There are no normative references in this document.