INTERNATIONAL STANDARD

10090

First edition 1992-10-15

Information technology — 90 mm optical disk cartridges, rewritable and read only, for data interchange

Technologies de l'information — Cartouches pour disques optiques de diamètre 90 mm, réinscriptibles et à lecture unique, pour échange de données



Cambanda

Conte	111.5	Page
Section 1 - General		1
1	Scope	1
2	Conformance	1
3	Normative reference	1
4	Definitions	1
4.1 4.2 4.3 4.4 4.5 4.6 4.7 4.8 4.9 4.10 4.11 4.12 4.13 4.14 4.15 4.16 4.17 4.18 4.19 4.20 4.21	case cyclic redundancy check (CRC) embossed mark entrance surface error correction code (ECC) field format groove interleaving Kerr rotation land and groove mark optical disk optical disk cartridge (ODC) polarization recording layer Reed-Solomon code rewritable optical disk sector substrate track zone	1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
5	Conventions and notations	3
5.1 5.2	Representation of numbers Names	3
6	List of acronyms	3
7	General description of the optical disk cartridge	3

© ISO/IEC 1992
All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case Postale 56 • CH-1211 Genève 20 • Switzerland Printed in Switzerland

8	General requirements	4
8.1	Environments	4
8.1.1 8.1.2 8.1.3 8.1.4	Testing environment Operating environment Storage environment Transportation	4 4 5 5
8.2 8.3 8.4	Temperature shock Safety requirements Flammability	5 5 5
9	Reference Drive	5
9.1 9.2 9.3 9.4 9.5	Optical system Optical beam Read channels Tracking Rotation of the disk	5 7 7 7 7
Section	2 - Mechanical and physical characteristics	8
10	Dimensional and physical characteristics of the case	8
10.1 10.2	General description of the case Reference planes of the case	8
10.3	Dimensions of the case	8
10.3.1 10.3.2	Overall dimensions Location hole	8 9
	Alignment hole Reference surfaces Detents Functional Areas Spindle and head windows Shutter Path for shutter opener and shutter sensor notch Mis-insert protections Gripper slots Label area	9 9 10 10 11 12 13 13 14
10.4	Mechanical characteristics	14
10.4.1 10.4.2 10.4.3 10.4.4 10.4.5	Material Mass Edge Distortion Compliance Shutter opening force	14 15 15 15 15
11	Dimensional, mechanical and physical characteristics of the disk	27
11.1 11.2 11.3	General description of the disk Reference axis and plane of the disk Dimensions of the disk	27 27 28
11.3.1	Hub dimensions	28

11.3.2	Clamping zone	28
11.4	Mechanical characteristics	29
11.4.1 11.4.2 11.4.3 11.4.4 11.4.5 11.4.6 11.4.7 11.4.8 11.4.9	Material Mass Moment of inertia Imbalance Axial deflection Axial acceleration Radial runout Radial acceleration Tilt	29 29 29 29 29 30 30
11.5	Optical characteristics	30
11.5.1 11.5.2 11.5.3 11.5.4	Index of refraction Thickness of the substrate Birefringence Reflectance	30 30 31 31
12	Interface between cartridge and drive	31
12.1 12.2 12.3 12.4	Clamping method Clamping force Capture cylinder (see figure 14) Disk position in operating condition (see figure 14)	31 31 31 32
Section	3 - Format of information	34
13	Track geometry	34
13.1 13.2 13.3 13.4	Track shape Direction of rotation Track pitch Track number	34 34 34 34
14	Track format	34
14.1 14.2 14.3	Track layout Radial alignment Sector Number	34 35 35
15	Sector format	35
15.1 15.2 15.3 15.4 15.5 15.6 15.7 15.8 15.9 15.10	Sector layout Sector Mark VFO fields Address Mark (AM) ID fields Postambles (PA) Offset Detection Field (ODF) Gap Sync Data field	35 36 36 36 37 37 37 37
15.10.1 15.10.2 15.10.3	User data bytes CRC and ECC bytes Resync bytes	38 38 38
15.11	Buffer field	38

16	Recording code	38
17	Format of the Information Zone	39
17.1 17.2		39 39
17.2.1 17.2.2 17.2.3 17.2.4 17.2.5 17.2.6	Acquire Zone Test Zones Control Zones Data Zone	40 40 40 41 41 41
18	Format of the Data Zone	41
18.1 18.2 18.3	Disk Definition Sector (DDS)	42 43 45
18.3.1 18.3.2		45 45
18.4	Embossed Zonc	45
18.4.1 18.4.2 18.4.3	Location Partitioning Parity Sectors	45 46 46
19	Defect management in the Rewritable Zone	46
19.1 19.2	Initialization of the disk Certification	47 47
19.2.1 19.2.2	Slipping Algorithm Linear Replacement Algorithm	47 47
19.3 19.4 19.5 19.6	Disks not certified Write procedure Primary Defect List (PDL) Secondary Defect List (SDL)	47 48 48 48
Section	4 - Characteristics of embossed information	50
20	Method of testing	50
20.1 20.2	Environment Use of the Reference Drive	50 51
20.2.1 20.2.2 20.2.3 20.2.4	Optics and mechanics Read power Read channels Tracking	51 51 51 51
20.3	Definition of signals	51
21	Signals from grooves	53
21.1 21.2 21.3 21.4	Cross-track signal Cross-track minimum signal Push-pull signal Divided push-pull signal	53 53 53 54

21.5 21.6 21.7	On-track signal Phase depth Track location	54 55 55
22	Signals from Headers	55
22.1 22.2 22.3	Sector Mark VFO1 and VFO2 Address Mark, ID field and Postamble	55 55 55
23	Signals from embossed Recording fields	56
Section	5 - Characteristics of the recording layer	56
24	Method of testing	56
24.1 24.2	Environment Reference Drive	56 56
24.2.1 24.2.2 24.2.3 24.2.4	Optics and mechanics Read power Read channel Tracking	56 56 56 57
24.3	Write conditions	57
24.3.1 24.3.2 24.3.3	Write pulse Write power and pulse width Write magnetic field	57 57 58
24.4	Erase conditions	58
24.4.1 24.4.2	Erase power Erase magnetic field	58 58
24.5	Definition of signals	58
25	Magneto-optical characteristics	59
25.1 25.2	Figure of merit Imbalance of the magneto-optical signal	59 59
26	Write characteristics	59
26.1 26.2 26.3	Resolution Narrow-band signal-to-noise ratio Cross-talk	59 59 60
27	Erase characteristics	60
Section	6 - Characteristics of user data	61
28	Method of testing	61
28.1 28.2	Environment Reference Drive	61 61
28.2.1 28.2.2 28.2.3 28.2.4 28.2.5 28.2.6	Optics and mechanics Read power Read amplifiers Analog-to-binary converters Error correction Tracking	61 61 61 62 62
29	Minimum quality of a sector	62
29.1	Headers	62

29.1.1 29.1.2	Sector Mark ID fields	62
29.2 29.3	User-written data Embossed data	62 62
30	Data interchange requirements	62
30.1 30.2 30.3 30.4	Tracking User-written data Embossed data Quality of disk	62 63 63 63
Annexe	S .	
A - Ed	lge distortion test	64
B - Co	mpliance test	65
C - Tra	ack deviation measurement	67
D - CR	RC for ID fields	71
E - Fo	rmat of the Data field of a sector	72
F - Co	ntents of the Control Zones	76
G - Gu	nidelines for sector replacement	84
Н - М	easurement of the figure of merit	84
J - Rea	ad power, write power and erase power	85
K - Te	est method for measuring the adsorbent force of the hub	86
L - De	crivation of the operating climatic environment	88
M - A	ir cleanliness class 100 000	92
N - Po	sition of the cartridge relative to the reference planes	93
P - Tra	ansportation	94
Q - Oi	ffice environment	94
R - Re	elaxation by zones of the requirements for signals	95

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75% of the national bodies casting a vote.

International Standard ISO/IEC 10090 was prepared by the European Computer Manufacturers Association (as Standard ECMA-154) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC1, *Information technology* in parallel with its approval by national bodies of ISO and IEC.

Annexes A, B, D, E, F, H, K, M, N and R form an integral part of this International Standard. Annexes C, G, J, L, P and Q are for information only.

Introduction

This International Standard specifies the characteristics of 90 mm optical disk cartridges (ODCs) of the type providing for data to be written, read and erased many times using the thermo-magnetic and magneto-optical effects.

A part or all of the optical disk may be pre-recorded and be reproduced by stamping or other means. This information is read without recourse to the magneto-optical effect.

This International Standard together with a standard for volume and file structure provides for full data interchange between data processing systems. Interchange involves the ability to write, read and erase data without introducing any error.

Information technology - 90 mm optical disk cartridges, rewritable and read only, for data interchange

Section 1 - General

1 Scope

This International Standard specifies

- the conditions for conformance testing and the Reference Drive;
- the mechanical and physical characteristics of the cartridge, so as to provide mechanical interchangeability between data processing systems;
- the format of the information on the disk, both embossed and user-written:
- the characteristics of the embossed information on the disk:
- the magneto-optical characteristics of the disk, enabling processing systems to write data onto the disk;
- the minimum quality of user-written data on the disk, enabling data processing systems to read data from the disk,

2 Conformance

A 90 mm optical disk cartridge is in conformance with this International Standard if it meets all mandatory requirements specified herein.

Annex R specifies the zones of the disk in which the requirements for the signal characteristics given in the body of this International Standard shall be met, and the zones in which a relaxation of these requirements is permitted.

A drive claiming conformance with this International Standard shall be able, in the operating environment, to write on any optical disk cartridge which is in conformance with this International Standard, and to read from any optical disk cartridge which is in conformance with this International Standard.

A drive shall not claim conformance if it cannot accept the full range of media conforming to this International Standard but only a specific sub-set of it.

3 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the standard listed below. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 950:1991, Safety of information technology equipment, including electrical business equipment.