This is a preview - click here to buy the full publication

INTERNATIONAL STANDARD

ISO/IEC 13962

First edition 1995-09-15

Information technology — Data interchange on 12,7 mm, 112-track magnetic tape cartridges — DLT 2 format

Technologies de l'information — Échange de données sur cartouches de bande magnétique de 12,7 mm, 112 pistes — Format DLT 2



Contents

	Page
1 Scope	1
2 Conformance	1
2.1 Magnetic tape cartridges	1
2.2 Generating systems	1
2.3 Receiving systems	1
3 Normative references	1
4 Definitions	1
4.1 Average Signal Amplitude	1
4.2 azimuth	1
4.3 back surface	1
4.4 Beginning-Of-Tape marker (BOT)	1
4.5 byte	1
4.6 cartridge	2
4.7 Cyclic Redundancy Check (CRC) character	2
4.8 Early Warning (EW)	2
4.9 Error-Detecting Code (EDC)	2
4.10 End-Of-Tape marker (EOT)	2
4.11 Entity	2
4.12 Error-Correcting Code (ECC)	2
4.13 flux transition position	2
4.14 flux transition spacing	2
4.15 Logical Block	2
4.16 logical track	2
4.17 magnetic tape	2
4.18 Master Standard Reference Tape	2
4.19 object	2
4.20 physical block	2
4.21 physical recording density	2
4.22 physical track	2
4.23 Record	2
4.24 Reference Edge	2
4.25 Reference Field	2
4.26 Secondary Standard Reference Tane	2

© ISO/IEC 1995

All rights reserved. Unless otherwise specified no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher

ISO/IEC Copyright Office \cdot Case Postale 56 \cdot CH-1211 Genève 20 \cdot Switzerland

Printed in Switzerland

4.27 Standard Reference Amplitude (SRA)4.28 Standard Reference Current4.29 Test Recording Current4.30 Typical Field	2 2 3 3
5 Conventions and notations	3
5.1 Representation of numbers 5.2 Names 5.3 Acronyms	3 3 3
6 Environment and safety	3
6.1 Cartridge and tape testing environment6.2 Cartridge operating environment6.3 Cartridge storage environment	3 4 4
6.4 Safety	4
6.4.1 Safeness 6.4.2 Flammability	4
6.5 Transportation	4
Section 2 - Requirements for the unrecorded tape	5
7 Mechanical and electrical requirements	5
 7.1 Material 7.2 Tape length 7.3 Width 7.4 Total thickness 7.5 Thickness of the base material 7.6 Thickness of the magnetic coating 7.7 Thickness of the back coating 7.8 Discontinuity 	5 5 5 5 5 5 5 5
7.9 Longitudinal curvature	5
7.9.1 Requirement 7.9.2 Procedure	5 5
7.10 Out-of-Plane distortions7.11 Cupping7.12 Roughness of the coating surfaces	5 5 6
7.12.1 Roughness of the back coating surface7.12.2 Roughness of the magnetic coating surface	6
7.13 Coating adhesion 7.14 Layer-to-layer adhesion	6 7
7.14.1 Requirements 7.14.2 Procedure	7
7.15 Modulus of elasticity	8
7.15.1 Requirement 7.15.2 Procedure	8
7.16 Flexural rigidity	8

7.16.1 Requirement 7.16.2 Procedure	8 8
7.17 Tensile yield force	9
7.17.1 Procedure	9
7.18 Electrical resistance	9
7.18.1 Requirement 7.18.2 Procedure	9 9
7.19 Inhibitor tape 7.20 Abrasivity	10 10
7.20.1 Requirement 7.20.2 Procedure	10 10
7.21 Light transmittance of the tape and the leader7.22 Coefficient of dynamic friction	10 10
 7.22.1 Requirements 7.22.2 Procedure for the measurement of the friction between the magnetic surface and the back surface 7.22.3 Procedure for the measurement of the friction between the magnetic surface or the back surface and calcium titanate ceramic 	10 11 11
8 Magnetic recording characteristics	11
8.1 Typical Field8.2 Signal amplitude8.3 Resolution8.4 Overwrite	11 12 12 12
8.4.1 Requirement	12
8.5 Peak shift	12
8.5.1 Requirement 8.5.2 Procedure	12 12
9 Tape quality	13
9.1 Missing pulses	13
9.1.1 Requirement	13
9.2 Missing pulse zone	13
9.2.1 Requirement	13
9.3 Tape durability	13
Section 3 - Mechanical specifications of the tape cartridge	14
10 General	14
 10.1 Bottom side and right side 10.2 Back side and left side 10.3 Tape reel 10.4 Tape leader 10.5 Front side 10.6 Operation of the cartridge 	14 15 16 16 18
10.7 Tape winding	19

10.8 Moment of inertia 10.9 Material	19 19
Section 4 - Requirements for an interchanged tape	28
11 Method of recording	28
11.1 Physical recording density11.2 Bit cell length	28 28
11.2.1 Average bit cell length11.2.2 Long-term average bit cell length11.2.3 Short-term average bit cell length	28 28 28
11.3 Flux transition spacing 11.4 Read signal amplitude 11.5 Azimuth 11.6 Channel skew	28 28 28 28
12 Tape format	29
12.1 Reference Edge12.2 Direction of recording12.3 Tape layout12.4 Calibration and Directory Area	29 29 29 29
12.4.1 Scratch Area 12.4.2 Guard Area G1 12.4.3 Calibration Tracks Area 12.4.4 Guard Area G2 12.4.5 Directory Area 12.4.6 Guard Area G3	30 30 31 31 31
12.5 Data Area	31
 12.5.1 Physical tracks 12.5.2 Width of the physical tracks 12.5.3 Logical tracks 12.5.4 Locations of the physical tracks 12.5.5 Layout of tracks in the Data Area 	32 32 32 32 33
13 Data format	30
13.1 Data Bytes 13.2 Logical Blocks 13.3 Data Blocks 13.4 Types of Logical Blocks 13.5 Entities 13.6 Logical Block format	36 36 36 37 37
13.6.1 Preamble 13.6.2 Sync 13.6.3 Data Field 13.6.4 Control Field 1 (CF1) 13.6.5 Control Field 2 (CF2) 13.6.6 CRC 13.6.7 Postamble	37 37 38 40 41

14 Use of Logical Blocks	41
14.1 Data Blocks	41
14.2 Tape Mark Blocks	41
14.3 Filler Blocks	41
14.4 End of Track Blocks (EOTR)	41
14.5 End of Data Blocks (EOD)	41
14.6 ECC Blocks	41
15 Format of Entities	42
16 Error handling	42
Annexes	43
A - Measurement of light transmittance	43
B - CRC generation	46
C - ECC generation	47
D - Format of Control Field 1	50
E - Format of Control Field 2	51
F - Recommendations for transportation	52
G - Inhibitor tape	53
H - Recommendations on tape durability	54
I - Handling guidelines	55

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 13962 was prepared by ECMA (as Standard ECMA-197) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology*.

Annexes A to E form an integral part of this International Standard. Annexes F to J are for information only.

Introduction

ISO/IEC 13421¹⁾ specifies a magnetic tape cartridge in which the 12,7 mm wide magnetic tape is recorded on 48 parallel physical tracks, recorded and read in pairs, which constitute two groups, the first recorded and read in forward direction, the second in reverse direction.

This International Standard constitutes a further development of the cartridge specified in ISO/IEC 13421 in that the number of tracks has been raised from 48 to 112, thus raising the total capacity of the cartridge accordingly. Drives for cartridges according to this International Standard may be able to read from, and write onto, cartridges according to ISO/IEC 13421.

¹⁾ ISO/IEC 13421:1993, Information technology - Data interchange on 12,7 mm, 48-track magnetic tape cartridges - DLT1 format.

Information technology - Data interchange on 12,7 mm, 112-track magnetic tape cartridges - DLT 2 format

Section 1 - General

1 Scope

This International Standard specifies the physical and magnetic characteristics of a 12,7 mm wide, 112-track magnetic tape cartridge, to enable interchangeability of such cartridges. It also specifies the quality of the recorded signals, a format - called Digital Linear Tape 2 (DLT 2) - and a recording method. Together with a labelling standard, e.g. ISO 1001, it allows full data interchange by means of such magnetic tape cartridges.

2 Conformance

2.1 Magnetic tape cartridges

A magnetic tape cartridge shall be in conformance with this International Standard if it satisfies all mandatory requirements of this International Standard. The tape requirements shall be satisfied throughout the extent of the tape.

2.2 Generating systems

A system generating a magnetic tape cartridge for interchange shall be entitled to claim conformance with this International Standard if all the recordings that it makes on a tape according to 2.1 meet the mandatory requirements of this International Standard.

2.3 Receiving systems

A system receiving a magnetic tape cartridge for interchange shall be entitled to claim conformance with this International Standard if it is able to handle any recording made on a tape according to 2.1.

3 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 1001:1986, Information processing - File structure and labelling of magnetic tapes for information interchange.

ISO 1302:1992, Technical drawings - Method of indicating surface texture.