

INTERNATIONAL  
STANDARD

**ISO/IEC**  
**13963**

First edition  
1995-04-15

---

---

**Information technology — Data  
interchange on 90 mm optical disk  
cartridges — Capacity: 230 megabytes per  
cartridge**

*Technologies de l'information — Échange de données sur cartouches  
pour disque optique de diamètre 90 mm — Capacité: 230 mégabytes par  
cartouche*



**Contents**

	<b>Page</b>
<b>Section 1 - General</b>	<b>1</b>
<b>1 Scope</b>	<b>1</b>
<b>2 Conformance</b>	<b>1</b>
<b>2.1 Optical disk cartridge (ODC)</b>	<b>1</b>
<b>2.2 Generating system</b>	<b>1</b>
<b>2.3 Receiving system</b>	<b>2</b>
<b>2.4 Compatibility statement</b>	<b>2</b>
<b>3 Normative reference</b>	<b>2</b>
<b>4 Definitions</b>	<b>2</b>
<b>4.1 band</b>	<b>2</b>
<b>4.2 case</b>	<b>2</b>
<b>4.3 Channel bit</b>	<b>2</b>
<b>4.4 clamping zone</b>	<b>2</b>
<b>4.5 control track</b>	<b>2</b>
<b>4.6 Cyclic Redundancy Check (CRC)</b>	<b>2</b>
<b>4.7 defect management</b>	<b>2</b>
<b>4.8 disk reference plane</b>	<b>2</b>
<b>4.9 embossed mark</b>	<b>2</b>
<b>4.10 entrance surface</b>	<b>2</b>
<b>4.11 Error Correction Code (ECC)</b>	<b>2</b>
<b>4.12 field</b>	<b>2</b>
<b>4.13 format</b>	<b>2</b>
<b>4.14 fully embossed disk</b>	<b>2</b>
<b>4.15 fully rewritable disk</b>	<b>2</b>
<b>4.16 groove</b>	<b>2</b>
<b>4.17 hub</b>	<b>2</b>
<b>4.18 interleaving</b>	<b>2</b>
<b>4.19 Kerr rotation</b>	<b>3</b>
<b>4.20 land and groove</b>	<b>3</b>
<b>4.21 logical track</b>	<b>3</b>
<b>4.22 mark</b>	<b>3</b>
<b>4.23 optical disk</b>	<b>3</b>
<b>4.24 optical disk cartridge (ODC)</b>	<b>3</b>
<b>4.25 partially embossed disk</b>	<b>3</b>
<b>4.26 physical track</b>	<b>3</b>
<b>4.27 physical track group</b>	<b>3</b>
<b>4.28 pitch</b>	<b>3</b>
<b>4.29 polarization</b>	<b>3</b>

© ISO/IEC 1995

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

<b>4.30</b>	read power	<b>3</b>
<b>4.31</b>	recording layer	<b>3</b>
<b>4.32</b>	Reed-Solomon code	<b>3</b>
<b>4.33</b>	sector	<b>3</b>
<b>4.34</b>	spindle	<b>3</b>
<b>4.35</b>	substrate	<b>3</b>
<b>4.36</b>	ZCAV	<b>3</b>
<b>4.37</b>	zone	<b>3</b>
<b>5</b>	<b>Conventions and notations</b>	<b>3</b>
<b>5.1</b>	Representation of numbers	<b>3</b>
<b>5.2</b>	Names	<b>4</b>
<b>6</b>	<b>List of acronyms</b>	<b>4</b>
<b>7</b>	<b>General description of the optical disk cartridge</b>	<b>4</b>
<b>8</b>	<b>General requirements</b>	<b>5</b>
<b>8.1</b>	Environments	<b>5</b>
<b>8.1.1</b>	Testing environment	<b>5</b>
<b>8.1.2</b>	Operating environment	<b>5</b>
<b>8.1.3</b>	Storage environment	<b>5</b>
<b>8.1.4</b>	Transportation	<b>5</b>
<b>8.2</b>	Temperature shock	<b>6</b>
<b>8.3</b>	Safety requirements	<b>6</b>
<b>8.4</b>	Flammability	<b>6</b>
<b>9</b>	<b>Reference Drive</b>	<b>6</b>
<b>9.1</b>	Optical system	<b>6</b>
<b>9.2</b>	Optical beam	<b>7</b>
<b>9.3</b>	Read channels	<b>8</b>
<b>9.4</b>	Tracking	<b>8</b>
<b>9.5</b>	Rotation of the disk	<b>8</b>
<b>Section 2</b>	<b>Mechanical and physical characteristics</b>	<b>9</b>
<b>10</b>	<b>Dimensional and physical characteristics of the case</b>	<b>9</b>
<b>10.1</b>	General description of the case	<b>9</b>
<b>10.2</b>	Reference planes of the case	<b>9</b>
<b>10.3</b>	Dimensions of the case	<b>9</b>
<b>10.3.1</b>	Overall dimensions	<b>9</b>
<b>10.3.2</b>	Location hole	<b>10</b>
<b>10.3.3</b>	Alignment hole	<b>10</b>
<b>10.3.4</b>	Reference surfaces	<b>10</b>
<b>10.3.5</b>	Detents	<b>11</b>
<b>10.3.6</b>	Functional Areas	<b>11</b>
<b>10.3.7</b>	Spindle and head windows	<b>12</b>
<b>10.3.8</b>	Shutter	<b>13</b>
<b>10.3.9</b>	Path for shutter opener and shutter sensor notch	<b>13</b>
<b>10.3.10</b>	Mis-insert protections	<b>14</b>

10.3.11 Gripper slots	14
10.3.12 Label area	15
10.4 Mechanical characteristics	15
10.4.1 Material	15
10.4.2 Mass	15
10.4.3 Edge distortion	15
10.4.4 Compliance	15
10.4.5 Shutter opening force	15
<b>11 Dimensional, mechanical and physical characteristics of the disk</b>	<b>27</b>
11.1 General description of the disk	27
11.2 Reference axis and plane of the disk	27
11.3 Dimensions of the disk	27
11.3.1 Hub dimensions	27
11.3.2 Clamping zone	28
11.4 Mechanical characteristics	29
11.4.1 Material	29
11.4.2 Mass	29
11.4.3 Moment of inertia	29
11.4.4 Imbalance	29
11.4.5 Axial deflection	29
11.4.6 Axial acceleration	29
11.4.7 Radial runout	29
11.4.8 Radial acceleration	30
11.4.9 Tilt	30
11.5 Optical characteristics	30
11.5.1 Index of refraction	30
11.5.2 Thickness of the substrate	30
11.5.3 Birefringence	30
11.5.4 Reflectance	30
<b>12 Interface between cartridge and drive</b>	<b>31</b>
12.1 Clamping method	31
12.2 Clamping force	31
12.3 Capture cylinder	31
12.4 Disk position in operating condition	31
<b>Section 3 - Format of information</b>	<b>33</b>
<b>13 Geometry of physical tracks</b>	<b>33</b>
13.1 Physical track shape	33
13.2 Direction of track spiral	33
<b>14 Track format</b>	<b>33</b>
14.1 Track number	33
14.2 Track layout	33
14.3 Clock frequencies and periods	33

14.4 Radial alignment	34
14.5 Sector number	34
<b>15 Sector format</b>	<b>34</b>
15.1 Sector layout	34
15.2 Sector Mark (SM)	35
15.3 VFO fields	36
15.4 Address Mark (AM)	36
15.5 ID fields	37
15.6 Postambles (PA)	37
15.7 Offset Detection Field (ODF)	37
15.8 Gap	37
15.9 Sync	37
15.10 Data field	37
15.10.1 User data bytes	37
15.10.2 CRC and ECC bytes	38
15.10.3 Resync bytes	38
15.11 Buffer field	38
<b>16 Recording code</b>	<b>38</b>
<b>17 Format of the Information Zone</b>	<b>39</b>
17.1 General description of the Information Zone	39
17.2 Division of the Information Zone	39
17.2.1 Initial Zone	40
17.2.2 Acquire Zone	40
17.2.3 Test Zones	40
17.2.4 Control Zones	41
17.2.5 Data Zone	41
17.2.6 Buffer Zone	41
<b>18 Format of the Data Zone</b>	<b>41</b>
18.1 Buffer tracks in the Data Zone	42
18.2 Defect Management Areas (DMAs)	42
18.3 Disk Definition Structure (DDS)	43
18.3.1 Fully rewritable disks	44
18.3.2 Fully embossed disks	45
18.3.3 Partially embossed disks	45
18.4 Partitioning	45
18.4.1 Fully rewritable disks	45
18.4.2 Partially embossed disks	45
18.4.3 Fully embossed disks	45
<b>19 Defect management</b>	<b>48</b>
19.1 Rewritable groups: Spare sector	48
19.1.1 Initialization of the disk	48

19.1.2 Certification	48
19.1.3 Disks not certified	48
19.1.4 Write procedure	49
19.1.5 Primary Defect List (PDL)	49
19.1.6 Secondary Defect List (SDL)	49
19.2 Embossed groups: Parity sectors	50
<b>Section 4 - Characteristics of embossed information</b>	<b>52</b>
<b>20 Method of testing</b>	<b>52</b>
20.1 Environment	52
20.2 Use of the Reference Drive	52
20.2.1 Optics and mechanics	52
20.2.2 Read power	52
20.2.3 Read channels	52
20.2.4 Tracking	52
20.3 Definition of signals	52
<b>21 Signals from grooves</b>	<b>55</b>
21.1 Cross-track signal	55
21.2 Cross-Track minimum signal	55
21.3 Push-pull signal	55
21.4 Divided push-pull signal	56
21.5 Phase depth	57
21.6 Track location	57
<b>22 Signals from Headers</b>	<b>57</b>
22.1 Sector Mark	57
22.2 VFO <sub>1</sub> and VFO <sub>2</sub>	57
22.3 Address Mark, ID field and Postamble	57
<b>23 Signals from embossed Recording fields</b>	<b>57</b>
<b>Section 5 - Characteristics of the recording layer</b>	<b>58</b>
<b>24 Method of testing</b>	<b>58</b>
24.1 Environment	58
24.2 Reference Drive	58
24.2.1 Optics and mechanics	58
24.2.2 Read power	58
24.2.3 Read channel	58
24.2.4 Tracking	58
24.3 Write conditions	58
24.3.1 Write pulse	58
24.3.2 Write power and pulse width	59
24.3.3 Write magnetic field	60
24.4 Erase conditions	60

24.4.1 Erase power	60
24.4.2 Erase magnetic field	60
24.5 Definition of signals	60
<b>25 Magneto-optical characteristics</b>	<b>60</b>
25.1 Figure of merit	59
25.2 Imbalance of the magneto-optical signal	61
<b>26 Write characteristics</b>	<b>61</b>
26.1 Resolution	61
26.2 Narrow-band signal-to-noise ratio	61
26.3 Cross-talk	62
<b>27 Erase characteristics</b>	<b>62</b>
<b>Section 6 - Characteristics of user data</b>	<b>63</b>
<b>28 Method of testing</b>	<b>63</b>
28.1 Environment	63
28.2 Reference Drive	63
28.2.1 Optics and mechanics	63
28.2.2 Read power	63
28.2.3 Read amplifiers	63
28.2.4 Analog-to-binary converters	63
28.2.5 Error correction	63
28.2.6 Tracking	63
<b>29 Minimum quality of a sector</b>	<b>63</b>
29.1 Headers	64
29.1.1 Sector Mark	64
29.1.2 ID fields	64
29.2 User-written data	64
29.3 Embossed data	64
<b>30 Data interchange requirements</b>	<b>64</b>
30.1 Tracking	64
30.2 User-written data	64
30.3 Embossed data	64
30.4 Quality of disk	64
<b>Annexes</b>	
A - Edge distortion test	65
B - Compliance test	66
C - Track deviation measurement	68
D - CRC for ID fields	72
E - Format of the Data field of a sector	73
F - Contents of the Control Zones	76

<b>G</b> - Guidelines for sector replacement	<b>84</b>
<b>H</b> - Measurement of the figure of merit	<b>85</b>
<b>J</b> - Read power, write power and erase power	<b>86</b>
<b>K</b> - Test method for measuring the adsorbent force of the hub	<b>87</b>
<b>L</b> - Derivation of the operating climatic environment	<b>89</b>
<b>M</b> - Air cleanliness class 100 000	<b>93</b>
<b>N</b> - Position of the cartridge relative to the reference planes	<b>94</b>
<b>P</b> - Transportation	<b>95</b>
<b>Q</b> - Office environment	<b>96</b>
<b>R</b> - Relaxation by zones of the requirements for signals	<b>97</b>
<b>S</b> - Values to be implemented in existing and future standards	<b>98</b>



## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrical Commission) form the specialised system for world-wide standardization. National Bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 13963 was prepared by the European Association for Standardizing Information and Communication Systems, ECMA, (as ECMA-201) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

Annexes A, B, D, E, F, H, K, M, N, R form an integral part of this International Standard. Annexes C, G, J, L, P, Q and S are for information only.

## Introduction

Technical Committee ECMA TC31 for Optical Disk Cartridges (ODC) was set up in 1984. The Committee made major contributions to ISO/IEC JTC1/SC23 for the development of standards for 90 mm, 120 mm, 130 mm, 300 mm and 356 mm ODCs.

A trend towards more Types and increasing capacities is followed by 90 mm ODCs based on the optical disk cartridge specified in ISO/IEC 10090.

This International Standard belongs to the 90 mm ODC series. It specifies three Types providing a capacity of 230 Megabytes per cartridge.

# **Information technology - Data interchange on 90 mm optical disk cartridges - Capacity: 230 megabytes per cartridge**

## **Section 1 : General**

### **1 Scope**

This International Standard specifies the characteristics of 90 mm Optical Disk Cartridges (ODC) with a capacity of 230 Mbytes per Cartridge. The Standard specifies three related, but different implementations of such cartridges, viz.

**Type R/W** Provides for data to be written, read and erased many times over the whole recording surface of the disk using the thermo-magnetic and magneto-optical effects.

**Type P-ROM** Provides for a part of the disk surface to be embossed by stamping or other means. This part of the disk is read without recourse to the magneto-optical effect. All parts which are not embossed provide for data to meet the requirements of Type R/W.

**Type O-ROM** Provides for the whole of the disk surface to be embossed and reproduced by stamping or other means. This type of disk is read without recourse to the magneto-optical effect.

Type R/W, Type P-ROM and Type O-ROM are also referred to as "fully rewritable", "partially embossed" and "fully embossed", respectively.

This International Standard specifies

- the conditions for conformance testing and the Reference Drive;
- the environments in which the cartridges are to be operated and stored;
- the mechanical and physical characteristics of the cartridge, so as to provide mechanical interchangeability between data processing systems;
- the format of the information on the disk, both embossed and user-written; including the physical disposition of the tracks and sectors, the error correction codes, and the modulation method used;
- the characteristics of the embossed information on the disk;
- the magneto-optical characteristics of the disk, enabling processing systems to write data onto the disk;
- the minimum quality of user-written data on the disk, enabling data processing systems to read data from the disk.

This International Standard provides for interchange between optical disk drives. Together with a standard for volume and file structure, it provides for full data interchange between data processing systems.

### **2 Conformance**

#### **2.1 Optical disk cartridge (ODC)**

An optical disk cartridge claiming conformance with this International Standard shall specify its Type. It shall be in conformance if it meets all mandatory requirements specified herein for that Type.

Annex R specifies the zones of the disk in which the requirements for the signal characteristics given in the body of this International Standard shall be met, and the zones in which a relaxation of these requirements is permitted.

#### **2.2 Generating system**

A claim of conformance with this International Standard shall specify which Type(s) is (are) supported. A system generating an ODC for interchange shall be entitled to claim conformance with this International Standard if it meets the mandatory requirements of this Standard for the Type(s) specified.

### 2.3 Receiving system

A claim of conformance with this International Standard shall specify which Type(s) is (are) supported. A system receiving an ODC for interchange shall be entitled to claim conformance to this International Standard if it is able to process any recording made on the cartridge in accordance with 2.1 on the Type(s) specified.

### 2.4 Compatibility statement

A claim of conformance by a Generating or Receiving system with this International Standard shall include a statement listing any other ECMA and International Standard supported. This statement shall specify the number of the Standard(s), the ODC type(s) supported (where appropriate) and whether support includes reading only or both reading and writing.

## 3 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the standard listed below. Members of IEC and ISO maintain registers of currently valid standards.

IEC 950:1991, *Safety of information technology equipment including electrical business equipment*.