
**Information technology — Control
network protocol —**

**Part 1:
Protocol stack**

*Technologies de l'information — Protocole de réseau de contrôle —
Partie 1: Pile de protocole*



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

page

Foreword	7
Introduction.....	8
1 Scope.....	9
2 Normative references.....	9
3 Terms and definitions	9
4 Symbols and abbreviations.....	11
4.1 Symbols and graphical representations.....	11
4.2 Abbreviations.....	12
5 Overview of protocol layering.....	13
6 MAC sublayer.....	15
6.1 Service provided.....	15
6.2 Interface to the link layer	15
6.3 Interface to the physical layer.....	16
6.4 MPDU format.....	17
6.5 Predictive <i>p</i> -persistent CSMA — overview description	17
6.6 Idle channel detection.....	18
6.7 Randomising.....	19
6.8 Backlog estimation.....	19
6.9 Optional priority.....	20
6.10 Optional collision detection	21
6.11 Beta1, Beta2 and Preamble Timings	21
7 Link layer.....	23
7.1 Assumptions.....	23
7.2 Service provided.....	24
7.3 CRC	24
7.4 Transmit algorithm	25
8 Network layer	26
8.1 Assumptions.....	26
8.2 Service provided.....	27
8.3 Service interface.....	27
8.4 Internal structuring of the network layer	28
8.5 NPDU format	28
8.6 Address recognition.....	29
8.7 Routers	29
8.8 Routing algorithm.....	30
8.9 Learning algorithm — subnets	30
9 Transaction control sublayer	30
9.1 Assumptions.....	30
9.2 Service provided.....	31
9.3 Service interface.....	31
9.4 State variables	31
9.5 Transaction control algorithm	32
10 Transport layer	32
10.1 Assumptions.....	32
10.2 Service provided.....	32
10.3 Service interface.....	33
10.4 TPDU types and formats.....	33

10.5	Protocol diagram	35
10.6	Transport protocol state variables	35
10.7	Send algorithm	35
10.8	Receive algorithm.....	36
10.9	Receive transaction record pool size and configuration engineering.....	36
10.9.1	General	36
10.9.2	Number of retries.....	36
10.9.3	Transport layer timers.....	37
11	Session layer	38
11.1	Assumptions.....	38
11.2	Service Provided	38
11.3	Service interface.....	39
11.4	Internal structure of the session layer	40
11.5	SPDU types and formats	41
11.6	Protocol timing diagrams	42
11.7	Request-response state variables	44
11.8	Request-response protocol — client part.....	45
11.9	Request-response protocol — server part	45
11.10	Request-response protocol timers.....	45
11.11	Authentication protocol.....	46
11.12	Encryption algorithm	46
11.13	Retries and the role of the checksum function	46
11.14	Random Number Generation	47
11.15	Using Authentication	47
12	Presentation/application layer	47
12.1	Assumptions.....	47
12.2	Service provided.....	47
12.3	Service interface.....	48
12.4	APDU types and formats	49
12.5	Protocol diagrams	50
12.6	Application protocol state variables	51
12.7	Request - response messaging in offline state.....	51
12.8	Network variables.....	52
12.8.1	General	52
12.8.2	Network variable processing	52
12.9	Error notification to the application program.....	53
12.9.1	General	53
12.9.2	Error notification for messages	53
12.9.3	Error notification for network variables	53
13	Network management & diagnostics	53
13.1	Assumptions.....	53
13.2	Services provided.....	54
13.3	Network management and diagnostics application structure.....	54
13.4	Node states	54
13.5	Using the network management services.....	55
13.5.1	General	55
13.5.2	Addressing considerations	55
13.5.3	Making network configuration changes.....	56
13.5.4	Downloading an Application Program	56
13.5.5	Error handling conditions (informative).....	56
13.6	Using router network management commands	59
13.7	NMPDU formats and types	60
13.7.1	General	60
13.7.2	Query ID.....	60
13.7.3	Respond to query	61
13.7.4	Update domain.....	61
13.7.5	Leave domain.....	61
13.7.6	Update key	61

13.7.7	Update address.....	62
13.7.8	Query address	62
13.7.9	Query network variable configuration.....	62
13.7.10	Update group address	62
13.7.11	Query domain	62
13.7.12	Update network variable configuration.....	62
13.7.13	Set node mode.....	63
13.7.14	Read memory.....	63
13.7.15	Write memory.....	63
13.7.16	Checksum recalculate.....	63
13.7.17	Install	64
13.7.18	Memory refresh.....	78
13.7.19	Query SI.....	78
13.7.20	Network variable value fetch.....	79
13.7.21	Manual service request message	79
13.7.22	Network management escape code	79
13.7.23	Router mode	80
13.7.24	Router clear group or subnet table	80
13.7.25	Router group or subnet table download.....	80
13.7.26	Router group forward.....	80
13.7.27	Router subnet forward.....	80
13.7.28	Router Do Not forward group.....	80
13.7.29	Router Do Not forward subnet.....	80
13.7.30	Router group or subnet table report	80
13.7.31	Router status	81
13.7.32	Router half escape code.....	81
13.8	DPDU types and formats	81
13.8.1	General	81
13.8.2	Query status.....	81
13.8.3	Proxy status	85
13.8.4	Clear status	85
13.8.5	Query transceiver status	85
Annex A	(normative) Reference implementation	86
A.1	General	86
A.2	Predictive CSMA algorithm	86
A.3	LPDU transmit algorithm	141
A.4	LPDU receive algorithm	143
A.5	Routing algorithm.....	144
A.6	Learning algorithm	145
A.7	Transaction control algorithm	145
A.8	Network layer algorithm.....	152
A.9	TPDU and SPDU send algorithm with authentication	168
A.10	Application Layer	223
A.11	Network Management Commands.....	278
A.12	Configuration data structures.....	315
A.13	Include files for the reference implementation	334
A.14	Application protocol state variables and address recognition Structures	363
A.15	Query-id data structures.....	366
A.16	Respond to query data structure.....	366
A.17	Update somain data structures.....	367
A.18	Leave domain data structures	367
A.19	Update key data structures	367
A.20	Update address data structures	367
A.21	Query address data structures	368
A.22	Query NV Cnfg data structures.....	369
A.23	Update group address data structures	369
A.24	Query domain data structures	369
A.25	Update network variable configuration data structures.....	370
A.26	Set node mode data structures.....	370

A.27	Read memory data structures.....	370
A.28	Write memory data structures	371
A.29	Checksum recalculate data structures	371
A.30	Install command data structures	371
A.31	Memory refresh data structures	380
A.32	Query SI data structures.....	380
A.33	NV fetch data structures	380
A.34	Manual service request message ddata structures.....	380
A.35	Product query data structures	381
A.36	Router mode data structures	381
A.37	Router table clear group or subnet table data structures.....	381
A.38	Router group or subnet download data structures	381
A.39	Router group forward data structures	382
A.40	Router subnet forward data structures.....	382
A.41	Router group No-Forward data structures	382
A.42	Router subnet No-Forward data structures	382
A.43	Group / subnet table report data structures	383
A.44	Router status data structures	383
A.45	Query status data structures	383
A.46	Proxy status data structures.....	384
A.47	Clear status data structures.....	384
A.48	Query transceiver status data structures	384
Annex B (normative) Additional Data Structures.....		385
B.1	General	385
B.1.1	System image	385
B.1.2	Application image.....	385
B.1.3	Network image	386
B.2	Read-only structures.....	386
B.2.1	Fixed read-only data structures.....	386
B.2.2	Read-only structure field descriptions.....	387
B.3	Domain table.....	390
B.3.1	Domain table field descriptions	391
B.4	Address table.....	391
B.4.1	Declaration of group address format	392
B.4.2	Group address field descriptions	392
B.4.3	Declaration of subnet/node address format.....	392
B.4.4	Subnet/node address field descriptions	393
B.4.5	Declaration of broadcast address format	393
B.4.6	Broadcast address field descriptions	393
B.4.7	Declaration of turnaround address format	393
B.4.8	Turnaround address field descriptions.....	394
B.4.9	Declaration of protocol processor's address format	394
B.4.10	Protocol processor address field descriptions.....	394
B.4.11	Timer field descriptions	394
B.5	Network variable tables - informative.....	395
B.5.1	Network variable configuration table field descriptions - informative	396
B.5.2	Network variable alias table field descriptions - informative.....	397
B.5.3	Network variable fixed table field descriptions - informative	397
B.6	Self-Identification structures.....	397
B.6.1	SI Structure field descriptions	398
B.6.2	NV descriptor table field descriptions.....	398
B.6.3	SNVT table extension records	399
B.6.4	SNVT alias field descriptions	400
B.6.5	Version 2 SI data.....	400
B.7	Configuration structure	403
B.7.1	General	403
B.7.2	Configuration structure field descriptions	404
B.8	Statistics relative structure	405
Annex C (informative) Behavioral characteristics		407

C.1	Channel capacity and throughput	407
C.2	Network metrics	408
C.3	Transaction metrics	409
C.4	Boundary conditions — power-up	410
C.5	Boundary conditions — high load	410
Annex D (normative)	PDU summary	411
Annex E (normative)	Naming and addressing	413
E.1	Address types and formats	413
E.2	Domains	413
E.3	Subnets and nodes	414
E.4	Groups	414
E.5	Unique_Node_ID and node address assignment	415
E.6	NPDU addressing	416
Annex F (normative)	List of patents that pertain to this International Standard	418
Bibliography	420

Figures

Figure 1 — Network topology & symbols	12
Figure 2 — Protocol terminology	12
Figure 3 — Protocol layering	14
Figure 4 — Interface between the MAC and the link layers	16
Figure 5 — MPDU/LPDU format	17
Figure 6 — Predictive <i>p</i> -persistent CSMA concepts and parameters	18
Figure 7 — Allocation of priority slots within the Busy Channel Packet Cycle	20
Figure 8 — CRC register state behaviour example	25
Figure 9 — Single channel topologies	26
Figure 10 — Typical tree-like domain topology	27
Figure 11 — Network service interface	28
Figure 12 — Network layer—internal structure	28
Figure 13 — NPDU format	28
Figure 14 — Transaction control service interface	31
Figure 15 — Transport interface to upper layers	33
Figure 16 — TPDU types and formats	34
Figure 17 — Transport protocol diagram for multicast message with a loss of both the message and the ACK TPDU	35
Figure 18 — Transport protocol—Send FSM	36
Figure 19 — Transport protocol—Receive FSM	36
Figure 20 — Probability of transaction completion in <i>k</i> Retries	37

Figure 21 — Methodology for calculating timer values	38
Figure 22 — Session layer interface to application layer	39
Figure 23 — Session layer—internal structuring.....	40
Figure 24 — SPDU types and formats	41
Figure 25 — Non-Idempotent request with multiple SPDU losses.....	43
Figure 26 — Secure idempotent request with multiple SPDU losses	44
Figure 27 — Request-response protocol—client FSM.....	45
Figure 28 — Request-response protocol—simplified server FSM.....	45
Figure 29 — Application layer interface	48
Figure 30 — APDU format.....	49
Figure 31 — Application protocol diagram for multicast acknowledged transaction.....	50
Figure 32 — Application protocol diagram for multicast request/response transaction.....	51
Figure B.1 — SI data	400
Figure C.1 — Probability of successful delivery over k hops	409
Figure D.1 — Protocol PDU summary	412
Figure E.1 — Physical topology and logical addressing (single domain)	415
Figure E.2 — NPDU/TPDU/SPDU addressing—physical address formats.....	416

Tables

Table 1 — Application layer primitives	48
Table 2 — Resource codes	65
Table 3 — Space of the property ID.....	65
Table B.1 — Buffer size encodings.....	389
Table B.2 — Buffer Count Encodings	390
Table B.3 — Encoding of timer field values	395
Table B.4 — Buffer timeout encoding	405
Table C.1 — Key throughput parameters.....	408
Table E.1 — NPDU/TPDU/SPDU addressing - logical address formats	416
Table F.1 — Patents in the US.....	418
Table F.2 — Patents in Europe and other countries.....	419

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

ISO/IEC 14908-1 was prepared by CEN/TC 247 and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by the national bodies of ISO and IEC.

ISO/IEC 14908 consists of the following parts, under the general title *Information technology — Control network protocol*:

- *Part 1: Protocol stack*
- *Part 2: Twisted pair communication*
- *Part 3: Power line channel specification*
- *Part 4: IP communication*

Introduction

This International Standard has been prepared to provide mechanisms through which various vendors of local area control networks may exchange information in a standardised way. It defines communication capabilities.

This International Standard is to be used by all involved in design, manufacture, engineering, installation and commissioning activities.

The International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC) draw attention to the fact that it is claimed that compliance with this International Standard may involve the use of patents held by Echelon Corporation.

The ISO and IEC take no position concerning the evidence, validity and scope of this patent right. The holder of this putative patent right has assured the ISO and IEC that they are willing to negotiate free of charge licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of the putative patent rights is registered with the ISO and IEC. Information may be obtained from:

Echelon Corporation, 4015 Meridian Avenue, San Jose, CA 94304, USA, phone +1-408-938-5234, fax: +1-408-790-3800 <http://www.echelon.com>.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights other than those identified above. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

INFORMATION TECHNOLOGY – CONTROL NETWORK PROTOCOL –

Part 1: Protocol stack

1 Scope

This specification applies to a communication protocol for local area control networks. The protocol provides peer-to-peer communication for networked control and is suitable for implementing both peer-to-peer and master-slave control strategies. This specification describes services in layers 2 to 7. In the layer 2 (data link layer) specification, it also describes the MAC sub-layer interface to the physical layer. The physical layer provides a choice of transmission media. The interface described in this specification supports multiple transmission media at the physical layer. In the layer 7 specification, it includes a description of the types of messages used by applications to exchange application and network management data.

2 Normative references

None.