

**INTERNATIONAL
STANDARD**

**ISO/IEC
15205
IEEE
Std 1496**

First edition
2000-06

SBus – Chip and module interconnect bus



Reference number
ISO/IEC 15205:2000(E)
IEEE
Std 1496, 1993 Edition

Abstract: An input/output expansion bus with a 32- or 64-bit width is described in this standard. The SBus is designed for systems requiring a small number expansion ports. SBus Cards may be connected to a standard Sbus Connector mounted on the motherboard. SBus Devices may also be attached to the SBus directly on the system's motherboard. The dimensions of the SBus Card are 83,8 mm by 146,7 mm, making the cards appropriate for small computer systems that make extensive use of highly integrated circuits. The SBus Cards are designed to be installed in a plane parallel to the system's motherboard as mezzanine cards. They are designed to provide connections for devices external to the computer system through an exposed back panel. The form factor is useful in Futurebus+, VMEbus, desktop computers, and similar applications. The SBus has the capability of transferring data at rates up to 168 Mbytes/s, depending on the implementation options selected.

SBus Cards may either serve as Masters on the bus, providing all virtual address information as well as the data to be transferred, or they may serve as Slaves on the bus, providing data transfer according to the requirements of some other SBus Master. The SBus Master for a data transfer is selected by an arbitration process managed by the single SBus Controller on the SBus. The SBus Controller provides a virtual to physical address translation service.

Keywords: I/O bus, SBus, SBus Card, Standard for Boot Firmware.

The Institute of Electrical and Electronics Engineers, Inc.
345 East 47th Street, New York, NY 10017-2394, USA

Copyright © 1993 by the Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. First published in 1993.

ISBN 2-8318-5165-3

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

CONTENTS

	Page
FOREWORD	4
INTRODUCTION	5
Clause	
1 General.....	8
1.1 Scope and object	8
1.2 Normative references.....	8
2 Definitions, usage of special terms, acronyms, and editorial conventions	9
2.1 Definitions	9
2.2 Usage of special terms	13
2.3 Acronyms.....	13
2.4 Editorial conventions.....	13
3 Overview.....	14
3.1 System overview.....	14
3.2 Overview of configurations.....	16
3.3 General design information	19
3.4 Performance	21
4 Signal definitions	23
4.1 CLK signal	23
4.2 RST* signal	24
4.3 PA[27:0] signals.....	25
4.4 SEL* signal.....	25
4.5 AS* signal.....	26
4.6 BR* signal.....	26
4.7 BG* signal	26
4.8 D[31:0], D[63:0], and DP signals	27
4.9 SIZ[2:0] signals.....	28
4.10 RD signal.....	28
4.11 ACK[2:0]* signals.....	29
4.12 LERR* signal	31
4.13 INT[7:1]* signals	32
5 SBus cycle definitions	33
5.1 Arbitration Phase	33
5.2 Translation Phase	34
5.3 Extended Transfer Information Phase	36
5.4 Transfer Phase	40
5.5 Dual function SBus Devices.....	58
5.6 Exception conditions.....	59
5.7 Extended Transfer locking protocol.....	60

Clause	Page
6 SBus electrical requirements.....	62
6.1 Power	62
6.2 Electronic characteristics	63
6.3 Electronic timing requirements	66
6.4 Compliance requirements	69
7 Environmental requirements.....	69
7.1 Operating range.....	69
8 Mechanical requirements	70
8.1 SBus Slot Connector.....	70
8.2 SBus Card	74
8.3 Panel installation	88
9 SBus program interface	89
9.1 Introduction.....	89
9.2 Program format and interpretation	89
9.3 Required FCode attributes	90
9.4 FCode language	90
9.5 Special functions of Word 0	90
Annex A (informative) Compliance checklist	92
Annex B (informative) Known implementation variations.....	97
Bibliography	101
Index	102

SBus – CHIP AND MODULE INTERCONNECT BUS

FOREWORD

- 1) ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 15205 was prepared by subcommittee 26: Microprocessor systems, of ISO/IEC joint technical committee 1: Information technology.

International Standards are drafted in accordance with ISO/IEC Directives, Part 3.

Annexes A and B are for information only.

This standard must be used in conjunction with the latest edition of the following standard: IEEE Std 1275.



International Electrotechnical Commission • 3, rue de Varembe, PO Box 131,
CH-1211-Geneva 20, Switzerland • Telephone: +41 22 919 0211 •
Telefax: +41 22 919 0300 • e-mail: inmail@iec.ch •
URL: <http://www.iec.ch>

INTRODUCTION

(This introduction is not a normative part of ISO/IEC 15205:2000, but is included for information only.)

This IEEE standard documents the implementation of the popular SBus interface. The SBus, originally developed and documented by Sun Microsystems as an I/O expansion bus, uses a standard form factor SBus Card that is a suitable size for the use of VLSI circuits in small computers. It has a high bandwidth and is capable of data transfer 8, 16, 32, or 64 bits in width. This standard includes the set of functionality originally documented by the *SBus Specification B.0* (Sun Microsystems Part #800.5922-10, Revision A, December 1990) and clarifies, corrects, and extends that functionality as required. The IEEE P1275 Working Group is developing a standard for boot firmware, which will define and document the initialization and boot interface for SBus Cards.

Special thanks are due to Bob Snively (P1496 Working Group draft technical editor) for the many hours spent in converting this document from the original *SBus Specification B.0* and editing it into its final form. Also deserving of thanks are Jim Lyle (P1496 Working Group vice Chair), Barbara Vance (P1496 Working Group former Secretary), Bob Gianni (P1496 Working Group Secretary), and Steve Hix (P1496 draft document editor) for their support in the Committee work and the generation of this document.

The following people were members of the P1496 Working Group that approved the draft for submission to IEEE for sponsor ballot:

Wayne Fischer, Chair

James Lyle, Co-Chair

Robert Gianni, Secretary

Robert Snively, Draft Technical Editor

Sanjay Adkar
Steven W. Aiken
Ray S. Alderman
Ravi Anantharaman
James Antonellis
Tom Armbruster
Jon K. Bennett
C.J. Beynon
Paul Borrill
Mike Chastain
Gary Croak
Scott Eichmann
Robert Elliott
Jurgen Fey
Larry Fiedler
William A. Fox
Paul Fulton
Brad Giffel

Steve Golson
Anthony A. Goodloe
James N. Hardage, Jr.
Hans Heilborn
Kai Holz
Timothy Hu
Mohammad Issa
Shinkyō Kaku
Kuljeet Kalkat
Thomas Kappler
Bill Keshlear
Gary Kidwell
Erik Kristenson
Ernst H. Kristiansen
Joel Libove
James Ludemann
Susan Mason
Shrenik Mehta
Donald J. Murphy

Elwood Parsons
Heinz Piorunneck
Jack Regula
Eayne Rickard
Michael Saari
Siamak Salimpour
Gary Sloane
Martin Sodos
Richard Spratt
Mike Strang
Lars Themsjö
David Therrien
Istvan Vadasz
Barbara Vance*
Naor Wallach
Eike Waltz
Leo Yuan
Janusz Zalewski

* Former Secretary

The following persons were on the balloting committee:

Amir Abouelnaga	Larry E. Gerald	Richard Mueller
Edward W. Aichinger	Robert R. Gianni	Michael Orlovsky
Ray S. Alderman	Steve Golson	Mira Pauker
Richard P. Ames	Julio Gonzalez-Sanz	Philip K. Piele
Keith D. Anthony	John Griffith	Rochit Rajsuman
Behrooz Bandall	Hans H. Heilborn	Brian Ramelson
Chris Bezirtzoglou	Zoltan R. Hunor	Gary Sloane
Michael L. Bradley	Edgar Jacques	Bob Snively
Scott M. Buck	David V. James	Michael Teener
Steven Cobb	Horace Jones	Joseph P. Trainor
Robert Crowde	W. Frederick Ki	Robert Tripi
Doug Degroot	Ernst H. Kristiansen	Rudolf Usselmann
Dante Del Corso	Lak Ming Lam	Clarence M. Weaver
Samuel Duncan	Gerry Laws	Michael Wenzel
Wilhelm P. Evertz	Boon Lum Lim	Andrew Wilson
Wayne Fischer	Marlyn Miner	Robert J. Wood
Chee K. Fong	William E. Molyneaux	David L. Wright
Joseph D. George		Oren Yuen

When the IEEE Standards Board approved this standard on June 17, 1993, it had the following membership:

Wallace S. Read, *Chair* **Donald C. Loughry, *Vice Chair***
Andrew G. Salem, *Secretary*

Gilles A. Baril	Ben C. Johnson	T. Don Michael*
Clyde R. Camp	Walter J. Karplus	Marco Migliaro
Donald C. Fleckenstein	Lorraine C. Kevra	L. John Rankine
Jay Forster*	E. G. Al Kiener	Arthur K. Reilly
David F. Franklin	Ivor N. Knight	Ronald H. Reimer
Ramiro Garcia	Joseph L. Koepfinger*	Gary S. Robinson
Donald N. Heirman	D. N. Jim Logothetis	Leonard L. Tripp
Jim Isaak		Donald W. Zipse

* Member Emeritus

Also included are the following nonvoting IEEE Standards Board liaisons:

Satish K. Aggarwal
James Beall
Richard B. Engelman
David E. Soffrin
Stanley Warshaw

Paula M. Kelty
IEEE Standards Project Editor

IEEE Standards documents are developed within the Technical Committees of the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Board. Members of the committees serve voluntarily and without compensation. They are not necessarily members of the Institute. The standards developed within IEEE represent a consensus of the broad expertise on the subject within the Institute as well as those activities outside of IEEE that have expressed an interest in participating in the development of the standard.

Use of an IEEE Standard is wholly voluntary. The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE Standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard. Every IEEE Standard is subjected to review at least every five years for revision or reaffirmation. When a document is more than five years old and has not been reaffirmed, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE Standard.

Comments for revision of IEEE Standards are welcome from any interested party, regardless of membership affiliation with IEEE. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments.

Interpretations: Occasionally questions may arise regarding the meaning of portions of standards as they relate to specific applications. When the need for interpretations is brought to the attention of IEEE, the Institute will initiate action to prepare appropriate responses. Since IEEE Standards represent a consensus of all concerned interests, it is important to ensure that any interpretation has also received the concurrence of a balance of interests. For this reason IEEE and the members of its technical committees are not able to provide an instant response to interpretation requests except in those cases where the matter has previously received formal consideration.

Comments on standards and requests for interpretations should be addressed to:

Secretary, IEEE-SA Standards Board
445 Hoes Lane
P.O. Box 1331
Piscataway, NJ 08855-1331
USA

Note: Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken with respect to the existence or validity of any patent rights in connection therewith. The IEEE shall not be responsible for identifying all patents for which a license may be required by an IEEE standard or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

Authorization to photocopy portions of any individual standard for internal or personal use is granted by the Institute of Electrical and Electronics Engineers, Inc., provided that the appropriate fee is paid to Copyright Clearance Center. To arrange for payment of licensing fee, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; (508) 750-8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

SBus – CHIP AND MODULE INTERCONNECT BUS

1 General

1.1 Scope and object

SBus is a high performance computer I/O interface for connecting integrated circuits and SBus Cards to a computer system motherboard. This standard defines the mechanical, electrical, environmental, and protocol requirements for the design of SBus Cards and the computer system motherboard that supports those cards.

Every SBus Card shall implement appropriate self-descriptive and initialization firmware using FCode, which is similar to the Forth programming language. The details of this firmware standard are beyond the scope of this standard.¹⁾ In addition, other software interfaces may be used for communication with SBus Cards.

SBus is intended to provide a high performance I/O bus interface with a small mechanical form factor. The small size, high levels of integration, and low power usage of SBus Cards enable them to be used in laptop computers, compact desktop computers, and other applications requiring similar characteristics. SBus Cards are mounted in a plane parallel to the motherboard of the computer system, allowing the computer system to have a low profile. SBus is not designed as a general purpose backplane bus.

SBus allows transfers to be in units of 8, 16, 32, or 64 bits. Burst transfers are allowed to further improve performance. SBus allows a number of SBus Master devices to arbitrate for access to the bus. The chosen SBus Master provides a 32-bit virtual address which the SBus Controller maps to the selection of the proper SBus Slave and the development of the 28-bit physical address for that Slave. The selected SBus Slave then performs the data transfers requested by the SBus Master. Simple SBus Cards may be designed to operate solely as Slaves on the SBus.

1.2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of IEC and ISO maintain registers of currently valid International Standards.

IEEE Std 1275:1994, IEEE Standard for Boot (Initialization Configuration) Firmware: Core Requirements and Practices²⁾

¹⁾ A firmware interface standard is under consideration.

²⁾ IEEE publications are available from the Institute of Electrical and Electronics Engineers, 445 Hoes Lane, P.O. Box 1331, Piscataway, NJ 08855-1331, USA (standards.ieee.org/).