INTERNATIONAL STANDARD

15307

First edition 1997-12-01

Information technology — Data interchange on 12,7 mm 128-track magnetic tape cartridges — DLT 4 format

Technologies de l'information — Échange de données sur cartouches de bande magnétique de 12,7 mm, 128 pistes — Format DLT 4



Contents

	Page
Section 1 - General	1
1 Scope	1
2 Conformance	1
2.1 Magnetic tape cartridges2.2 Generating systems	1 1
2.3 Receiving systems	1
3 Normative references	1
4 Definitions	1
 4.1 Average Signal Amplitude 4.2 azimuth 4.3 back surface 4.4 Beginning-Of-Tape marker (BOT) 	1 1 1 1
4.5 byte	1
4.6 cartridge	2
4.7 Cyclic Redundancy Check (CRC) character4.8 Early Warning (EW)	2
4.9 Error-Detecting Code (EDC)	2
4.10 End-Of-Tape marker (EOT)	2
4.11 Entity	2
4.12 Error-Correcting Code (ECC)	2
4.13 flux transition position	2
4.14 flux transition spacing	2
4.15 Logical Block	2
4.16 logical track	2
4.17 magnetic tape	2
4.18 Master Standard Reference Tape	2
4.19 object	2
4.20 page	2
4.21 physical block	2
4.22 physical recording density	2
4.23 physical track	2
4.24 Record	2
4.25 Reference Edge	3
4.26 Reference Field	3
4.27 Secondary Standard Reference Tape	3
4.28 Standard Reference Amplitude (SRA)	3
4.29 Standard Reference Current	3
4.30 Test Recording Current	3
4.31 Typical Field	3

©ISO/IEC 1997

All rights reserved. Unless otherwise specified no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher ISO/IEC Copyright Office · Case Postale 56 · CH-1211 Genève 20 · Switzerland Printed in Switzerland

5 Conventions and notations	3
5.1 Representation of numbers	3
5.2 Dimensions 5.3 Names	3 3
5.4 Acronyms	3
6 Environment and safety	4
6.1 Cartridge and tape testing environment	4
6.2 Cartridge operating environment	4
6.3 Cartridge storage environment6.4 Safety	4
6.4.1 Safeness 6.4.2 Flammability	4 4
6.5 Transportation	5
Section 2 - Requirements for the unrecorded tape	5
7 Mechanical and electrical requirements	5
7.1 Material	5
7.2 Tape length	5 5
7.3 Width 7.4 Total thickness	5
7.5 Discontinuity	5
7.6 Longitudinal curvature	5
7.6.1 Requirement	5
7.6.2 Procedure	5
7.7 Out-of-Plane distortions	5
7.8 Cupping7.9 Roughness of the coating surfaces	5 5
7.9.1 Roughness of the back coating surface	5
7.9.2 Roughness of the magnetic coating surface	6
7.10 Coating adhesion	6
7.11 Layer-to-layer adhesion	6
7.11.1 Requirements	6
7.11.2 Procedure	6
7.12 Modulus of elasticity	7
7.12.1 Requirement 7.12.2 Procedure	7
7.13 Flexural rigidity	7
7.13.1 Requirement 7.13.2 Procedure	7 8
7.14 Tensile yield force	8
7.14.1 Procedure	8
7.15 Electrical resistance	8
7.15.1 Requirement 7.15.2 Procedure	8 8
7.16 Inhibitor tape7.17 Abrasivity	9 9

7.17.1 Requirement 7.17.2 Procedure	9
7.18 Light transmittance of the tape and the leader7.19 Coefficient of dynamic friction	9
 7.19.1 Requirements 7.19.2 Procedure for the measurement of the friction between the magnetic surface and the back surface 7.19.3 Procedure for the measurement of the friction between the magnetic surface or the back surface and calcium titanate ceramic 	10 10
8 Magnetic recording characteristics	10
8.1 Typical Field8.2 Signal amplitude8.3 Resolution8.4 Overwrite	11 11 11 11
8.4.1 Requirement	11
8.5 Peak shift	11
8.5.1 Requirement 8.5.2 Procedure	11 11
9 Tape quality	12
9.1 Missing pulses	12
9.1.1 Requirement	12
9.2 Missing pulse zone	12
9.2.1 Requirement	12
9.3 Tape durability	12
Section 3 - Mechanical specifications of the tape cartridge	12
10 General	12
10.1 Bottom side and right side 10.2 Back side and left side 10.3 Tape reel 10.4 Tape leader 10.5 Front side 10.6 Operation of the cartridge 10.7 Tape winding 10.8 Moment of inertia 10.9 Material	13 14 14 15 16 17 17 17
Section 4 - Requirements for an interchanged tape	27
11 Method of recording	27
11.1 Physical recording density 11.2 Channel bit cell length	27 27
11.2.1 Average Channel bit cell length 11.2.2 Long-term average Channel bit cell length 11.2.3 Short-term average Channel bit cell length	27 27 27
11.3 Flux transition spacing 11.4 Read signal amplitude 11.5 Azimuth 11.6 Channel skew	27 27 28 28
12 Tape format	28

12.1 Reference Edge 12.2 Direction of recording 12.3 Tape layout 12.4 Calibration and Directory Area	28 28 28 28
12.4.1 Scratch Area 12.4.2 Guard Area G1 12.4.3 Calibration Tracks Area 12.4.4 Guard Area G2 12.4.5 Directory Area 12.4.6 Guard Area G3	29 29 29 30 30 30
12.5 Data Area 12.5.1 Physical tracks 12.5.2 Width of the physical tracks 12.5.3 Logical tracks 12.5.4 Locations of the physical tracks 12.5.5 Layout of tracks in the Data Area 13 Data format 13.1 Data Bytes 13.2 Logical Blocks 13.3 Data Blocks 13.4 Types of Logical Blocks 13.5 Entities	30 31 31 31 32 32 33 33 33 33
13.6.1 Preamble 13.6.2 Sync 13.6.3 Data Field 13.6.4 EDC 13.6.5 Control Field 1 (CF1) 13.6.6 Control Field 2 (CF2) 13.6.7 CRC 13.6.8 Postamble 14 Use of Logical Blocks 14.1 Data Blocks 14.2 Filler Blocks 14.3 End of Track Blocks (EOTR) 14.4 End of Data Blocks (EOD) 14.5 ECC Blocks	33 34 34 36 36 37 38 38 38 38 38 39 39
15 Format of Entities	39
16 Error handling	39
Annexes	
A - Measurement of light transmittance	4(
B - Generation of the Data Block CRCs	43
C - ECC generation	44
D - Generation of page CRCs	47
E - Format of MAP entries	48
F - Format of Control Field 1	49
G - Format of Control Field 2	50
H - Recommendations for transportation	51

J - Inhibitor tape	52
K - Recommendations on tape durability	53
L - Handling guidelines	54

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75% of the national bodies casting a vote.

International Standard ISO/IEC 15307 was prepared by ECMA (as ECMA-231) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

Annexes A to G form an integral part of this International Standard. Annexes H to L are for information only.

Introduction

This International Standard constitutes a further development of the family of DLT-formatted magnetic tape cartridges. It allows for a capacity of 20 Gbytes of uncompressed data, or, typically, of 40 Gbytes of compressed user data.

Information technology — Data interchange on 12,7 mm 128-track magnetic tape cartridges — DLT 4 format

Section 1 - General

1 Scope

This International Standard specifies the physical and magnetic characteristics of a 12,7 mm wide, 128-track magnetic tape cartridge, to enable interchangeability of such cartridges. It also specifies the quality of the recorded signals, a format - called Digital Linear Tape 4 (DLT 4) - and a recording method. Together with a labelling standard, for instance ISO 1001 for Magnetic Tape Labelling, it allows full data interchange by means of such magnetic tape cartridges.

2 Conformance

2.1 Magnetic tape cartridges

A magnetic tape cartridge shall be in conformance with this International Standard if it satisfies all mandatory requirements of this International Standard. The tape requirements shall be satisfied throughout the extent of the tape.

2.2 Generating systems

A system generating a magnetic tape cartridge for interchange shall be entitled to claim conformance with this International Standard if all the recordings that it makes on a tape according to 2.1 meet the mandatory requirements of this International Standard.

2.3 Receiving systems

A system receiving a magnetic tape cartridge for interchange shall be entitled to claim conformance with this International Standard if it is able to handle any recording made on a tape according to 2.1.

3 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 1001:1986, Information processing — File structure and labelling of magnetic tapes for information interchange.

ISO 1302:1992, Technical drawings — Method of indicating surface texture.