

INTERNATIONAL STANDARD

ISO/IEC 15718

First edition
1998-08-01

Information technology — Data interchange on 8 mm wide magnetic tape cartridge — Helical scan recording — HH-1 format

*Technologies de l'information — Échange de données sur cartouche de
bande magnétique de 8 mm de large — Enregistrement par balayage en
spirale — Format HH-1*



Contents

Section 1 - General	1
1 Scope	1
2 Conformance	1
2.1 Magnetic tape cartridge	1
2.2 Generating drive	1
2.3 Receiving drive	1
3 Normative References	2
4 Definitions	2
4.1 Absolute Frame Address	2
4.2 a.c. erase	2
4.3 algorithm	2
4.4 Area ID	2
4.5 Average Signal Amplitude	2
4.6 azimuth	2
4.7 back surface	2
4.8 bit cell	2
4.9 byte	2
4.10 cartridge	2
4.11 Channel bit	2
4.12 compressed data	2
4.13 Cyclic Redundancy Check (CRC) character	2
4.14 Data Format ID	2
4.15 End of Data (EOD)	2
4.16 Error Correcting Code	2
4.17 flux transition position	2
4.18 flux transition spacing	2
4.19 Frame	2
4.20 Logical Beginning of Tape (LBOT)	2
4.21 record	2
4.22 magnetic tape	2
4.23 Master Standard Reference Tape	3
4.24 Partition Boundary	3

© ISO/IEC 1998

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

4.25 Physical Beginning of Tape (PBOT)	3
4.26 Physical End of Tape (PEOT)	3
4.27 physical recording density	3
4.28 Reference Field	3
4.29 Secondary Standard Reference Tape	3
4.30 Standard Reference Amplitude (SRA)	3
4.31 Standard Reference Recording Current	3
4.32 Tape Reference Edge	3
4.33 Test Recording Current	3
4.34 track	3
4.35 Typical Field	3
4.36 uncompressed data	3
5 Conventions and notations	3
5.1 Representation of numbers	3
5.2 Names	4
6 Acronyms	4
7 Environment and safety	4
7.1 Testing environment	4
7.2 Operating environment	4
7.3 Storage environment	4
7.4 Transportation	4
7.5 Safety	5
7.6 Flammability	5
Section 2 - Requirements for the case	6
8 Dimensional and mechanical characteristics of the case	6
8.1 General	6
8.2 Overall dimension	6
8.3 Holding areas	7
8.4 Cartridge insertion	7
8.5 Window	8
8.6 Loading grips	8
8.7 Label areas	8
8.8 Datum areas and datum holes	8
8.9 Support Areas	9
8.10 Recognition holes	10
8.11 Write-inhibit hole	10
8.12 Pre-positioning surfaces	11
8.13 Cartridge lid	11
8.14 Cartridge reel lock	12
8.15 Reel access holes	13
8.16 Interface between the reels and the drive spindles	13
8.17 Light path	15
8.18 Position of the tape in the case	15
8.19 Tape path zone	16
8.20 Tape access cavity	16
8.21 Tape access cavity clearance requirements	16
Section 3 - Requirements for the Unrecorded Tape	33
9 Mechanical, physical and dimensional characteristics of the tape	33
9.1 Materials	33

9.2 Tape length	33
9.2.1 Magnetic tape	33
9.2.2 Leader and trailer tapes	33
9.2.3 Splicing tape	33
9.3.1 Width of magnetic tape	33
9.3.2 Width of leader and trailer tapes	33
9.3.3 Width and position of splicing tape	33
9.4 Discontinuities	33
9.5 Thickness	33
9.5.1 Thickness of the magnetic tape	33
9.5.2 Thickness of leader and trailer tape	34
9.5.3 Thickness of the splicing tape	34
9.6 Longitudinal curvature	34
9.7 Cupping	34
9.8 Coating adhesion	34
9.9 Layer-to-layer adhesion	35
9.10 Tensile strength	35
9.10.1 Breaking strength	35
9.10.2 Yield strength	35
9.11 Residual elongation	35
9.12 Electrical resistance of coated surfaces	35
9.13 Tape winding	36
9.14 Light transmittance of tape	36
9.15 Media Recognition System (MRS)	36
10 Magnetic recording characteristics	37
10.1 Typical Field	37
10.2 Signal amplitude	38
10.3 Resolution	38
10.4 Overwrite	38
10.5 Ease of erasure	38
10.6 Tape quality	38
10.6.1 Missing pulses	38
10.6.2 Missing pulse zone	38
10.7 Signal-to-Noise Ratio (SNR)	39
Section 4 - Requirements for an interchanged tape	40
11 Format	40
11.1 General	40
11.2 Information Matrix	41
11.2.1 Loading the Information Matrix	41
11.3 Sync Block	53
11.3.1 Sync Block Data	53
11.3.2 Sync Block Header	53
11.3.3 Sync Block Header in Preamble Zone	54
11.4 Data Zone	54
11.4.1 Identification and arrangement of Information Blocks in the Data Zone of a Frame	54
11.4.2 Identification and arrangement of Sync Blocks in Data Zone of a Track	55

12 Method of recording	55
12.1 Physical recording density	55
12.2 Long-term average bit cell length	55
12.3 Short-term average bit cell length	55
12.4 Rate of change	56
12.5 Bit shift	56
12.6 Read signal amplitude	56
12.7 Recording current	56
13 Track geometry	56
13.1 Track configuration	56
13.2 Average track pitch	57
13.3 Variations of the track pitch	57
13.4 Track width	57
13.5 Track angle	57
13.6 Track edge linearity	57
13.7 Track length	57
13.8 Data Zone reference	57
13.9 Azimuth angles	57
14 Recording pattern	57
14.1 Recorded Sync Block	57
14.2 Preamble Zone	57
14.3 Postamble Zone	57
15 Format of a track	58
15.1 Track capacity	58
15.2 Positioning accuracy	58
15.3 Tracking scheme	58
16 Layout of a Single Data Space tape	58
16.1 Frame type	58
16.1.1 Data Frame	58
16.1.2 Gap Frame	58
16.1.3 Long File Mark Frame	58
16.1.4 Short File Mark Frame	58
16.1.5 Set Mark Frame	58
16.1.6 End of Data Frame	58
16.1.7 Format Frame	59
16.1.8 Data Frame in System Area	59
16.2 Device Area	59
16.3 Reference Area	59
16.4 System Area	59
16.4.1 Guard Band No.1	59
16.4.2 System Log Preamble	59
16.4.3 System Log	59
16.4.4 System Log Postamble	59
16.4.5 Guard Band No.2	59
16.4.6 Data Area Preamble	59
16.5 Data Area	59
16.5.1 Long File Mark	59
16.5.2 Short File Mark	59
16.5.3 Set Mark	60

16.5.4	Write operation	60
16.5.5	Append and overwrite operations	60
16.5.6	Rewritten Frames	60
16.6	EOD Area	60
16.7	Post-EOD Area	60
17	Layout of a partitioned tape	61
17.1	Overall magnetic tape layout	61
17.1.1	Device Area	61
17.1.2	Partition 1	61
17.1.3	Partition 0	62
17.2	Partition Identification	62
Annexes		
A	- Measurement of light transmittance of tape and leaders	63
B	- Measurement of Signal-to-Noise Ratio	66
C	- Representation of 8-bit bytes by 10-bit patterns	67
D	- Measurement of bit shift	75
E	- Measurement of track edge linearity tolerance	78
F	- Recommendations for transportation	79
G	- Example of the content of a Data Block in the System Area	80

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 15718 was prepared by JISC (as Standard JIS X.6143-1997) with document support and contribution from ECMA (ECMA-247) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

Annexes A to E form an integral part of this International Standard. Annexes F and G are for information only.

Information technology — Data interchange on 8 mm wide magnetic tape cartridge — Helical scan recording — HH-1 format

Section 1 - General

1 Scope

This International Standard specifies the physical and magnetic characteristics of an 8 mm wide magnetic tape cartridge so as to provide physical interchange of such cartridges between drives. It also specifies the quality of the recorded signals, the recording method and the recorded format - called HH-1 format - thereby allowing for full data interchange between drives by means of such magnetic tape cartridges.

Information interchange between systems also requires, as a minimum, agreement between the interchange parties upon the interchange code(s) and the specifications of the structure and labelling of the information on the interchanged cartridge.

2 Conformance

2.1 Magnetic tape cartridge

A tape cartridge shall be in conformance with this International Standard if it meets all the mandatory requirements specified herein. The tape requirements shall be satisfied throughout the extent of the tape.

2.2 Generating drive

A drive generating a magnetic tape cartridge for interchange shall be in conformance with this International Standard if all recordings on the tape meet the mandatory requirements of this International Standard.

A claim of conformance shall state which of the following optional features are implemented and which are not

- the performing of a Read-After-Write check and the recording of any necessary rewritten frames;
- the generation of ECC3 Blocks.

In addition a claim of conformance shall state

- whether or not, registered data compression algorithm(s) are implemented within the system and are able to compress data received from the host, and
- the registered identification number(s) of the implemented algorithm(s).

2.3 Receiving drive

A drive receiving a magnetic tape cartridge for interchange shall be in conformance with this International Standard if it is able to handle any recording made on the tape according to this International Standard. In particular it shall

- be able to recognize rewritten frames and to make available to the host, data and File Marks from only one of these frames;
- be able to recognize a ECC3 Block, and ignore it if the system is not capable of using ECC3 check bytes in a process of error correction;
- be able to recognize compressed data, identify the algorithm used, and make the algorithm registration number available to the host;
- be able to make compressed data available to the host.

In addition a claim of conformance shall state

- whether or not the system is capable of using ECC3 check bytes in a process of error correction;
- whether or not one or more decompression algorithm(s) are implemented within the system, and are able to be applied to compressed data prior to making such data available to the host;
- the registered identification number(s) of the data compression algorithm(s) for which a complementary data decompression algorithm is implemented.
- whether or not the system is capable of updating the System Log(s) if the Write-inhibit Hole state so permits.

3 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

- | | |
|---------------------|--|
| ISO 527-1:1993, | <i>Plastics — Determination of tensile properties — Part 1: General principles.</i> |
| ISO 1302:1992, | <i>Technical drawings — Method of indicating surface texture.</i> |
| ISO/IEC 11576:1995, | <i>Information technology — Procedure for the registration of algorithms for the lossless compression of data.</i> |
| IEC 950:1991, | <i>Safety of information technology equipment.</i> |