This is a preview - click here to buy the full publication

INTERNATIONAL STANDARD

15780

First edition 1998-08-01

Information technology — 8 mm wide magnetic tape cartridge — Helical scan recording — AIT-1 format

Technologies de l'information — Cartouche de bande magnétique de 8 mm de large — Enregistrement par balayage en spirale — Format AIT-1



ISO/IEC 15780:1998(E)

Contents

Section 1 - General	1
1 Scope	1
2 Conformance2.1 Magnetic tape cartridge2.2 Generating drive2.3 Receiving drive	1 1 1 1
3 Normative references	2
4 Definitions 4.1 Absolute Frame Number (AFN) 4.2 a.c. erase 4.3 Access	2 2 2 2
4.4 algorithm 4.5 Area ID	2
4.6 Automatic Track Finding (ATF)4.7 Average Signal Amplitude	2 2 2
4.8 azimuth4.9 back surface	2 2
4.10 byte	2
4.11 cartridge 4.12 Channel bit	2 2
4.13 Codeword	2
4.14 Early Warning Point (EWP)	2
4.15 End of Data (EOD)	2
4.16 Entity	2
4.17 Error Correcting Code (ECC) 4.18 flux transition position	2 2
4.19 flux transition position	2
4.20 Frame	2
4.21 Housekeeping Frame	3
4.22 Logical Beginning of Tape (LBOT)	3
4.23 magnetic tape	3
4.24 Master Standard Amplitude Calibration Tape	3
4.25 Master Standard Reference Tape	3
4.26 Memory In Cartridge (MIC)	3
4.27 Partition Boundary	3
4.28 Physical Beginning of Tape (PBOT)	3
4.29 Physical End of Tape (PEOT)	3
4.30 physical recording density	3

© ISO/IEC 1998

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Switzerland

4.31 pre-recording condition 4.32 processing 4.33 processed data 4.34 Processed Record 4.35 record 4.36 Reference Field 4.37 reprocessing 4.38 Secondary Standard Amplitude Calibration Tape 4.39 Secondary Standard Reference Tape 4.40 Separator Mark 4.41 Standard Reference Amplitude (SRA) 4.42 Tape Reference Edge 4.43 Typical Field 4.44 Standard Reference Current 4.45 Test Recording Current	3 3 3 3 3 3 3 3 4 4 4 4
4.46 track 4.47 unprocessed data 4.48 Unprocessed Record	4 4 4
5 Conventions and Notations 5.1 Representation of numbers 5.2 Names	4 4 4
6 Acronyms	4
7 Environment and safety 7.1 Test environment 7.2 Operating environment 7.3 Storage environment 7.4 Transportation 7.5 Safety 7.6 Flammability	5 5 5 5 5 5 5
8 Dimensional and mechanical characteristics of the case 8.1 General 8.2 Overall dimension 8.3 Holding areas 8.4 Cartridge insertion 8.5 Window 8.6 Loading grips	6 6 6 7 7 8 8
8.7 Label areas 8.8 Datum areas and Datum holes 8.9 Support areas 8.10 Recognition holes 8.11 Write-inhibit hole	8 8 9 10 10
 8.12 Pre-positioning surfaces 8.13 Cartridge lid 8.14 Cartridge reel lock 8.15 Reel access holes 8.16 Interface between the reels and the drive spindles 8.17 Light path 	11 11 12 13 13
 8.17 Light path 8.18 Position of the tape in the case 8.19 Tape path zone 8.20 Tape access cavity 8.21 Tape access cavity clearance requirements 	14 15 15 15 16
8.22 Requirements for the MIC 8.22.1 Access holes	16 16

8.22.2 Recognition recesses	17
Section 3 - Requirements for the unrecorded tape	37
9 Mechanical, physical and dimensional characteristics of the tape 9.1 Materials 9.2 Tape length 9.2.1 Length of magnetic tape 9.2.2 Length of leader and trailer tapes 9.2.3 Length of the splicing tapes 9.3 Tape width 9.3.1 Width of magnetic, leader and trailer tapes 9.3.2 Width and position of the splicing tape 9.4 Discontinuities 9.5 Tape thickness 9.5.1 Thickness of the magnetic tape 9.5.2 Thickness of leader and trailer tape 9.5.3 Thickness of splicing tape 9.6 Longitudinal curvature 9.7 Cupping 9.8 Coating adhesion 9.9 Layer-to-layer adhesion 9.10 Tensile strength 9.10.1 Breaking strength 9.10.2 Yield strength 9.11 Residual elongation	37 37 37 37 37 37 37 37 37 38 38 38 38 38 38 39 39
9.12 Electrical resistance of the recording surface9.13 Tape winding	40 40
9.14 Light transmittance of the tape	40
10.1 Typical Field 10.2 Signal Amplitude 10.3 Resolution 10.4 Overwrite 10.5 Ease of erasure 10.6 Tape quality 10.6.1 Missing pulses 10.6.2 Missing pulse zone 10.7 Signal-to-Noise Ratio (SNR) characteristic	40 41 41 41 41 42 42 42 42 42
Section 4 - Requirements for an interchanged tape	42
11.1 General 11.2 Basic Groups 11.2.1 Entity 11.2.2 Group Information Table 11.2.3 Block Access Table (BAT) 11.3 Sub-Groups 11.3.1 G1 Sub-Group 11.3.2 G2 Sub-Group - Randomizing 11.3.3 G3 Sub-Group 11.4 Data Block 11.4.1 ID information 11.4.2 Recording of the ID Information in the Data Block Headers	42 42 43 43 44 46 49 50 51 52 53
12 Method of recording 12.1 Physical recording density	58 58

12.2 Long-term average bit cell length 12.3 Short-term average bit cell length 12.4 Rate of change 12.5 Bit shift 12.6 Read signal amplitude 12.7 Maximum recorded levels	58 58 58 58 58
13 Track geometry 13.1 Track configuration 13.2 Average track pitch 13.3 Variations of the track pitch 13.4 Track width 13.5 Track angle 13.6 Track edge straightness 13.7 Track length 13.8 Azimuth angles 14 Recorded patterns	59 59 59 59 60 60 60
14.1 Recorded Data Block 14.2 Margin blocks	60 60
15 Format of a track 15.1 Track capacity 15.2 Positioning accuracy 15.3 Tracking scheme	60 60 61 62
16 Layout of a Single Data Space tape 16.1 Device Area 16.2 Reference Area 16.3 Position Tolerance Band No. 1 16.4 System Area 16.4.1 System Preamble 16.4.2 System Log 16.4.3 System Postamble 16.4.4 Position Tolerance Band No. 2 16.4.5 Vendor Group Preamble 16.5.1 Vendor Group 16.5.2 Recorded Data Group 16.5.3 ECC3 16.5.4 Multiple Recorded Instances 16.5.5 Repeated Frames 16.5.6 Appending and overwriting 16.6 EOD Area 16.7 Optional Device Area 16.8 Early Warning Point - EWP 16.9 Initialization	62 63 63 63 64 64 67 67 67 67 68 68 69 70 71
17 Layout of partitioned tape 17.1 Overall magnetic tape layout 17.1.1 Partition 17.2 LBOT 17.3 Empty Partition 17.4 Initialization of partitioned tapes	72 72 72 73 73 73
18 Housekeeping Frames 18.1 Amble Frames 18.2 System Amble Frames	73 73 74

Annexes

A - Measurement of light transmittance	75
B - Measurement of Signal-to-Noise Ratio	78
C - Method for determining the nominal and the maximum allowable recorded levels	79
D - Representation of 8-bit bytes by 10-bit patterns	80
E - Measurement of bit shift	92
F - Method of measuring the straightness of track edges	94
G - ECC calculation	95
H - Recommendations for transportation	98
J - Read-After-Write	99
K - Example of the content of a Basic Group No. 0	100

Foreword

©ISO/IEC

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

This International Standard was prepared by ECMA (as ECMA-246) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval of national bodies of ISO and IEC.

Annexes A to G form an integral part of this International Standard. Annexes H to K are for information only.

vii

Information technology — 8 mm wide magnetic tape cartridge — Helical scan recording — AIT-1 format

Section 1 - General

1 Scope

This International Standard specifies the physical and magnetic characteristics of an 8 mm wide magnetic tape cartridge to enable physical interchange of such cartridges between drives. It also specifies the quality of the recorded signals, the recording method and the recorded format - called Advanced Intelligent Tape No. 1 (AIT-1) - thereby allowing data interchange between drives by means of such magnetic tape cartridges.

Information interchange between systems also requires, at a minimum, agreement between the interchange parties upon the interchange code(s) and the specifications of the structure and labelling of the information on the interchanged cartridge.

2 Conformance

2.1 Magnetic tape cartridge

A tape cartridge shall be in conformance with this International Standard if it meets all the mandatory requirements specified herein. The tape requirements shall be satisfied throughout the extent of the tape.

2.2 Generating drive

A drive generating a magnetic tape cartridge for interchange shall be in conformance with this International Standard if all recordings on the tape meet the mandatory requirements of this International Standard, and if either or both methods of appending and overwriting are implemented.

A claim of conformance shall state which of the following optional features are implemented and which are not

- the performing of a Read-After-Write check and the recording of any necessary repeated frames;
- the generation of ECC3 Frames.

In addition a claim of conformance shall state

- whether or not one, or more, registered algorithm(s) are implemented within the system and are able to compress data received from the host prior to collecting the data into Basic Groups, and
- the registered identification number(s) of the implemented compression algorithm(s).

2.3 Receiving drive

A drive receiving a magnetic tape cartridge for interchange shall be in conformance with this International Standard if it is able to handle any recording made on the tape according to this International Standard. In particular it shall

- be able to recognise repeated frames, and to make available to the host, data and Separator Marks from only one of these frames;
- be able to recognise multiple representations of the same Basic Group, and to make available to the host, data and Separator Marks from only one of these representations;
- be able to recognise an ECC3 frame, and ignore it if the system is not capable of using ECC3 check bytes in a process of error correction;
- be able to recognise processed data within an Entity, identify the algorithm used, and make its registered identification number available to the host;
- be able to make processed data available to the host.

In addition a claim of conformance shall state

- whether or not the system is capable of using ECC3 check bytes in a process of error correction;

- whether or not one or more de-compression algorithm(s) are implemented within the system, and are able to be applied to compressed data prior to making such data available to the host;
- the registered identification number(s) of the compression algorithm(s) for which a complementary de-compression algorithm is implemented.

3 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO/R 527 (all parts), Plastics - Determination of tensile properties.

ISO 1302:1992, Technical drawings - Method of indicating surface texture.

ISO/IEC 11576:1994, Information technology - Procedure for the registration of algorithms for the lossless compression

of data.