

This is a preview - [click here to buy the full publication](#)

# INTERNATIONAL STANDARD

# ISO/IEC 16824

First edition  
1999-05-15

---

---

## Information technology — 120 mm DVD rewritable disk (DVD-RAM)

*Technologies de l'information — Disque à réécriture DVD de diamètre  
120 mm (DVD-RAM)*



Reference number  
ISO/IEC 16824:1999(E)

| <b>Contents</b>                                  | <b>Page</b> |
|--|-------------|
| <b>Section 1 - General</b>                       | <b>1</b>    |
| <b>1 Scope</b>                                   | <b>1</b>    |
| <b>2 Conformance</b>                             | <b>1</b>    |
| 2.1 Optical Disk                                 | 1           |
| 2.2 Generating system                            | 1           |
| 2.3 Receiving system                             | 1           |
| <b>3 Normative references</b>                    | <b>1</b>    |
| <b>4 Definitions</b>                             | <b>1</b>    |
| 4.1 Case   | 1           |
| 4.2 Channel bit                                  | 2           |
| 4.3 Digital Sum Value (DSV)                      | 2           |
| 4.4 Disk Reference Plane                         | 2           |
| 4.5 Dummy substrate                              | 2           |
| 4.6 Embossed mark                                | 2           |
| 4.7 Entrance surface                             | 2           |
| 4.8 Land and Groove                              | 2           |
| 4.9 Mark   | 2           |
| 4.10 Phase change                                | 2           |
| 4.11 Polarization                                | 2           |
| 4.12 Recording layer                             | 2           |
| 4.13 Sector                                      | 2           |
| 4.14 Space                                       | 2           |
| 4.15 Substrate                                   | 2           |
| 4.16 Track                                       | 2           |
| 4.17 Track pitch                                 | 2           |
| 4.18 ZCLV  | 2           |
| 4.19 Zone  | 2           |
| <b>5 Conventions and notations</b>               | <b>2</b>    |
| 5.1 Representation of numbers                    | 2           |
| 5.2 Names  | 3           |
| <b>6 List of acronyms</b>                        | <b>3</b>    |
| <b>7 General description of the optical disk</b> | <b>3</b>    |
| <b>8 General requirements</b>                    | <b>4</b>    |
| 8.1 Environments                                 | 4           |
| 8.1.1 Test environment                           | 4           |

© ISO/IEC 1999

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

|   |           |
|---|-----------|
| 8.1.2 Operating environment   | 4         |
| 8.1.3 Storage environment   | 5         |
| 8.1.4 Transportation  | 5         |
| 8.2 Safety requirement  | 5         |
| 8.3 Flammability  | 5         |
| <b>9 Reference Drive</b>  | <b>5</b>  |
| 9.1 Optical Head  | 5         |
| 9.2 Read channels   | 6         |
| 9.3 Rotation speed  | 6         |
| 9.4 Disk clamping   | 7         |
| 9.5 Normalized servo transfer function  | 7         |
| 9.6 Reference Servo for axial tracking  | 7         |
| 9.7 Reference Servo for radial tracking   | 8         |
| <b>Section 2 - Dimensional, mechanical and physical characteristics of the disk</b> | <b>9</b>  |
| <b>10 Dimensional characteristics</b>   | <b>9</b>  |
| 10.1 Overall dimensions   | 10        |
| 10.2 First transition area  | 11        |
| 10.3 Second transition area   | 11        |
| 10.4 Clamping Zone  | 11        |
| 10.5 Third transition area  | 11        |
| 10.6 Rim area   | 12        |
| 10.7 Remark on tolerances   | 12        |
| 10.8 Label  | 12        |
| <b>11 Mechanical characteristics</b>  | <b>12</b> |
| 11.1 Mass   | 12        |
| 11.2 Moment of inertia  | 12        |
| 11.3 Dynamic imbalance  | 12        |
| 11.4 Sense of rotation  | 12        |
| 11.5 Runout   | 12        |
| 11.5.1 Axial runout   | 12        |
| 11.5.2 Radial runout  | 12        |
| <b>12 Optical characteristics</b>   | <b>13</b> |
| 12.1 Index of refraction  | 13        |
| 12.2 Thickness of the transparent substrate   | 13        |
| 12.3 Angular deviation  | 13        |
| 12.4 Birefringence of the transparent substrate                                     | 13        |
| 12.5 Reflectivity   | 13        |
| <b>Section 3 - Format of information</b>  | <b>14</b> |
| <b>13 Data format</b>   | <b>14</b> |
| 13.1 Data Frames  | 14        |
| 13.1.1 Data ID  | 15        |
| 13.1.2 Data ID Error Detection code (IED)   | 16        |
| 13.1.3 Reserved bytes   | 16        |
| 13.1.4 Error Detection Code (EDC)   | 16        |
| 13.2 Scrambled Frames   | 17        |
| 13.3 ECC Blocks   | 17        |
| 13.4 Recording Frames   | 19        |
| 13.5 Recording code and NRZI conversion   | 20        |

|   |           |
|---|-----------|
| 13.6 Recorded Data Field  | 21        |
| 13.7 DC component suppress Control (DCC)                                | 22        |
| 13.7.1 DCC for the data in the Rewritable Area                          | 22        |
| 13.7.2 DCC for the data in the Embossed Area                            | 22        |
| 13.7.3 PID and PED recording  | 23        |
| <b>14 Track format</b>  | <b>23</b> |
| 14.1 Track shape  | 23        |
| 14.2 Track path   | 24        |
| 14.3 Track pitch  | 24        |
| 14.4 Track layout   | 24        |
| 14.5 Rotation speed   | 24        |
| 14.6 Radial alignment   | 25        |
| 14.7 Sector number  | 25        |
| <b>15 Sector format</b>   | <b>26</b> |
| 15.1 Sector layout  | 26        |
| 15.1.1 Sector layout in the Rewritable Area                             | 26        |
| 15.1.2 Sector layout in the Embossed Area                               | 26        |
| 15.2 VFO fields   | 27        |
| 15.3 Address Mark (AM)  | 28        |
| 15.4 Physical ID (PID) fields   | 28        |
| 15.5 PID Error Detection code (PED) fields                              | 29        |
| 15.6 Postamble 1 and Postamble 2 (PA 1, PA 2) fields                    | 29        |
| 15.7 Mirror field   | 31        |
| 15.8 Gap field  | 31        |
| 15.9 Guard 1 field  | 31        |
| 15.10 Pre-Synchronous code (PS) field                                   | 31        |
| 15.11 Data field  | 31        |
| 15.12 Postamble 3 (PA 3) field  | 31        |
| 15.13 Guard 2 field   | 31        |
| 15.14 Recording polarity randomization                                  | 31        |
| 15.15 Buffer field  | 32        |
| <b>16 Format of the Information Zone</b>                                | <b>32</b> |
| 16.1 Division of the Information Zone                                   | 32        |
| 16.2 Lead-in Zone   | 34        |
| 16.2.1 Structure of Lead-in Zone  | 34        |
| 16.2.2 Initial Zone   | 34        |
| 16.2.3 Reference Code Zone  | 34        |
| 16.2.4 Buffer Zone 1  | 34        |
| 16.2.5 Buffer Zone 2  | 35        |
| 16.2.6 Control Data Zone  | 35        |
| 16.2.7 Connection Zone  | 39        |
| 16.2.8 Guard Track Zones 1 and 2  | 40        |
| 16.2.9 Disk Test Zone   | 40        |
| 16.2.10 Drive Test Zone   | 40        |
| 16.2.11 Reserved Zone   | 40        |
| 16.2.12 DMA 1 and DMA 2   | 40        |
| 16.3 Data Zone  | 41        |
| 16.3.1 Structure of Data Zone and of the Defect Management Areas (DMAs) | 41        |
| 16.3.2 Guard Track Zones  | 41        |
| 16.3.3 Partitioning   | 41        |
| 16.4 Lead-out Zone  | 43        |
| 16.4.1 Structure of Lead-out Zone                                       | 43        |
| 16.4.2 DMA 3 and DMA 4  | 43        |
| 16.4.3 Reserved Zone  | 43        |

|   |           |
|---|-----------|
| <b>16.4.4</b> Guard Track Zone 1  | <b>43</b> |
| <b>16.4.5</b> Drive Test Zone   | <b>43</b> |
| <b>16.4.6</b> Disk Test Zone  | <b>43</b> |
| <b>16.4.7</b> Guard Track Zone 2  | <b>43</b> |
| <br>  |           |
| <b>17 Defect management</b>   | <b>43</b> |
| <b>17.1</b> Defect Management Areas (DMAs)  | <b>43</b> |
| <b>17.2</b> Disk Definition Structure (DDS)   | <b>44</b> |
| <b>17.3</b> Spare sectors   | <b>46</b> |
| <b>17.4</b> Slipping Algorithm  | <b>47</b> |
| <b>17.5</b> Linear Replacement Algorithm  | <b>47</b> |
| <b>17.6</b> Primary Defect List (PDL)   | <b>48</b> |
| <b>17.7</b> Secondary Defect List (SDL)   | <b>50</b> |
| <b>17.8</b> Formatting of the disk  | <b>51</b> |
| <b>17.8.1</b> Full and Partial Certification  | <b>52</b> |
| <b>17.8.2</b> Initialization  | <b>52</b> |
| <b>17.8.3</b> Re-initialization   | <b>52</b> |
| <b>17.8.4</b> Data field number resulting from Initialization and Re-initialization | <b>53</b> |
| <b>17.9</b> Write procedure   | <b>54</b> |
| <b>17.10</b> Read procedure   | <b>54</b> |
| <b>17.10.1</b> Blank ECC block  | <b>54</b> |
| <b>17.10.2</b> Read procedure   | <b>54</b> |
| <br>  |           |
| <b>Section 4 - Characteristics of embossed information</b>                          | <b>55</b> |
| <br>  |           |
| <b>18 Method of testing</b>   | <b>55</b> |
| <b>18.1</b> Environment   | <b>55</b> |
| <b>18.2</b> Reference Drive   | <b>55</b> |
| <b>18.2.1</b> Optics and mechanics  | <b>55</b> |
| <b>18.2.2</b> Read power  | <b>55</b> |
| <b>18.2.3</b> Read channels   | <b>55</b> |
| <b>18.2.4</b> Tracking channel  | <b>55</b> |
| <b>18.2.5</b> Tracking  | <b>55</b> |
| <b>18.3</b> Definition of signals   | <b>55</b> |
| <br>  |           |
| <b>19 Signals from lands and grooves</b>  | <b>60</b> |
| <b>19.1</b> Push-pull signal  | <b>60</b> |
| <b>19.2</b> Divided push-pull signal  | <b>60</b> |
| <b>19.3</b> On-track signal   | <b>61</b> |
| <b>19.4</b> Phase depth   | <b>61</b> |
| <b>19.5</b> Wobble signal   | <b>61</b> |
| <br>  |           |
| <b>20 Signals from Header fields</b>  | <b>62</b> |
| <b>20.1</b> VFO 1 and VFO 2   | <b>62</b> |
| <b>20.2</b> Address Mark, PID, PED and Postamble                                    | <b>62</b> |
| <b>20.3</b> Signals from Header 1, Header 2, Header 3 and Header 4                  | <b>63</b> |
| <b>20.4</b> Phase depth   | <b>63</b> |
| <br>  |           |
| <b>21 Signals from Embossed Area</b>  | <b>63</b> |
| <b>21.1</b> High Frequency (HF) signal  | <b>63</b> |
| <b>21.1.1</b> Modulated amplitude   | <b>63</b> |
| <b>21.1.2</b> Signal asymmetry  | <b>64</b> |
| <b>21.1.3</b> Cross-track signal  | <b>64</b> |
| <b>21.2</b> Jitter  | <b>64</b> |

|   |           |
|---|-----------|
| 21.3 Servo signal   | 64        |
| 21.3.1 Differential phase tracking error signal   | 64        |
| 21.3.2 Tangential push-pull signal  | 64        |
| <b>Section 5 - Characteristics of the recording layer</b>   | <b>65</b> |
| <b>22 Method of testing</b>   | <b>65</b> |
| 22.1 Environment  | 65        |
| 22.2 Reference Drive  | 65        |
| 22.2.1 Optics and mechanics   | 66        |
| 22.2.2 Read power   | 66        |
| 22.2.3 Read channel   | 66        |
| 22.2.4 Tracking   | 66        |
| 22.3 Write conditions   | 66        |
| 22.3.1 Write pulse  | 66        |
| 22.3.2 Write power  | 66        |
| 22.4 Definition of signals  | 66        |
| <b>23 Write characteristics</b>   | <b>67</b> |
| 23.1 Modulated amplitude and Signal asymmetry   | 67        |
| 23.2 Jitter   | 67        |
| <b>Section 6 - Characteristics of user data</b>   | <b>67</b> |
| <b>24 Method of testing</b>   | <b>67</b> |
| <b>Annexes</b>  |           |
| <b>A - Measurement of the angular deviation <math>\alpha</math></b>                                     | <b>68</b> |
| <b>B - Measurement of birefringence</b>   | <b>70</b> |
| <b>C - Measurement of the differential phase tracking error</b>   | <b>72</b> |
| <b>D - Reflectivity calibration and measuring method</b>  | <b>76</b> |
| <b>E - Tapered cone for disk clamping</b>   | <b>78</b> |
| <b>F - Measuring conditions for the operation signals</b>   | <b>79</b> |
| <b>G - 8-to-16 Recording code with RLL (2,10) requirements</b>  | <b>81</b> |
| <b>H - Definition of the write pulse</b>  | <b>91</b> |
| <b>J - Guideline for randomization of the Gap length, the Guard 1 length and the recording polarity</b> | <b>93</b> |
| <b>K - Transportation</b>   | <b>94</b> |
| <b>L - Guideline for sector replacement</b>   | <b>95</b> |

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

This International Standard was prepared by JISC (as Standard JIS X 6243-1998) with document support and contribution from ECMA and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

Annexes A to H form a normative part of this International Standard. Annexes J to L are for information only.

# Information technology — 120 mm DVD rewritable disk (DVD-RAM)

## Section 1 - General

### 1 Scope

This International Standard specifies the mechanical, physical and optical characteristics of a 120 mm optical disk to enable interchange of such disks. It specifies the quality of the recorded signals, the format of the data and the recording method, thereby allowing for information interchange by means of such disks. The data can be written, read and overwritten many times using the phase change method. This disk is identified as DVD-RAM.

This International Standard specifies

- two related but different Types of this disk (see clause 7),
- the conditions for conformance,
- the environments in which the disk is to be tested, operated and stored,
- the mechanical, physical and dimensional characteristics of the disk, so as to provide mechanical interchange between data processing systems,
- the format of the information on the disk, including the physical disposition of the tracks and sectors, the error correcting codes and the coding method,
- the characteristics of the signals recorded on the disk, thus enabling data processing systems to read the data from the disk.

This International Standard provides for the interchange of disks between optical disk drives. Together with a standard for volume and file structure, it provides for full data interchange between data processing systems. The optical disks specified by this International Standard may be enclosed in cases according to ISO/IEC 16825 as specified therein.

### 2 Conformance

#### 2.1 Optical Disk

A claim of conformance with this International Standard shall specify the Type implemented. An optical disk shall be in conformance with this International Standard if it meets all mandatory requirements specified for this Type.

#### 2.2 Generating system

A generating system shall be in conformance with this International Standard if the optical disk it generates is in accordance with 2.1.

#### 2.3 Receiving system

A receiving system shall be in conformance with this International Standard if it is able to handle both Types of optical disk according to 2.1.

### 3 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 950:1991, *Safety of information technology equipment*.

ISO/IEC 16825:1999, *Information technology — Case for 120 mm DVD-RAM disks*.