

INTERNATIONAL STANDARD

ISO/IEC 17876

Second edition
2003-04-01

Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Inter-exchange signalling protocol — Private User Mobility (PUM) — Registration supplementary service

*Technologies de l'information — Télécommunications et échange
d'information entre systèmes — Réseau privé à intégration de
services — Protocole de signalisation d'interéchange — Mobilité de
l'utilisateur privé (PUM) — Service supplémentaire d'enregistrement*

Reference number
ISO/IEC 17876:2003(E)



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO/IEC 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Foreword	v
Introduction	vi
1 Scope	1
2 Conformance	1
3 Normative references	1
4 Terms and definitions	2
4.1 External definitions	2
4.2 Remote PINX	3
4.3 Previous Visitor PINX	3
4.4 Alternative identifier	3
4.5 Activating user	3
5 List of acronyms	3
6 Signalling protocol for the support of SS-PUMR	4
6.1 SS-PUMR description	4
6.2 SS-PUMR operational requirements	4
6.2.1 Requirements on the Visitor PINX	4
6.2.2 Requirements on the Home PINX	4
6.2.3 Requirements on the Previous Visitor PINX	4
6.2.4 Requirements on a Transit PINX	4
6.2.5 Requirements on the Directory PINX	4
6.2.6 Requirements on the Remote PINX	4
6.3 SS-PUMR coding requirements	5
6.3.1 Operations	5
6.3.2 Information elements	9
6.3.3 Messages	9
6.4 SS-PUMR state definitions	9
6.4.1 States at the Visitor PINX	9
6.4.2 States at the Home PINX	9
6.4.3 States at the Directory PINX	10
6.4.4 States at the Previous Visitor PINX	10
6.4.5 States at the Remote PINX	10
6.5 SS-PUMR signalling procedures for registration	10
6.5.1 Actions at the Visitor PINX for registration	10
6.5.2 Additional actions at the Visitor PINX in case of remote registration	11
6.5.3 Actions at the Home PINX for registration	12
6.5.4 Actions at a Transit PINX for registration	12
6.5.5 Actions at the previous Visitor PINX for registration	13
6.5.6 Actions at the Remote PINX for registration	13
6.6 SS-PUMR signalling procedures for de-registration	13
6.6.1 Actions at the Visitor PINX for de-registration	14
6.6.2 Actions at the Home PINX for de-registration	15
6.6.3 Actions at a Transit PINX for de-registration	16
6.6.4 Actions at the Remote PINX for de-registration	16

6.7	SS-PUMR signalling procedures for interrogation	16
6.7.1	Actions at the Visitor PINX for interrogation	16
6.7.2	Actions at the Home PINX for interrogation	17
6.7.3	Actions at the Remote PINX for interrogation	18
6.8	Signalling procedures for enquiry to a Directory PINX	19
6.8.1	Actions at a PINX for enquiry to a Directory PINX	19
6.8.2	Actions at the Directory PINX for enquiry	19
6.9	SS-PUMR impact of interworking with public ISDNs	19
6.10	SS-PUMR impact of interworking with non-ISDNs	19
6.11	Protocol interactions between SS-PUMR and other supplementary services and ANFs	20
6.11.1	Interaction with Calling Name Identification Presentation (SS-CNIP)	20
6.11.2	Interaction with Connected Name Identification Presentation (SS-CONP)	20
6.11.3	Interaction with Call Forwarding Unconditional (SS-CFU)	20
6.11.4	Interaction with Call Forwarding Busy (SS-CFB)	20
6.11.5	Interaction with Call Forwarding No Reply (SS-CFNR)	20
6.11.6	Interaction with Call Deflection (SS-CD)	20
6.11.7	Interaction with Path Replacement (ANF-PR)	20
6.11.8	Interaction with Call Transfer (SS-CT)	20
6.11.9	Interaction with Call Completion to Busy Subscriber (SS-CCBS)	20
6.11.10	Interaction with Call Completion on No Reply (SS-CCNR)	20
6.11.11	Interaction with Call Offer (SS-CO)	20
6.11.12	Interaction with Do Not Disturb (SS-DND)	20
6.11.13	Interaction with Do Not Disturb Override (SS-DNDO)	20
6.11.14	Interaction with Call Intrusion (SS-CI)	20
6.11.15	Interaction with Call Interception (ANF-CINT)	20
6.11.16	Interaction with Transit Counter (ANF-TC)	20
6.11.17	Interaction with Recall (SS-RE)	21
6.11.18	Interaction with Advice Of Charge (SS-AOC)	21
6.11.19	Interaction with Wireless Terminal Incoming Call (SS-WTMI)	21
6.11.20	Interactions with Wireless Terminal Outgoing call (SS-WTMO)	21
6.11.21	Interactions with Wireless Terminal Location Registration (SS-WTLR)	21
6.11.22	Interactions with Wireless Terminal Authentication of the WTM User (SS-WTAT)	21
6.11.23	Interactions with Wireless Terminal Authentication of the PISN (SS-WTAN)	21
6.11.24	Interactions with Message Waiting Indication (SS-MWI)	21
6.11.25	Interactions with Common Information (ANF-CMN)	22
6.11.26	Interactions with Call Priority Interruption (SS-CPI)	22
6.11.27	Interactions with Call Priority Interruption Protection (SS-CPIP)	22
6.12	SS-PUMR parameter values (timers)	22
6.12.1	Timer T1	22
6.12.2	Timer T2	22
6.12.3	Timer T3	22
6.12.4	Timer T4	22
6.12.5	Timer T5	22
Annexes		
A	Protocol Implementation Conformance Statement (PICS) proforma	23
B	Examples of Message Sequences	30
C	Specification and Description Language (SDL) representation of procedures	43
D	Imported ASN.1 Definitions	59
E	ASN.1 definitions according to ITU-T Recs. X.208 / X.209	60

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 17876 was prepared by ECMA (as ECMA-282) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

This second edition cancels and replaces the first edition (ISO/IEC 17876:2000), which has been technically revised.

Introduction

This International Standard is one of a series of standards defining services and signalling protocols applicable to Private Integrated Services Networks (PISNs). The series uses ISDN concepts as developed by ITU-T and conforms to the framework of standards for Open Systems Interconnection as defined by ISO/IEC.

This International Standard specifies the signalling protocol for use at the Q reference point in support of the Private User Mobility Registration supplementary service.

This International Standard is based upon the practical experience of ECMA member companies and the results of their active and continuous participation in the work of ISO/IEC JTC 1, ITU-T, ETSI and other international and national standardization bodies. It represents a pragmatic and widely based consensus.

Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Inter-exchange signalling protocol — Private User Mobility (PUM) — Registration supplementary service

1 Scope

This International Standard specifies the signalling protocol for the support of the Private User Mobility Registration supplementary service (SS-PUMR) at the Q reference point between Private Integrated services Network eXchanges (PINXs) connected together within a Private Integrated Services Network (PISN).

SS-PUMR is a supplementary service which enables a PUM user to register at, or de-register from, any wired or wireless terminal within the PISN. The ability to register at different locations in the PISN at different times enables the PUM user to maintain the provided services (including the ability to make and receive calls) at different access points. De-registration is used to inform the PISN that the PUM user is temporarily unable to make use of the provided services (including the receipt of calls). SS-PUMR may provide the PUM user with the ability to obtain information on the current registration sessions (interrogation).

The Q reference point is defined in ISO/IEC 11579-1.

Service specifications are produced in three stages and according to the method specified in ITU-T Rec. I.130. This International Standard contains the stage 3 specification for the Q reference point and satisfies the requirements identified by the stage 1 and stage 2 specifications in ISO/IEC 17875.

The signalling protocol for SS-PUMR uses certain aspects of the generic procedures for the control of supplementary services specified in ISO/IEC 11582.

This International Standard also specifies additional signalling protocol requirements for the support of interactions at the Q reference point between SS-PUMR and other supplementary services and ANFs.

NOTE 1 - Additional interactions that have no impact on the signalling protocol at the Q reference point can be found in the relevant stage 1 specifications.

This International Standard is applicable to PINXs which can interconnect to form a PISN.

This International Standard applies to PUM only within a single PISN.

2 Conformance

In order to conform to this International Standard, a PINX shall satisfy the requirements identified in the Protocol Implementation Conformance Statement (PICS) proforma in annex A.

Conformance to this International Standard includes conforming to those clauses that specify protocol interactions between SS-PUMR and other supplementary services and ANFs for which signalling protocols at the Q reference point are supported in accordance with the stage 3 standards concerned.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 11571:1998, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Networks - Addressing*

ISO/IEC 11579-1:1994, *Information technology - Telecommunications and information exchange between systems - Private integrated services network - Part 1: Reference configuration for PISN Exchanges (PINX)*

ISO/IEC 11582:2002, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Generic functional protocol for the support of supplementary services - Inter-exchange signalling procedures and protocol*

ISO/IEC 15506:2003, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Inter-exchange signalling protocol - Message Waiting Indication supplementary service*

ISO/IEC 15428:1999, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Specification, functional model and information flows - Wireless Terminal Location Registration supplementary service and Wireless Terminal Information Exchange additional network feature*

ISO/IEC 15429:2003, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Inter-exchange signalling protocol - Wireless Terminal Location Registration supplementary service and Wireless Terminal Information exchange additional network feature*

ISO/IEC 17875:2000, *Information technology - Telecommunications and information exchange between systems - Private Integrated Services Network - Specification, functional model and information flows - Private User Mobility (PUM) - Registration supplementary service*

ITU-T Rec. I.112:1993, *Vocabulary of terms for ISDNs*

ITU-T Rec. I.130:1988, *Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN (Blue Book)*

ITU-T Rec. I.210:1933, *Principles of telecommunication services supported by an ISDN and the means to describe them*

ITU-T Rec. Q.950:2000, *Supplementary services protocols, structure and general principles*

ITU-T Rec. Z.100:1999, *Specification and description language (SDL)*