

INTERNATIONAL STANDARD

ISO/IEC 18050

First edition
2006-02-15

Information technology — Office equipment — Print quality attributes for machine readable Digital Postage Marks

*Technologies de l'information — Équipement de bureau — Attributs
d'impression qualité pour les timbres postaux numériques lisibles par
machine*

Reference number
ISO/IEC 18050:2006(E)



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO/IEC 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	v
Introduction.....	vi
1 Scope	1
2 Normative references.....	1
3 Terms and definitions	2
4 Symbols and abbreviations.....	3
5 Requirements.....	3
6 Basic measurement methodology.....	4
7 Verification requirements for Digital Postage Marks.....	5
7.1 Verification equipment.....	5
7.2 Optical geometry.....	5
7.3 Light source	6
7.4 Measuring aperture	6
7.4.1 Measuring aperture for two-dimensional multi-row symbologies	7
7.4.2 Measuring aperture for two-dimensional matrix symbologies	7
7.5 Mail format.....	7
8 Grading implications for individual symbol attributes.....	8
9 Additional grading parameters - quiet zone	9
10 Qualification of printing systems for Digital Postage Marks	9
Annex A (normative) Test procedure for printing systems for Digital Postage Marks.....	11
A.1 Environmental conditions for test.....	11
A.2 Test materials.....	11
A.3 Test procedure	12
Annex B (informative) Light sources and spectral response characteristics for verification of Digital Postage Marks	13
B.1 Narrow-band illumination.....	13
B.2 Broad-band illumination (white light)	13
B.2.1 Halogen lamps	14
B.2.2 Light emitting diode	14
B.2.3 Gas discharge lamp	14
B.2.4 Fluorescent lamps.....	15
Annex C (informative) Symbol parameters measured in accordance with ISO/IEC 15415	16
C.1 Parameters for two-dimensional multi-row symbols.....	16
C.2 Parameters for two-dimensional matrix symbologies.....	17
Annex D (informative) Characteristics of Digital Postage Mark printing and reading environments that affect print quality	18
D.1 Printing of Digital Postage Marks.....	18
D.1.1 Ink-jet printing	18
D.1.2 Laser printing	18
D.1.3 Thermal transfer printing	19
D.1.4 Direct thermal printing	19
D.1.5 Matching X dimension to printer resolution	19
D.2 Reading environment.....	20

Annex E (informative) Possible causes of low parameter grades in the Digital Postage Mark

environment	21
E.1 Multi-row symbologies.....	21
E.1.1 Symbol Contrast.....	21
E.1.2 Minimum reflectance	21
E.1.3 Minimum edge contrast	21
E.1.4 Modulation.....	21
E.1.5 Decode	22
E.1.6 Defects	22
E.1.7 Decodability.....	22
E.1.8 Codeword yield.....	22
E.1.9 Unused error correction (UEC)	22
E.1.10 Quiet zone	22
E.1.11 Print growth.....	22
E.1.12 Codeword quality	23
E.2 Matrix symbologies.....	23
E.2.1 Symbol Contrast.....	23
E.2.2 Fixed pattern damage.....	23
E.2.3 Modulation.....	23
E.2.4 Axial non-uniformity	23
E.2.5 Grid non-uniformity	24
E.2.6 Unused error correction	24
E.2.7 Quiet zone	24
E.2.8 Print growth.....	24
Bibliography	25

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 18050 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 28, *Office equipment*.

Introduction

Digital Postage Marks (or franking marks), sometimes abbreviated to DPM, are used to evidence the payment of postage and/or other fees related to services requested by mailers. Digital Postage Marks are represented by symbols imprinted on the envelope, the label or the insert. Digital Postage Marks produced by different vendors' systems are generated with a variety of symbols and graphical images. The symbologies used for these images are primarily two-dimensional bar codes of both multi-row (PDF417) and matrix types (e.g. Data Matrix), as specified in UPU standard S 28. However, postal operators may also use other symbologies, e.g. OCR or 4-state codes for these purposes. The two-dimensional bar code symbologies offer advantages for the machine-readable representation of data strings of the order of 80 or more bytes in length, due to their high information density characteristics.

Public postal operators and private carriers have a high interest in automatically reading and validating these marks, preferably at high speed. These symbols must be read reliably by postal processing equipment. The highest practicable read rate is desired by users of such equipment in order to ensure efficient automation of this process, and any shortfall in the read rate may have as its consequence a loss of revenue to the operator.

This International Standard has been designed to customize the generic method of measuring the print quality of two-dimensional bar code symbols to the needs of the postal application and to recommend appropriate print quality levels that should contribute to the achievement of the read rates desired by the authorities responsible for validation of the Digital Postage Marks and by postal operators; it is also intended to provide guidelines for printing machine readable Digital Postage Marks on mail items. This International Standard will provide mailers, postal operators and their suppliers with a practical, quantitative and objective way to measure and communicate to each other basic print quality parameters of machine readable Digital Postage Marks. Since all attributes do not contribute uniformly to the readability of a Digital Postage Mark, this International Standard identifies five levels of criticality for an attribute (graded 0 to 4, in ascending order of quality), and a grading scheme that assesses the overall symbol quality based on averaging the results of multiple scans.

The International Standard may be used in the following ways:

- It allows an estimate to be made of the readability of a Digital Postage Mark without actually submitting it to any postal validation and the qualification of said symbol as acceptable or not acceptable for readability purposes.
- It allows an estimate to be made of the quality levels potentially achievable by a printing system with particular substrates.
- It provides a tool for process control in the operation of Digital Postage Mark printing systems.

This International Standard applies the measurement methodology defined in ISO/IEC 15415 for print quality attributes that tend to influence the readability of two-dimensional bar codes. This methodology is derived from a view of the current state-of-the-art in two-dimensional bar code scanning technologies.

Yet, such a state-of-the-art is not a perfectly defined concept. First, it is likely to evolve with time towards improved recognition capabilities. Second, an automatic identification and data capture system is always the result of a compromise between recognition power and cost. This is why this International Standard is expressed in the form of guidelines rather than prescriptions. However, it is not technically possible to define guidelines concerning solely the printing of Digital Postage Marks without taking into account the manufacturing of the mail item as a whole. The readability of the Digital Postage Mark is a function not only of the inherent quality of printing, i.e. the interaction of the ink, substrate and printing mechanism together with the effects of the shape of the mail-piece and its transport through the printing system on the production of the mark, but also of the effects of environmental and handling factors in transit between the production point and the point at which it is to be read. For example, the symbol contrast of Digital Postage Marks is not only that provided by the printer/paper combination under defined illumination conditions. It also results from a variety

of other factors among which the covering of the mail item or the material of the transparent window through which the Digital Postage Mark may be seen. As a consequence, the guidelines described in this International Standard apply to the Digital Postage Mark blocks of fully assembled mail items. It is the responsibility of the users of this International Standard to achieve compliance with the guidelines by controlling the effects of the physical elements resulting in the relevant attributes.

The guidelines are primarily a tool for predicting the level of Digital Postage Mark readability with respect to current scanning technologies, and compliance with them should result in a high level of Digital Postage Mark readability. The guidelines are aimed at facilitating the relations between postal operators and customers, vendors of mail generation and printing equipment and suppliers of mail reading and sorting equipment. In particular, equipment vendors need firm and precise guidance in designing print systems and formats for machine readability. Therefore, a quantitative specification of print quality is critical to the development of products that meet the needs of mailers and postal operators.

Information technology — Office equipment — Print quality attributes for machine readable Digital Postage Marks

1 Scope

This International Standard:

- specifies a methodology for the measurement of defined print quality attributes of Digital Postage Marks in the form of two-dimensional bar code symbols on mail-pieces,
- defines methods for grading the results of these measurements and deriving an overall symbol quality grade as a guide to estimating the readability of the Digital Postage Marks,
- provides guidelines for printing and gives information on possible causes of deviation from high grades to assist users in taking appropriate corrective action,
- defines a test procedure for the assessment of printing systems for the production of Digital Postage Marks.

These provisions apply to the Digital Postage Mark blocks as they appear on fully produced mail items when remitted to postal operators, including the characteristics resulting from operations other than printing per se that affect their appearance to a mail processing system (covering, inserts into transparent window envelopes, affixed Digital Postage Mark labels).

This International Standard does not define the qualification tests or sampling requirements necessary to determine the practical feasibility of any specific read rate.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 15415:2004, *Information technology – Automatic identification and data capture techniques – Bar code print quality test specification – Two-dimensional symbols*

ISO/IEC 15416:2000, *Information technology – Automatic identification and data capture techniques – Bar code print quality test specification – Linear symbols*

ISO/IEC 15419:2001, *Information technology – Automatic identification and data capture techniques – Bar code digital imaging and printing performance testing*

ISO/IEC 15426-2:2005, *Information technology – Automatic identification and data capture techniques – Bar code verifier conformance specification – Part 2: Two-dimensional symbols.*

EN 1556:1996, *Bar coding – Terminology.*

Universal Postal Union (UPU) standard S-28, *Communication of Postal Information using Two-dimensional Symbols*

UPU standard S-36, *Digital Postage Marks: Applications, Security and Design*

UPU standard S-44-1, *Colour and Durability Attributes of Franking Marks*