

# INTERNATIONAL STANDARD

# ISO/IEC 18092

First edition  
2004-04-01

---

---

## Information technology — Telecommunications and information exchange between systems — Near Field Communication — Interface and Protocol (NFCIP-1)

*Technologies de l'information — Télécommunications et échange  
d'information entre systèmes — Communication de champ proche —  
Interface et protocole (NFCIP-1)*

Withhold

---

---

Reference number  
ISO/IEC 18092:2004(E)



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

Withdrawn

© ISO/IEC 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

Foreword.....	v
Introduction .....	vi
<b>1</b> <b>Scope</b> .....	<b>1</b>
<b>2</b> <b>Conformance</b> .....	<b>1</b>
<b>3</b> <b>Normative references</b> .....	<b>1</b>
<b>4</b> <b>Terms and definitions</b> .....	<b>1</b>
<b>5</b> <b>Conventions and notations</b> .....	<b>4</b>
<b>5.1</b> <b>Representation of numbers</b> .....	<b>4</b>
<b>5.2</b> <b>Names</b> .....	<b>4</b>
<b>6</b> <b>Acronyms</b> .....	<b>4</b>
<b>7</b> <b>General</b> .....	<b>5</b>
<b>8</b> <b>RF field</b> .....	<b>6</b>
<b>8.1</b> <b>Passive Communication Mode</b> .....	<b>6</b>
<b>8.2</b> <b>Active Communication Mode</b> .....	<b>6</b>
<b>8.3</b> <b>External RF field threshold value</b> .....	<b>6</b>
<b>9</b> <b>RF Signal Interface</b> .....	<b>6</b>
<b>9.1</b> <b>Bit duration</b> .....	<b>6</b>
<b>9.2</b> <b>Active communication mode</b> .....	<b>7</b>
<b>9.2.1</b> <b>106 kbps</b> .....	<b>7</b>
<b>9.2.2</b> <b>212 kbps and 424 kbps</b> .....	<b>9</b>
<b>9.3</b> <b>Passive communication mode</b> .....	<b>10</b>
<b>9.3.1</b> <b>106 kbps Initiator to Target</b> .....	<b>10</b>
<b>9.3.2</b> <b>106 kbps Target to Initiator</b> .....	<b>11</b>
<b>9.3.3</b> <b>212 kbps and 424 kbps Initiator to Target</b> .....	<b>11</b>
<b>9.3.4</b> <b>212 kbps and 424 kbps Target to Initiator</b> .....	<b>12</b>
<b>10</b> <b>General Protocol flow</b> .....	<b>12</b>
<b>11</b> <b>Initialization</b> .....	<b>13</b>
<b>11.1</b> <b>RF Collision Avoidance</b> .....	<b>13</b>
<b>11.1.1</b> <b>Initial RF Collision Avoidance</b> .....	<b>13</b>
<b>11.1.2</b> <b>Response RF Collision Avoidance</b> .....	<b>15</b>
<b>11.2</b> <b>Passive communication mode</b> .....	<b>16</b>
<b>11.2.1</b> <b>Initialisation and Single Device Detection at 106 kbps</b> .....	<b>16</b>
<b>11.2.2</b> <b>Initialisation and SDD at 212 kbps and 424 kbps</b> .....	<b>29</b>
<b>11.3</b> <b>Active communication mode</b> .....	<b>32</b>
<b>11.3.1</b> <b>Initialisation at 106, 212, and 424 kbps</b> .....	<b>32</b>
<b>11.3.2</b> <b>Active communication mode RF Collision Avoidance</b> .....	<b>32</b>
<b>12</b> <b>Transport Protocol</b> .....	<b>33</b>
<b>12.1</b> <b>Transport Data</b> .....	<b>33</b>
<b>12.2</b> <b>Passive communication mode Activation flow</b> .....	<b>34</b>
<b>12.3</b> <b>Active communication mode Activation flow</b> .....	<b>34</b>
<b>12.4</b> <b>Commands</b> .....	<b>37</b>
<b>12.5</b> <b>Activation of the protocol</b> .....	<b>37</b>
<b>12.5.1</b> <b>Attribute Request and Response Commands</b> .....	<b>37</b>
<b>12.5.2</b> <b>Wakeup Request and Response Commands</b> .....	<b>43</b>
<b>12.5.3</b> <b>Parameter Selection Request and Response Commands</b> .....	<b>45</b>
<b>12.6</b> <b>Data Exchange Protocol</b> .....	<b>48</b>

12.6.1	Data Exchange Protocol Request and Response .....	48
12.6.2	Response timeout extension .....	51
12.6.3	Attention – Target present.....	52
12.6.4	Protocol operation.....	52
12.6.5	Multi Activation.....	52
12.6.6	More information (Chaining) .....	53
12.7	Deactivation of the protocol.....	53
12.7.1	Deselect Request and Response command.....	54
12.7.2	Release Request and Response commands.....	55
Annex A	(normative) CRC calculation .....	57
A.1	CRC for Active and Passive communication mode at 106 kbps .....	57
A.2	Example of CRC calculation at 106 kbps .....	57
A.3	CRC for Active and Passive communication mode at 212 kbps and 424 kbps .....	58
A.4	Example of CRC calculation at 212 kbps and 424 kbps.....	58

Withdrawn

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 18092 was prepared by ECMA (as ECMA-340) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

Withhold

## Introduction

This International Standard specifies the interface and protocol for simple wireless communication between close coupled devices. These Near Field Communication (NFC) devices communicate with transfer rates of 106, 212, and 424 kbps.

This NFC Interface and Protocol (NFCIP-1) standard allows, but does not specify, applications in network products and consumer equipment.

Withdrawn

# Information technology — Telecommunications and information exchange between systems — Near Field Communication — Interface and Protocol (NFCIP-1)

## 1 Scope

This International Standard defines communication modes for Near Field Communication Interface and Protocol (NFCIP-1) using inductive coupled devices operating at the centre frequency of 13,56 MHz for interconnection of computer peripherals. It also defines both the Active and the Passive communication modes of Near Field Communication Interface and Protocol (NFCIP-1) to realize a communication network using Near Field Communication devices for networked products and also for consumer equipment. This International Standard specifies, in particular, modulation schemes, codings, transfer speeds, and frame format of the RF interface, as well as initialization schemes and conditions required for data collision control during initialization. Furthermore, this International Standard defines a transport protocol including protocol activation and data exchange methods.

Information interchange between systems also requires, at a minimum, agreement between the interchange parties upon the interchange codes and the data structure.

## 2 Conformance

A system implementing the Active and the Passive communication mode shall be in conformance with this International Standard if it meets all the mandatory requirements specified herein.

## 3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ITU-T V.41:1988, *Code-independent error-control system*