

INTERNATIONAL STANDARD

ISO/IEC 18809

First edition
2000-12-15

Information technology — 8 mm wide magnetic tape cartridge for information interchange — Helical scan recording AIT-1 with MIC format

*Technologies de l'information — Cartouche à bande magnétique de 8 mm
de large pour l'échange d'information — Enregistrement par balayage en
spirale AIT-1 avec format MIC*

Reference number
ISO/IEC 18809:2000(E)



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO/IEC 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Contents

Section 1 - General	1
1 Scope.....	1
2 Conformance.....	1
2.1 Magnetic tape cartridge.....	1
2.2 Generating drive.....	1
2.3 Receiving drive.....	1
3 Normative references.....	2
4 Terms and definitions.....	2
4.1 Absolute Frame Number (AFN).....	2
4.2 a.c. erase.....	2
4.3 Access.....	2
4.4 algorithm.....	2
4.5 Area ID.....	2
4.6 Automatic Track Finding (ATF).....	2
4.7 Average Signal Amplitude.....	2
4.8 azimuth.....	2
4.9 back surface.....	2
4.10 byte.....	2
4.11 cartridge.....	2
4.12 Channel bit.....	2
4.13 Codeword.....	2
4.14 Early Warning Point (EWP).....	2
4.15 End of Data (EOD).....	2
4.16 Entity.....	2
4.17 Error Correcting Code (ECC).....	2
4.18 flux transition position.....	2
4.19 flux transition spacing.....	2
4.20 Frame.....	3
4.21 Housekeeping Frame.....	3
4.22 Logical Beginning of Tape (LBOT).....	3
4.23 magnetic tape.....	3
4.24 Master Standard Amplitude Calibration Tape.....	3
4.25 Master Standard Reference Tape.....	3
4.26 Memory In Cartridge (MIC).....	3
4.27 Partition Boundary.....	3
4.28 Physical Beginning of Tape (PBOT).....	3
4.29 Physical End of Tape (PEOT).....	3
4.30 physical recording density.....	3
4.31 pre-recording condition.....	3
4.32 processing.....	3
4.33 processed data.....	3
4.34 Processed Record.....	3
4.35 record.....	3
4.36 Reference Field.....	3
4.37 Secondary Standard Amplitude Calibration Tape.....	3
4.38 Secondary Standard Reference Tape.....	3
4.39 Separator Mark.....	3
4.40 Standard Reference Amplitude (SRA).....	3
4.41 Tape Reference Edge.....	4
4.42 Typical Field.....	4
4.43 Standard Reference Current.....	4
4.44 Test Recording Current.....	4
4.45 track.....	4

4.46	unprocessed data.....	4
4.47	Unprocessed Record.....	4
5	Conventions and Notations.....	4
5.1	Representation of numbers.....	4
5.2	Names.....	4
6	Acronyms.....	4
7	Environment and safety.....	4
7.1	Test environment.....	4
7.2	Operating environment.....	5
7.3	Storage environment.....	5
7.4	Transportation.....	5
7.5	Safety.....	5
7.6	Flammability.....	5
Section 2 - Requirements for the case.....		6
8	Dimensional and mechanical characteristics of the case.....	6
8.1	General.....	6
8.2	Overall dimension (figures 5 and 6).....	6
8.3	Holding areas.....	7
8.4	Cartridge insertion.....	7
8.5	Window (figure 1).....	8
8.6	Loading grips (figures 5 and 7).....	8
8.7	Label areas (figures 6 and 8).....	8
8.8	Datum areas and Datum holes.....	8
8.9	Support areas (figure 9).....	9
8.10	Recognition holes (figures 10, 11 and 12).....	10
8.11	Write-inhibit hole (figure 11).....	10
8.12	Pre-positioning surfaces (figures 4 and 10).....	11
8.13	Cartridge lid (figures 6, 13 and 15).....	11
8.14	Cartridge reel lock (figures 10 and 16).....	12
8.15	Reel access holes (figure 10).....	13
8.16	Interface between the reels and the drive spindles.....	13
8.17	Light path (figures 10, 12, 20 and 21).....	14
8.18	Position of the tape in the case (figure 21).....	15
8.19	Tape path zone.....	15
8.20	Tape access cavity (figure 10).....	16
8.21	Tape access cavity clearance (figure 24).....	16
8.22	Requirements for the MIC (figures 25 and 26).....	16
8.23	Recognition recesses (figures 8 and 10).....	17
Section 3 - Requirements for the unrecorded tape.....		38
9	Mechanical, physical and dimensional characteristics of the tape.....	38
9.1	Materials.....	38
9.2	Tape length.....	38
9.2.1	Length of the magnetic tape.....	38
9.2.2	Length of the leader and trailer tapes.....	38
9.2.3	Length of the splicing tapes.....	38
9.3	Tape width.....	38
9.3.1	Width of the magnetic, leader and trailer tapes.....	38
9.3.2	Width and position of the splicing tape.....	38
9.4	Discontinuities.....	39
9.5	Tape thickness.....	39
9.5.1	Thickness of the magnetic tape.....	39
9.5.2	Thickness of the leader and trailer tapes.....	39
9.5.3	Thickness of the splicing tape.....	39
9.6	Longitudinal curvature.....	39

9.7	Cupping.....	39
9.8	Coating adhesion.....	39
9.9	Layer-to-layer adhesion.....	40
9.10	Tensile strength.....	40
9.10.1	Breaking strength.....	40
9.10.2	Yield strength.....	40
9.11	Residual elongation.....	40
9.12	Electrical resistance of the recording surface.....	40
9.13	Tape winding.....	41
9.14	Light transmittance of the tape.....	41
10	Magnetic recording characteristics.....	41
10.1	Typical Field.....	42
10.2	Signal Amplitude.....	42
10.3	Resolution.....	42
10.4	Overwrite.....	42
10.5	Ease of erasure.....	42
10.6	Tape quality.....	42
10.6.1	Missing pulses.....	42
10.6.2	Missing pulse zone.....	43
10.7	Signal-to-Noise Ratio (SNR) characteristic.....	43
Section 4 - Requirements for an interchanged tape.....		43
11	Format.....	43
11.1	General.....	43
11.2	Basic Groups.....	43
11.2.1	Entity.....	44
11.2.2	Group Information Table.....	45
11.2.3	Block Access Table (BAT).....	47
11.3	Sub-Groups.....	50
11.3.1	G1 Sub-Group.....	50
11.3.2	G2 Sub-Group - Randomizing.....	51
11.3.3	G3 Sub-Group.....	52
11.4	Data Block.....	53
11.4.1	ID information.....	54
11.4.2	Recording of the ID Information in the Data Block Headers.....	56
12	Method of recording.....	62
12.1	Physical recording density.....	62
12.2	Long-term average bit cell length.....	62
12.3	Short-term average bit cell length.....	62
12.4	Rate of change.....	62
12.5	Bit shift.....	63
12.6	Read signal amplitude.....	63
12.7	Maximum recorded levels.....	63
13	Track geometry.....	63
13.1	Track configuration.....	63
13.2	Average track pitch.....	63
13.3	Variations of the track pitch.....	64
13.4	Track width.....	64
13.5	Track angle.....	64
13.6	Track edge straightness.....	64
13.7	Track length.....	64
13.8	Azimuth angles.....	64
14	Recorded patterns.....	64
14.1	Recorded Data Block.....	64

14.2	Margin blocks	64
15	Format of a track.....	64
15.1	Track structure.....	64
15.2	Positioning accuracy.....	65
15.3	Tracking scheme.....	66
16	Layout of the tape	66
16.1	Device Area	67
16.2	Reference Area	67
16.3	Position Tolerance Band No. 1	68
16.4	System Area.....	68
16.4.1	System Preamble	68
16.4.2	System Log.....	68
16.4.3	System Postamble.....	72
16.4.4	Position Tolerance Band No. 2.....	72
16.4.5	Vendor Group Preamble	72
16.5	Data Area.....	72
16.5.1	Vendor Group.....	72
16.5.2	Recorded Data Group	72
16.5.3	ECC3	72
16.5.4	Multiple Recorded Instances	73
16.5.5	Repeated Frames.....	73
16.5.6	Appending and overwriting	74
16.6	EOD Area	75
16.7	Optional Device Area	75
16.8	Logical End Of Tape (LEOT).....	76
16.9	Logical Beginning of Tape (LBOT)	76
16.10	Early Warning Point - EWP.....	76
16.11	Empty Partition.....	76
16.12	Initialization.....	76
17	Housekeeping Frames.....	77
17.1	Amble Frames.....	77
17.2	System Amble Frames	77
18	Content of the MIC.....	77
 Annexes		
A	- Measurement of light transmittance.....	79
B	- Measurement of Signal-to-Noise Ratio	82
C	- Method for determining the nominal and the maximum allowable recorded levels	83
D	- Representation of 8-bit bytes by 10-bit patterns	84
E	- Measurement of bit shift	96
F	- Method of measuring the straightness of track edges.....	98
G	- ECC calculation	99
H	- Recommendations for transportation.....	102
J	- Read-After-Write	103
K	- Example of the content of a Basic Group No. 0	104
L	- Examples of MIC chip	105

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

This International Standard was prepared by ECMA (as ECMA-291) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval of national bodies of ISO and IEC.

Annexes A to G form a normative part of this International Standard, annexes H to L are for information only.

Introduction

This International Standard constitutes a further development of the magnetic tape cartridge specified in International Standard ISO/IEC 14833. A higher capacity is achieved by using a thinner, thus longer tape.

Information technology — 8 mm wide magnetic tape cartridge for information interchange — Helical scan recording AIT-1 with MIC format

Section 1 - General

1 Scope

This International Standard specifies the physical and magnetic characteristics of an 8 mm wide magnetic tape cartridge containing a memory chip to enable physical interchange of such cartridges between drives. It also specifies the quality of the recorded signals, the recording method and the recorded format - called Advanced Intelligent Tape No. 1 with Memory In Cartridge (AIT-1 with MIC) - thereby allowing data interchange between drives by means of such magnetic tape cartridges. The System Log is recorded in the MIC.

This International Standard specifies two types of cartridge depending on the thickness of the magnetic tape contained in the case.

Information interchange between systems also requires, at a minimum, agreement between the interchange parties upon the interchange code(s) and the specifications of the structure and labelling of the information on the interchanged cartridge.

2 Conformance

2.1 Magnetic tape cartridge

A tape cartridge shall be in conformance with this International Standard if it meets all the mandatory requirements specified herein. The tape requirements shall be satisfied throughout the extent of the tape.

2.2 Generating drive

A drive generating a magnetic tape cartridge for interchange shall be in conformance with this International Standard if all recordings on the tape meet the mandatory requirements of this International Standard, and if either or both methods of appending and overwriting are implemented. In addition, such a drive shall be able to record the System Log in the MIC.

A claim of conformance shall state which of the following optional features are implemented and which are not

- the performing of a Read-After-Write check and the recording of any necessary repeated frames;
- the generation of ECC3 Frames.

In addition a claim of conformance shall state

- whether or not one, or more, registered algorithm(s) are implemented within the system and are able to compress data received from the host prior to collecting the data into Basic Groups, and
- the registered identification number(s) of the implemented compression algorithm(s).

2.3 Receiving drive

A drive receiving a magnetic tape cartridge for interchange shall be in conformance with this International Standard if it is able to handle any recording made on the tape according to this International Standard. In particular it shall

- be able to read the System Log recorded in the MIC,
 - be able to recognise repeated frames, and to make available to the host, data and Separator Marks from only one of these frames;
 - be able to recognise multiple representations of the same Basic Group, and to make available to the host, data and Separator Marks from only one of these representations;
 - be able to recognise an ECC3 frame, and ignore it if the system is not capable of using ECC3 check bytes in a process of error correction;
 - be able to recognise processed data within an Entity, identify the algorithm used, and make its registered identification number available to the host;
 - be able to make processed data available to the host.
- In addition a claim of conformance shall state

- whether or not the system is capable of using ECC3 check bytes in a process of error correction;
- whether or not one or more de-compression algorithm(s) are implemented within the system, and are able to be applied to compressed data prior to making such data available to the host;
- the registered identification number(s) of the compression algorithm(s) for which a complementary de-compression algorithm is implemented.

3 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 527-3:1995	<i>Plastics – Determination of tensile properties – Part 3: Test conditions for films and sheets.</i>
ISO 1302:1992	<i>Technical drawings – Method of indicating surface texture on drawings.</i>
ISO/IEC 11576:1994	<i>Information technology – Procedure for the registration of algorithms for the lossless compression of data.</i>
IEC 60950:1999	<i>Safety of information technology equipment.</i>