

TECHNICAL REPORT

**ISO/IEC
TR
19782**

First edition
2006-06-01

Information technology — Automatic identification and data capture techniques — Effects of gloss and low substrate opacity on reading of bar code symbols

*Technologies de l'information — Techniques d'identification
automatique et de capture des données — Effets de la brillance et de la
faible opacité du substrat sur la lecture des symboles de code à barres*

Reference number
ISO/IEC TR 19782:2006(E)



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO/IEC 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

1	Scope	1
2	Normative references	1
3	Terms and definitions.....	1
4	Symbols and abbreviated terms	2
5	Measurement procedures	2
5.1	Effects of gloss and/or low opacity	2
5.2	Measurement of gloss	3
5.3	Measurement of opacity.....	4
6	Test reports	5
6.1	Test report for gloss	5
6.2	Test report for opacity.....	5
7	Impact of gloss and opacity effects on verification	5
Annex A	(informative) Example of gloss measurement technique	7
A.1	General description of set-up.....	7
A.2	Test fixture.....	8
A.3	Example profiles – substrate and image	8
A.4	Comparison of TAPPI T 425 Gloss measurements with gloss profile measurements.....	13
Annex B	(informative) Reporting of gloss measurements.....	14
B.1	Recommendation for gloss profile measurement.....	14
B.2	Example of scan rate profile	15
Annex C	(informative) Opacity measurement.....	17
C.1	Test Set-Up	17
C.2	Measurement of Opacity for purposes of gloss determination	17

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

In exceptional circumstances, the joint technical committee may propose the publication of a Technical Report of one of the following types:

- type 1, when the required support cannot be obtained for the publication of an International Standard, despite repeated efforts;
- type 2, when the subject is still under technical development or where for any other reason there is the future but not immediate possibility of an agreement on an International Standard;
- type 3, when the joint technical committee has collected data of a different kind from that which is normally published as an International Standard (“state of the art”, for example).

Technical Reports of types 1 and 2 are subject to review within three years of publication, to decide whether they can be transformed into International Standards. Technical Reports of type 3 do not necessarily have to be reviewed until the data they provide are considered to be no longer valid or useful.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC TR 19782, which is a Technical Report of type 3, was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 31, *Automatic identification and data capture techniques*.

Introduction

Users of bar code systems have experienced problems with poor read rates. These read rate problems can sometimes be attributed to spectral gloss from either the substrate or the image or both.

In many bar code applications, the position and orientation of the scanner relative to the bar code symbol can be directly controlled by the operator. In these applications, the presentation of the bar code symbol to the reader will usually be manipulated by the operator to achieve optimal performance. However, in bar code applications using fixed position automated reading systems, the ability to control bar code symbol presentation to the reader and achieve optimised performance is diminished.

Due to the very high volume of bar code marked items in today's supply chain, even a small reduction in read rate can represent significant logistics problems.

Traditional gloss measurements are made at the angle that maximises specular reflection and do not provide results that can be used to predict performance at other angles. Moreover, many laser scanners use a retro-collective optical system that would correspond to a gloss meter using a zero degree angle of incidence, which is not commonly available.

Present international bar code quality standards, such as ISO/IEC 15416, do not factor the impact of gloss from either the bar code image or substrate into quality grade ratings. Thus a Grade "4" label may be high gloss or low gloss. Low gloss labels and images tend to work well in all scanning systems, while high gloss labels and images may not. In the absence of industry specifications, users have no convenient reference to use when requesting suppliers to provide labels that will work well in their systems. This Technical Report provides a method for the measurement of gloss that will permit users to judge if the bar code symbol and substrate are suitably matched for the reading system used in their application.

Low opacity of the substrate can degrade system performance because it may reduce the apparent contrast of the bar code symbol. This Technical Report therefore provides means for measuring the substrate opacity.

The test method described in this Technical Report provides a means for the production of reproducible measurements. In specific applications, it may be necessary to correlate these measurements to practical performance. For example, a substrate backed by dark liquid may exhibit lower opacity than when measured dry.

Information technology — Automatic identification and data capture techniques — Effects of gloss and low substrate opacity on reading of bar code symbols

1 Scope

This Technical Report gives guidelines to deal with the effects of substrate gloss and/or low opacity on the performance of bar code symbols when scanned by reading and verification systems.

This Technical Report defines methods of measurement for gloss and opacity; it identifies conditions and values that present a risk of reading problems and provides recommendations to users on the specification of substrates and the set-up of scanning systems to minimize these problems. It also addresses the relationship between verification results and read performance when either or both of the factors are present.

This document is intended for those who specify or implement labelling systems and those involved in the reading of bar code symbols on packages, components and other carriers of bar code symbols.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 19762-1, *Information technology — Automatic identification and data capture (AIDC) techniques — Harmonized vocabulary — Part 1: General terms relating to AIDC*

ISO/IEC 19762-2, *Information technology — Automatic identification and data capture (AIDC) techniques — Harmonized vocabulary — Part 2: Optically readable media (ORM)*

ISO/IEC 15415, *Information technology — Automatic identification and data capture techniques — Bar code print quality test specification — Two-dimensional symbols*

ISO/IEC 15416, *Information technology — Automatic identification and data capture techniques — Bar code print quality test specification — Linear symbols*

TAPPI T 425 om-01, *Opacity of paper (15/d geometry, illuminant A/2°, 89 % reflectance backing and paper backing)*