

INTERNATIONAL STANDARD

ISO/IEC 22050

First edition
2002-10-01

Information technology — Data interchange on 12,7 mm, 384-track magnetic tape cartridges — Ultrium-1 format

*Technologies de l'information — Échange de données sur cartouches à
bande magnétique 12,7 mm, 384 pistes — Format Ultrium-1*

Reference number
ISO/IEC 22050:2002(E)



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO/IEC 2002

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Contents

Section 1 – General

1	Scope	1
2	Conformance	1
2.1	Magnetic tape cartridge	1
2.2	Generating system	1
2.3	Receiving system	1
3	Normative references	1
4	Terms and definitions	2
4.1	Access Point	2
4.2	algorithm	2
4.3	algorithmically processed data	2
4.4	a.c. erase	2
4.5	Average Signal Amplitude	2
4.6	back surface	2
4.7	Beginning of Tape (BOT)	2
4.8	Beginning of Wrap (BOW)	2
4.9	bit	2
4.10	bit cell	2
4.11	Broad Band Signal-to-Noise Ratio (BBSNR)	2
4.12	byte	2
4.13	cartridge	2
4.14	Channel bit	3
4.15	Codeword	3
4.16	Codeword Pair	3
4.17	Codeword Quad (CQ)	3
4.18	CQ Set	3
4.19	cyclic redundancy check (CRC) character	3
4.20	Data Set	3
4.21	Data Set Information Table (DSIT)	3
4.22	End of Data (EOD)	3
4.23	End of Tape (EOT)	3
4.24	End of Wrap (EOW)	3
4.25	Error Correcting Code (ECC)	3
4.26	File Mark	3
4.27	flux transition position	3
4.28	flux transition spacing	3
4.29	forward tape motion	3
4.30	header	3
4.31	Housekeeping Data Set	3
4.32	logical forward	4
4.34	Logical Point	4
4.35	magnetic tape	4
4.36	Master Standard Reference Tape (MSRT)	4
4.37	LTO Cartridge Memory (LTO CM)	4
4.38	Optimum Recording Current	4

4.39	physical end of tape	4
4.40	physical forward	4
4.41	physical reverse	4
4.42	pre-record condition	4
4.43	processed data	4
4.44	Processed Record	4
4.45	Processing (Compression)	4
4.46	Protected Record	4
4.47	Record	5
4.48	recorded element	5
4.50	Reprocessing (Decompression)	5
4.51	reverse tape motion	5
4.52	run length limited encoding (RLL)	5
4.53	Secondary Standard Reference Tape (SSRT)	5
4.54	servo acquisition region	5
4.55	Standard Reference Amplitude (SRA)	5
4.56	Symbol	5
4.57	Synchronised Codeword Quad (SCQ)	5
4.58	Test Recording Density (TRD)	5
4.59	wrap	5
4.60	write equalisation	5
4.61	(1,7) RLL code	5
5	Conventions and notations	6
5.1	Representation of numbers	6
5.2	Dimensions	6
5.3	Names	6
5.4	Alphanumeric string encoding	6
6	Acronyms	6
7	Environment and safety	6
7.1	Cartridge and tape testing environment	7
7.2	Cartridge operating environment	7
7.3	Cartridge storage environment	7
7.4	Tape tension	7
7.5	Safety	7
7.6	Flammability	7
7.7	Transportation	7
Section 2 - Requirements for the Cartridge		8
8	Dimensional and Mechanical Characteristics of the Cartridge	8
8.1	Elements of the cartridge	8
8.2	Reference Planes of the case	8
8.3	Dimensions of the case	8
8.3.1	Overall dimension	8
8.3.2	Reference points for reference planes	9
8.3.3	Positioning notches	10
8.3.4	Handling notches	10
8.3.5	Mis-insertion protection	11
8.3.6	Stacking features	11
8.3.7	Label area of the rear side	12
8.3.8	Central window	12
8.3.9	Sliding door	12
8.3.10	Case opening	12
8.4	Write-inhibit mechanism	13

8.5	Flexibility of the case	13
8.5.1	Requirements	13
8.5.2	Procedure	13
8.6	Tape reel	13
8.6.1	Locking mechanism	13
8.6.2	Axis of rotation of the reel	14
8.6.3	Reel flanges	14
8.6.4	Metallic insert	14
8.6.5	Toothed rim	15
8.6.6	Hub of the reel	15
8.6.7	Relative positions of hub and case	15
8.6.8	Characteristics of the toothed rim	15
8.7	Magnetic tape	16
8.7.1	Tape wind	16
8.7.2	Wind tension	16
8.7.3	Circumference of the tape reel	16
8.7.4	Moment of inertia	16
8.8	Leader pin assembly	17
8.8.1	Leader pin assembly dimensions	17
8.8.2	Leader tape attachment to leader pin assembly	17
8.8.3	Latching the leader pin assembly in the case	17
8.8.4	Mechanism and tape exit keepout area	18
8.9	LTO CM	18
8.10	Areas reserved for cartridge presence sensing	19
8.11	Handling grips and insertion indicator	19
8.11.1	Side grips	19
8.11.2	Insertion indicator	19
8.11.3	Top grip	19
8.11.4	Bottom grip	20
8.12	Pad Printing Areas	20
8.13	Opacity	20
Section 3 - Requirements for the Unrecorded Tape		35
9	Mechanical, physical and dimensional characteristics of the tape	35
9.1	Materials	35
9.2	Tape length	35
9.2.1	Length of magnetic tape	35
9.2.2	Length of leader tape	35
9.2.3	Length of splicing tape	35
9.3	Tape Width	35
9.3.1	Width of magnetic tape	35
9.3.2	Width of leader tape	35
9.3.3	Width of splicing tape	35
9.3.4	Procedure	36
9.4	Tape Thickness	36
9.4.1	Procedure	36
9.5	Longitudinal curvature	36
9.5.1	Procedure	36

9.6	Edge Quality	36
9.6.1	Edge deviation	36
9.7	Tape flatness	37
9.7.1	Cupping	37
9.7.2	Curl/Twist	38
9.8	Coating adhesion	38
9.8.1	Procedure	38
9.9	Layer-to-layer adhesion	38
9.9.1	Requirement	38
9.9.2	Procedure	39
9.10	Coefficient of friction	40
9.10.1	Requirement	40
9.10.2	Procedure for the measurement of the dynamic friction between the magnetic surface and the back surface	40
9.10.3	Procedure for the measurement of the dynamic friction between the back surface and SS-310 stainless steel	40
9.10.4	Procedure for the measurement of the dynamic friction between the magnetic surface and AlO ₂ /TiC ceramic	40
9.11	Surface quality	41
9.11.1	Surface roughness	41
9.12	Abrasivity	41
9.13	Tensile strength	41
9.13.1	Breaking strength	41
9.13.2	Offset yield strength	41
9.14	Longitudinal compliance	41
9.14.1	Procedure	42
9.15	Residual elongation	42
9.15.1	Requirement	42
9.15.2	Procedure	42
9.16	Flexural rigidity	42
9.16.1	Requirement	42
9.16.2	Procedure	42
9.17	Transverse dimensional stability	42
9.18	Electrical resistance of coated surfaces	42
9.18.1	Requirement	42
9.18.2	Procedure	42
10	Magnetic Recording Characteristics	43
10.1	General	43
10.2	Test conditions	43
10.3	Optimum Recording Current	44
10.4	Signal amplitude	44
10.5	Resolution	44
10.6	Overwrite	44
10.6.1	Requirement	44

10.7	Ease of erasure	44
10.8	Broad Band Signal-to-Noise Ratio	44
10.8.1	Requirement	44
10.9	Tape quality	44
10.9.1	Missing pulses	44
10.9.2	Missing pulse zone	45
Section 4 - Requirements for an Interchanged Tape		45
11	Method of recording servo bands	45
11.1	General	45
11.2	Servo bands	45
11.2.1	Servo stripes	46
11.2.2	Servo bursts	46
11.2.3	Servo frames	46
11.2.4	Servo signal amplitude	47
11.2.5	Servo signal polarity	47
11.2.6	Servo defects	48
11.3	Servo frame encoding	48
11.3.1	Method of encoding position and manufacturer's data	48
11.3.2	LPOS word construction	50
11.3.3	Tape manufacturer encoding	51
11.3.4	Cross tape identification	53
11.4	Servo band location	53
11.5	Servo band pitch	53
11.6	Nominal servo locations	53
11.7	Long-term average servo location	53
12	Method of recording data tracks	54
12.1	Physical recording density	54
12.2	Nominal bit cell length	54
12.3	Long-term average bit cell length	54
12.4	Short-term Average Bit Cell Length (STA)	54
12.5	Rate of change of the STA	54
12.6	Bit shift	54
12.7	Recording performance test conditions	54
12.8	Track sequence addressing	54
12.9	Location of data tracks	55
12.10	Track width	55
12.11	Adjacent track pitch	56
12.12	Azimuth	56
12.13	Total character skew	56
12.14	Channel Layout	56
13	Format	57
13.1	General	57
13.2	Protected Record	58
13.3	Processed Protected Record Sequence	59
13.3.1	Control Symbols	59
13.3.2	End Marker	60
13.3.3	Access Points	60
13.3.4	Alignment and append points	61

13.4	Data Set	61
13.4.1	Format Identification Data Set (FID)	61
13.4.2	User Data Set	62
13.4.3	EOD Data Set	62
13.4.4	Housekeeping Data Set	62
13.5	Data Set Information Table (DSIT)	62
13.5.1	Drive Manufacturer Use	63
13.5.2	Drive Manufacturer Use C1	63
13.5.3	Reserved	63
13.5.4	Drive Manufacturer's Identity	63
13.5.5	Data Set number	63
13.5.6	Valid Data Length	64
13.5.7	Access Point Offset	64
13.5.8	Total Records	64
13.5.9	Total File Marks	65
13.5.10	Record Count	65
13.5.11	File Mark Count	66
13.5.12	Thread Count	66
13.5.13	Data Set Type	66
13.5.14	Data Set Flags	67
13.5.15	Thread Write Pass	67
13.5.16	Tape Write Pass	67
13.6	ECC	67
13.6.1	Sub Data Set	68
13.6.2	C1 Sub Data Set	68
13.6.3	ECC Encoded Sub Data Set	69
13.6.4	Codeword Pair designation	70
13.7	Codeword Quads (CQ)	70
13.7.1	Codeword Pair Header	71
13.7.2	First Codeword Pair	72
13.7.3	Second Codeword Pair	72
13.8	Allocation of CQs to Logical Tracks	73
13.9	Data randomisation	74
13.10	RLL encoding	74
14	Recording of data on tape	75
14.1	Synchronised Data Set	75
14.1.1	Data Set Separator (DSS)	75
14.1.2	VFO Field 1	76
14.1.3	VFO Field 2	76
14.1.4	Synchronised Codeword Quad (SCQ)	76
14.2	Write equalisation bit encoding	77
14.3	Writing cells on tape	77
15	Regions on tape	77
15.1	Logical Points and regions	77
15.2	Calibration Region	79
15.3	User Data Region	79
15.4	Interrupted Data Sets	79
15.5	Repeated CQ Sets	80

15.6	Amble CQs	80
15.7	Beginning of Wrap (BOW)	81
15.8	End of Wrap (EOW)	81
15.9	Appending and Overwriting	81
15.10	Servo Tracking Faults	82
Annexes		
A	Measurement of Bit Shift	83
B	Measurement of Broad Band Signal-to-Noise Ratio	84
C	Tape Abrasivity Measurement Procedure	86
D	LTO Cartridge Memory	88
E	Flexural Rigidity Procedure	107
F	LTO CM electrical interface	109
G	Recommendations for transportation	126
H	Inhibitor Tape	127
I	Vendor code lists	128

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 22050 was prepared by ECMA (as ECMA-319) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

Annexes A to F form a normative part of this International Standard. Annexes G to I are for information only.

Information technology — Data interchange on 12,7 mm, 384-track magnetic tape cartridges — Ultrium-1 format

Section 1 — General

1 Scope

This International Standard specifies the physical and magnetic characteristics of magnetic tape cartridges, using magnetic tape 12,65 mm wide so as to provide physical interchange of such cartridges between drives. It also specifies the quality of the recorded signals, the recording method and the recorded format, thereby allowing data interchange between drives by means of such cartridges. The format supports variable length Logical Records, high speed search, and the use of a registered algorithm for data compression.

This International Standard specifies four types of cartridges depending on the length of tape contained in the case. These four types are referred to as Type A, Type B, Type C and Type D; their nominal capacity is 100 Gbytes, 50 Gbytes, 30 Gbytes and 10 Gbytes, respectively.

NOTE - One Gbyte contains 1 000 000 000 bytes.

Information interchange between systems also requires, at a minimum, agreement between the interchange parties upon the interchange code(s) and the specification of the structure and labeling of the information on the interchanged cartridge.

This International Standard shall be used only in conjunction with ISO/IEC 22091.

Together with a standard for volume and file structure, e.g. Standard ISO 1001, this document provides for full data interchange between data processing systems.

2 Conformance

2.1 Magnetic tape cartridge

A tape cartridge shall be in conformance with this International Standard if it meets all the mandatory requirements specified herein. The tape requirements shall be satisfied throughout the extent of the tape.

2.2 Generating system

A system generating a magnetic tape cartridge for interchange shall be in conformance with this International Standard if all the recordings that it makes meet the mandatory requirements of this International Standard.

2.3 Receiving system

A system receiving a magnetic tape cartridge for interchange shall be in conformance with this International Standard if it is able to handle any recording made on the tape according to this International Standard.

3 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 1001:1986	<i>Information processing — File structure and labelling of magnetic tapes for information interchange</i>
ISO 527 (all parts)	<i>Plastics — Determination of tensile properties</i>
ISO 3574:1999	<i>Cold-reduced carbon steel sheet of commercial and drawing qualities</i>
ISO 4287:1997	<i>Geometrical product specification (GPS) — Surface texture: Profile method — Terms, definitions and surface texture parameters</i>
ISO/IEC 646:1991	<i>Information technology — ISO 7-bit coded character set for information interchange</i>

- ISO/IEC 11576:1994 *Information technology — Procedure for the registration of algorithms for the lossless compression of data*
- ISO/IEC 14443-2:2001 *Identification cards — Contactless integrated circuit(s) cards — Proximity cards — Part 2: Radio frequency power and signal interface*
- ISO/IEC 22091:2002 *Information technology — Streaming Lossless Data Compression algorithm (SLDC)*
- IEC 60950-1:2001 *Information technology equipment — Safety — Part 1: General requirements*
- ASTM D4065-01:1995 *Standard Practice for Plastics: Dynamic Mechanical Properties: Determination and Report of Procedures*
- ASTM D4092-01:1996 *Standard Terminology: Plastics: Dynamic Mechanical Properties*