

INTERNATIONAL STANDARD

ISO/IEC 22533

First edition
2005-07-01

Information technology — Data interchange on 90 mm optical disk cartridges — Capacity: 2,3 Gbytes per cartridge

*Technologies de l'information — Échange de données sur cartouches
de disque optique de 90 mm — Capacité: 2,3 Go par cartouche*

Reference number
ISO/IEC 22533:2005(E)



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO/IEC 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	vii
Section 1 - General	1
1 Scope	1
2 Conformance	1
2.1 Optical disk Cartridge (ODC)	1
2.2 Generating system.....	1
2.3 Receiving system.....	2
2.4 Compatibility statement	2
3 Normative references	2
4 Terms and definitions.....	2
5 Conventions and notations	5
5.1 Representation of numbers	5
5.2 Names	5
6 Abbreviations and acronyms	5
7 General description of the optical disk cartridge	6
8 General requirements	6
8.1 Environments	6
8.2 Temperature shock.....	8
8.3 Safety requirements	8
8.4 Flammability	8
9 Reference Drive.....	8
9.1 Optical system	8
9.2 Optical beam	9
9.3 Read channels.....	10
9.4 Tracking	10
9.5 Rotation of the disk	10
Section 2 - Mechanical and physical characteristics	11
10 Dimensional and physical characteristics of the case	11
10.1 General description of the case (see Figure 2).....	11
10.2 Reference planes of the case	11
10.3 Dimensions of the case.....	11
10.4 Mechanical characteristics	18
11 Dimensional, mechanical and physical characteristics of the disk	31
11.1 General description of the disk	31
11.2 Reference axis and plane of the disk.....	31
11.3 Dimensions of the disk (see Figure 13)	31
11.4 Mechanical characteristics	32
11.5 Optical Characteristics	34
12 Interface between cartridge and drive	36
12.1 Clamping method.....	36
12.2 Clamping force	36
12.3 Capture cylinder (see Figure 14)	36
12.4 Disk position in operating condition (see Figure 14).....	36

Section 3 - Format of information.....	38
13 Geometry of physical tracks	38
13.1 Physical track shape.....	38
13.2 Direction of track spiral	39
13.3 Physical track pitch	39
14 Track format.....	39
14.1 Logical Track number	39
14.2 Logical Track layout	39
14.3 Clock frequencies and periods.....	40
14.4 Radial alignment	40
14.5 Sector number	41
15 Sector format	41
15.1 Sector layout.....	41
15.2 Sector Mark (SM).....	42
15.3 VFO fields.....	42
15.4 Address Mark (AM)	43
15.5 ID fields	43
15.6 Postambles (PA).....	44
15.7 Gap	45
15.8 Sync.....	45
15.9 Data field	45
15.10 VCO lock pattern field (VLP)	46
15.11 Buffer field	46
16 Recording code	46
17 Format of the Information Zone.....	47
17.1 General description of the Information Zone	47
17.2 Division of the Information Zone.....	47
18 Format of the Data Zone.....	51
18.1 Buffer tracks and Test tracks in the Data Zone	51
18.2 Defect Management Areas (DMAs)	51
18.3 Disk Definition Structure (DDS)	55
18.4 Partitioning	55
18.5 Logical block address	55
19 Defect management	57
19.1 Initialization of the disk	57
19.2 Certification	57
19.3 Disks not certified	58
19.4 Write procedure.....	58
19.5 Primary Defect List (PDL).....	58
19.6 Secondary Defect List (SDL).....	59
Section 4 - Characteristics of embossed information.....	60
20 Method of testing	60
20.1 Environment	60
20.2 Use of the Reference Drive	60
20.3 Definition of signals	61
21 Signals from grooves	62
21.1 Divided push-pull signal.....	62
21.2 Phase depth.....	63
21.3 Track location	63
22 Signals from Headers	63
22.1 Sector Mark.....	64
22.2 VFO1 and VFO2	64
22.3 Address Mark, ID field and Postamble.....	64
22.4 Timing jitter.....	64

22.5	Asymmetry	65
23	Signals from embossed Recording fields	65
23.1	Signal amplitude	65
23.2	Timing jitter	65
Section 5 - Characteristics of the recording layer and user data		66
24	Method of testing	66
24.1	Environment	66
24.2	Reference Drive.....	66
24.3	Write conditions	67
24.4	Erase conditions	69
24.5	Definition of signals.....	70
25	Magneto-optical characteristics	70
25.1	Figure of merit.....	70
25.2	Imbalance of the magneto-optical signal	70
26	Write characteristics.....	71
26.1	Resolution	71
26.2	Narrow-band signal-to-noise ratio (NBSNR).....	72
26.3	Cross-talk ratio.....	73
26.4	Timing jitter	73
26.5	Media thermal interaction	73
27	Erase power determination.....	74
Section 6 - Characteristics of user data		75
28	Method of testing	75
28.1	Environment	75
28.2	Reference Drive.....	75
29	Minimum quality of a sector	76
29.1	Headers.....	76
29.2	User-written data.....	77
30	Data interchange requirements.....	77
30.1	Tracking	77
30.2	User-written data.....	77
30.3	Quality of disk	77
Annex A (normative) Edge distortion test		78
Annex B (normative) Compliance test		79
Annex C (normative) CRC for ID fields		81
Annex D (normative) Interleave, CRC, ECC, Resync for the data field.....		82
Annex E (normative) Contents of the Control Zone		87
Annex F (normative) Determination of the Resync patterns		94
Annex G (normative) Measurement of the figure of merit		99
Annex H (normative) Read Channel for measuring NBSNR and jitter.....		100
Annex I (normative) Implementation Independent Mark Quality Determination (IIMQD) for the interchange of recorded media		103
Annex J (normative) Air cleanliness class 100 000		104
Annex K (normative) Position of the cartridge relative to the reference planes		105
Annex L (normative) Relaxation by zones of the requirements for signals.....		106
Annex M (normative) Test method for measuring the adsorbent force of the hub.....		107
Annex N (informative) Track deviation measurement		109

Annex O (informative) **Derivation of the operating climatic environment** 113

Annex P (informative) **Transportation** 118

Annex Q (informative) **Office environment** 119

Annex R (informative) **Values to be implemented in existing and future standards** 120

Annex S (informative) **Measurement of the vertical birefringence of the substrate**..... 121

Annex T (informative) **Sector retirement guidelines** 123

Annex U (informative) **Laser power calibration for evaluation of media power sensitivity**..... 124

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 22533 was prepared by Ecma (as ECMA-353) and was adopted, under a special fast-track procedure, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 23, *Digital storage media for information interchange*, in parallel with its approval by national bodies of ISO and IEC.

Information technology — Data interchange on 90 mm optical disk cartridges — Capacity: 2,3 Gbytes per cartridge

Section 1 - General

1 Scope

This International Standard defines the characteristics of 90 mm Optical Disk Cartridges (ODC) with a capacity of 2,3 GB per Cartridge. The Standard specifies only Type R/W for 2 048-byte sectors of such cartridge.

Type R/W provides for data to be written, read and erased many times over the entire recording surface of the disk using the thermo-magnetic and magneto-optical effects. It is also referred to as "fully rewritable". This International Standard provides for 2 048-byte sectors only. All sectors on a disk are of the same size.

This International Standard specifies

- the conditions for conformance testing and the Reference Drive;
- the environments in which the cartridges are to be operated and stored;
- the mechanical and physical characteristics of the cartridge, so as to provide mechanical interchangeability between data processing systems;
- the format of the information on the disk, both embossed and user-written; including the physical disposition of the tracks and sectors, the error correction codes, and the modulation method used;
- the characteristics of the embossed information on the disk;
- the magneto-optical characteristics of the disk, enabling processing systems to write data onto the disk;
- the minimum quality of user-written data on the disk, enabling data processing systems to read data from the disk.

This International Standard provides for interchange between optical disk drives. Together with a standard for volume and file structure, it provides for full data interchange between data processing systems.

2 Conformance

2.1 Optical disk Cartridge (ODC)

A claim of conformance with this International Standard shall specify the Type of the ODC. It shall be in conformance if it meets all mandatory requirements specified herein for that Type.

2.2 Generating system

A claim of conformance with this International Standard shall specify which Type is supported. A system generating an ODC for interchange shall be in conformance with this International Standard if it meets the mandatory requirements of this International Standard for the Type specified.

2.3 Receiving system

A claim of conformance with this International Standard shall specify which Type is supported. A system receiving an ODC for interchange shall be in conformance with this International Standard if it is able to process any recording made on the cartridge in accordance with 2.1 on the Type specified.

2.4 Compatibility statement

A claim of conformance with this International Standard shall include a statement listing any other International Standard supported by the system for which conformance is claimed. This statement shall specify the number of the Standard(s), the ODC type(s) supported (where appropriate) and whether support includes reading or both reading and writing.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ECMA-287 *Safety of electronic equipment (2002)*