

This is a preview - click here to buy the full publication

STANDARD

**ISO/IEC
23912**

First edition
2005-11-01

Corrected version
2006-04-01

Information technology — 80 mm (1,46 Gbytes per side) and 120 mm (4,70 Gbytes per side) DVD Recordable Disk (DVD-R)

*Technologies de l'information — Disque enregistrable DVD (DVD-R) de
80 mm (1,46 GB par face) et 120 mm (4,7 GB par face) de diamètre*

Reference number
ISO/IEC 23912:2005(E)



© ISO/IEC 2005

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO/IEC 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Section 1 - General.....	1
1 Scope.....	1
2 Conformance	1
2.1 Optical Disk.....	1
2.2 Generating system	1
2.3 Receiving system	2
3 Normative references.....	2
4 Terms and definitions	2
5 Conventions and notations	4
5.1 Representation of numbers.....	4
5.2 Names	5
6 Acronyms	5
7 General description of a disk.....	6
8 General requirement	7
8.1 Environments.....	7
8.1.1 Test environment.....	7
8.1.2 Operating environment.....	7
8.1.3 Storage environment.....	8
8.1.4 Transportation	8
8.2 Safety requirements	9
8.3 Flammability.....	9
9 Reference measurement devices	9
9.1 Pick-Up Head (PUH)	9
9.1.1 PUH for measuring recorded disks	9
9.1.2 PUH for measuring unrecorded disks.....	11
9.2 Measurement conditions	12
9.2.1 Recorded and unrecorded disk	12
9.2.2 Recorded disk.....	12
9.2.3 Unrecorded disk	12
9.3 Normalized servo transfer function.....	12
9.4 Reference servo for axial tracking.....	13
9.5 Reference servo for radial tracking	14
Section 2 - Dimensional, mechanical and physical characteristics of the disk.....	16
10 Dimensional characteristics.....	16
10.1 Overall dimensions	17
10.2 First transition area.....	18
10.3 Second transition area.....	18
10.4 Clamping Zone.....	18
10.5 Third transition area.....	18
10.6 R-Information Zone	19
10.6.1 Sub-divisions of the R-Information Zone.....	19
10.7 Information Zone	19
10.7.1 Sub-divisions of the Information zone	19
10.8 Track geometry	20
10.9 Channel bit length	20
10.10 Rim area	21
10.11 Remark on tolerances	21
10.12 Label	21

11	Mechanical parameters	22
11.1	Mass	22
11.2	Moment of inertia.....	22
11.3	Dynamic imbalance	22
11.4	Sense of rotation.....	22
11.5	Runout	22
11.5.1	Axial runout	22
11.5.2	Radial runout.....	22
12	Optical parameters	23
12.1	Recorded and unrecorded disk parameters	23
12.1.1	Index of refraction.....	23
12.1.2	Thickness of the transparent substrate	23
12.1.3	Angular deviation.....	23
12.1.4	Birefringence of the transparent substrate.....	24
12.2	Recorded disk reflectivity	24
12.3	Unrecorded disk parameters	24
12.3.1	Polarity of reflectivity modulation.....	24
12.3.2	Recording power sensitivity variation	24
	Section 3 - Operational signals	25
13	Operational signals for recorded disk	25
13.1	Measurement conditions	25
13.2	Read conditions	25
13.3	Recorded disk high frequency (HF) signals	25
13.3.1	Modulated amplitude	25
13.3.2	Signal asymmetry	26
13.3.3	Cross-track signal.....	26
13.4	Quality of signals	26
13.4.1	Jitter	26
13.4.2	Random errors	26
13.4.3	Defects	26
13.5	Servo signals.....	27
13.5.1	Differential phase tracking error signal.....	27
13.5.2	Tangential push-pull signal	27
13.6	Groove wobble signal	29
14	Operational signals for the unrecorded disk	30
14.1	Measurement conditions	30
14.2	Recording conditions	30
14.3	Basic write strategy for media testing	30
14.3.1	Definition of the write pulse.....	31
14.4	Servo signals.....	31
14.4.1	Radial push-pull tracking error signal	32
14.4.2	Defects	33
14.5	Addressing signals	33
14.5.1	Land Pre-Pit signal	33
14.5.2	Groove wobble signal	35
14.5.3	Relation in phase between wobble and Land Pre-Pit	35
	Section 4 - Data format.....	37
15	General.....	37
16	Data Frames	37
16.1	Identification Data (ID).....	38
16.2	ID Error Detection Code	39
16.3	RSV	39
16.4	Error Detection Code.....	39
17	Scrambled Frames	39
18	ECC Block configuration	40

19	Recording Frames	42
20	Modulation	43
21	Physical Sectors.....	43
22	Suppress control of the d.c. component	45
23	Linking scheme	46
23.1	Structure of linking.....	46
23.2	2K-Link and 32K-Link.....	47
23.3	Lossless-Link.....	47
	Section 5 - Format of the Information Zone.....	50
24	General description of the Information Zone	50
24.1	Layout of the Information Zone	50
24.2	Physical Sector numbering	50
25	Lead-in and Lead-out Zone	51
25.1	Lead-in Zone	51
25.1.1	Initial Zone.....	52
25.1.2	Buffer Zone 0	52
25.1.3	R-Physical Format Information Zone	52
25.1.4	Reference Code Zone.....	54
25.1.5	Buffer Zone 1	54
25.1.6	Control Data Zone	55
25.1.7	Extra Border Zone	58
25.2	Lead-out Zone	58
	Section 6 - Format of the Unrecorded Zone	59
26	General description of the Unrecorded Zone	59
26.1	Layout of the Unrecorded Zone	59
26.2	ECC Block address	59
26.3	ECC Block numbering.....	60
27	Pre-pit Data format	60
27.1	General description.....	60
27.2	Pre-pit block structure	62
27.3	Pre-pit data block configuration	64
27.3.1	Relative address	65
27.3.2	ECC Block address data configuration.....	66
27.3.3	Parity A and Parity B	66
27.3.4	Field ID0.....	67
27.3.5	Field ID1.....	68
27.3.6	Field ID2 and ID5.....	70
27.3.7	Field ID3 and Field ID4	75
28	Data structure of R-Information Zone	77
28.1	Layout of Power Calibration Area and Recording Management Area	77
28.2	Structure of the Power Calibration Area	77
28.3	Data configuration of the Recording Management Area (RMA)	78
28.3.1	Sector format of the Recording Management Area	78
28.3.2	Recording Management Data (RMD)	79
	Annex A (normative) Measurement of the angular deviation α	88
	Annex B (normative) Measurement of birefringence	90
	Annex C (normative) Measurement of the differential phase tracking error	93
	Annex D (normative) Measurement of light reflectance	97
	Annex E (normative) Tapered cone for disk clamping	99
	Annex F (normative) Measurement of jitter.....	100
	Annex G (normative) 8-to-16 Modulation with RLL (2,10) requirements.....	103

Annex H (normative) Optimum Power Control	113
Annex J (normative) Measurement of the groove wobble amplitude.....	115
Annex K (normative) Measurement methods for the operational signals for an unrecorded disk	117
Annex L (normative) NBCA Code	118
Annex M (normative) Border Zone	124
Annex N (normative) Write Strategy variations	133
Annex P (normative) Measurement method of the Land Pre-Pit signal	134
Annex Q (informative) Transportation.....	135

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 23912 was prepared by ECMA (as ECMA-359) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

This corrected version of ISO/IEC 23912:2005 incorporates the following corrections:

- description of Figure 20 corrected in 14.5.1;
- data for Table 26 corrected in 28.3.2.1;
- label for Figure F.3 corrected in F.4;
- Figure J.1 in J.2 corrected;
- on the third line of page 128 (M.3.1), the words "see Table M.2" replaced by "see Table M.3";
- the text of the last line of page 130 (M.3.1) corrected.

Introduction

In June 2001 eleven members proposed to ECMA TC31 to develop a standard for 120 mm and 80 mm DVD Recordable optical disks using Organic Dye recording technology and TC31 adopted this project. In April 2004 ten members proposed to TC31 to restart this project and TC31 re-activated the work that has resulted in this International Standard.

This International Standard specifies two Types of Recordable optical disks, one (Type 1S) making use of recording on only a single side of the disk and yielding a nominal capacity of 4,70 Gbytes for a 120 mm disk and 1,46 Gbytes for an 80 mm disk, the other (Type 2S) making use of recording on both sides of the disk and yielding a nominal capacity of 9,4 Gbytes for a 120 mm disk and 2,92 Gbytes for an 80 mm disk.

Information technology — 80 mm (1,46 Gbytes per side) and 120 mm (4,70 Gbytes per side) DVD Recordable Disk (DVD-R)

Section 1 - General

1 Scope

This International Standard specifies the mechanical, physical and optical characteristics of an 80 mm and a 120 mm DVD Recordable disk to enable the interchange of such disks. It specifies the quality of the pre-recorded, unrecorded and the recorded signals, the format of the data, the format of the information zone, the format of the unrecorded zone, and the recording method, thereby allowing for information interchange by means of such disks. This disk is identified as a DVD Recordable (DVD-R) disk.

This International Standard specifies

- 80 mm and 120 mm nominal diameter disks that may be either single or double sided,
- the conditions for conformance,
- the environments in which the disk is to be operated and stored,
- the mechanical and physical characteristics of the disk, so as to provide mechanical interchange between data processing systems,
- the format of the pre-recorded information on an unrecorded disk, including the physical disposition of the tracks and sectors, the error correcting codes and the coding method used,
- the format of the data and the recorded information on the disk, including the physical disposition of the tracks and sectors, the error correcting codes and the coding method used,
- the characteristics of the signals from pre-recorded and unrecorded areas on the disk, enabling data processing systems to read the pre-recorded information and to write to the disks,
- the characteristics of the signals recorded on the disk, enabling data processing systems to read the data from the disk.

This International Standard provides for interchange of disks between disk drives. Together with a standard for volume and file structure, it provides for full data interchange between data processing systems.

2 Conformance

2.1 Optical Disk

A claim of conformance shall specify the type of the disk, i.e. its size and whether it is single-sided or double sided. An optical disk shall be in conformance with this International Standard if it meets the mandatory requirements specified for this type.

2.2 Generating system

A generating system shall be in conformance with this International Standard if the optical disk it generates is in accordance with 2.1.

2.3 Receiving system

A receiving system shall be in conformance with this International Standard if it is able to handle an optical disk according to 2.1.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 8859-1, *Information technology — 8-bit single-byte coded graphic character sets — Part 1: Latin alphabet No. 1*

ISO/IEC 8859-2, *Information technology — 8-bit single-byte coded graphic character sets — Part 2: Latin alphabet No. 2*

ISO/IEC 8859-3, *Information technology — 8-bit single-byte coded graphic character sets — Part 3: Latin alphabet No. 3*

ISO/IEC 8859-4, *Information technology — 8-bit single-byte coded graphic character sets — Part 4: Latin alphabet No. 4*

ECMA-287, *Safety of electronic equipment – 2nd edition (December 2002)*