
**Information technology — Real-time
locating systems (RTLS) —**

Part 5:

**Chirp spread spectrum (CSS) at 2,4 GHz
air interface**

*Technologies de l'information — Systèmes de localisation en temps réel
(RTLS) —*

*Partie 5: Spectre étalé de compression d'impulsions (CSS) à une
interface d'air de 2,4 GHz*

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**COPYRIGHT PROTECTED DOCUMENT**

© ISO/IEC 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	vi
Introduction.....	vii
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols and abbreviated terms	3
5 Overview	6
5.1 Components	6
5.2 Purpose	6
5.3 Not covered by the standard	7
5.4 System	7
5.5 Document structure	7
6 Requirements	7
6.1 Frequency range	7
6.2 2,4 GHz spread spectrum air interface specifications	7
6.3 Compliance requirements	8
6.4 Manufacturer tag ID	8
6.5 Physical layer parameters	8
7 Physical (PHY) layer specification	9
7.1 Modulations	9
7.2 Data rates	9
7.2.1 General PHY packet format	9
7.3 2-ary orthogonal CSS	9
7.3.1 Reference modulator diagram	10
7.3.2 Bandwidths and Transmit power spectral density (PSD) mask	10
7.3.3 Equivalent baseband representation of the continuous time 2-ary orthogonal CSS signal	12
7.3.4 Signal tolerance	13
7.3.5 Bit to symbol mapping	13
7.3.6 Chirp generator	13
7.3.7 Preamble	13
7.3.8 Start of frame delimiter	14
7.3.9 Bit scrambler	14
7.3.10 PHY Header	14
7.3.11 Overview (informative)	14
7.4 DQPSK-CSS	16
7.4.1 Reference modulator diagram	16
7.4.2 Bandwidth and transmit Power Spectral Density (PSD) mask	17
7.4.3 Equivalent baseband representation of the continuous time DQPSK-CSS signal	18
7.4.4 Signal tolerance	20
7.4.5 Overview (informative)	20
7.4.6 Demultiplexer (DEMUX)	22
7.4.7 Serial to Parallel mapping (S/P)	22
7.4.8 Data Symbol - to - Bi-Orthogonal code word mapping	22
7.4.9 Parallel - to - Serial converter (P/S) and QPSK symbol mapping	25
7.4.10 Differential-QPSK (DQPSK) coding	25
7.4.11 DQPSK to DQPSK-CSS modulation	26
7.4.12 Chirp generator	26
7.4.13 Bit interleaver	26

7.4.14	Preamble	26
7.4.15	Start of frame delimiter	27
7.4.16	PHY Header	27
8	MAC sub-layer specification.....	27
8.1	Overview	27
8.2	General packet format.....	27
8.3	Packet types	27
8.4	MAC frame formats.....	28
8.4.1	MAC frame format for Data packet.....	28
8.4.2	MAC frame format for ACK packet.....	28
8.4.3	MAC frame format for Broadcast packet.....	28
8.4.4	MAC frame format for RTS packet	29
8.4.5	MAC frame format for CTS packet	29
8.4.6	MAC frame fields.....	29
8.5	MAC Timing	31
8.5.1	2-way handshake	31
8.5.2	3-way handshake	32
8.5.3	Ranging-related time measurements.....	33
8.5.4	Media access	33
9	Tag application layer specification	36
9.1	Overview	36
9.1.1	Example scenario	37
9.2	Tag application states	38
9.2.1	Default state	38
9.2.2	Wait state	38
9.2.3	Range state.....	39
9.2.4	Sleep state	39
9.2.5	Blink state	39
9.2.6	State transitions.....	40
9.3	Commands	41
9.3.1	SwitchState command	42
9.3.2	SetConfigVector command.....	45
9.3.3	GetConfigVector command	47
9.3.4	SetRangingPeers command	47
9.3.5	AddRangingPeers command.....	47
9.3.6	GetRangingPeers command.....	48
9.3.7	User defined command	48
9.3.8	Command prioritization	48
9.4	Tag application packet formats.....	49
9.4.1	Application blink packet	50
9.4.2	Application command packet.....	51
9.4.3	Application report packet	51
9.4.4	GetConfigVector report.....	52
9.4.5	GetRangingPeers report	52
9.4.6	Ranging report	52
9.4.7	Application ranging packet.....	53
9.5	Ranging packet exchanges	57
9.5.1	Ranging packet exchange type 1	57
9.5.2	Ranging packet exchange type 2	58
9.5.3	Ranging packet exchange type 3.....	60
9.5.4	Ranging packet exchange type 4.....	61
9.6	Timing values.....	62
9.7	Default profile.....	62
9.8	Error handling	62
Annex A (informative) Time base tolerances in two-way ranging.....		63
Annex B (informative) Coexistence		66
Annex C (informative) Computing location values from range values.....		69

Annex D (informative) Location and roaming of tags	70
Bibliography	72

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 24730-5 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 31, *Automatic identification and data capture techniques*.

ISO/IEC 24730 consists of the following parts, under the general title *Information technology — Real-time locating systems (RTLS)*:

- *Part 1: Application program interface (API)*
- *Part 2: 2,4 GHz air interface protocol*
- *Part 5: Chirp spread spectrum at 2,4 GHz air interface*

Introduction

CSS is a technique for spreading the bandwidth of a digital signal by using chirp pulses. Chirp pulses are pulses with a monotonically increasing or decreasing instantaneous frequency. Chirp pulses were originally used for radar applications. Recently, systems and standards have been developed which use chirp pulses also for communication applications. This part of ISO/IEC 24730 includes ranging and bidirectional communication between tags and infrastructure. Bidirectional communication enables the infrastructure to control the behaviour of tags in a timely manner.

Information technology — Real-time locating systems (RTLS) —

Part 5: Chirp spread spectrum (CSS) at 2,4 GHz air interface

1 Scope

ISO/IEC 24730 defines air interface protocols and an application programming interface (API) for real-time locating systems (RTLS). This part of ISO/IEC 24730 defines an air interface protocol which utilizes chirp spread spectrum (CSS) at frequencies from 2,4 GHz to 2,483 GHz. This protocol supports bidirectional communication and two-way ranging between the readers and tags of an RTLS. The mandatory default mode ensures interoperability between tags and infrastructure from various manufacturers, while the availability of several options offers flexibility to the developer of the infrastructure to adapt the behaviour of the overall system to the specific needs of his application.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 15963, *Information technology — Radio frequency identification for item management — Unique identification for RF tags*

ISO/IEC 19762-1, *Information technology — Automatic identification and data capture (AIDC) techniques — Harmonized vocabulary — Part 1: General terms relating to AIDC*

ISO/IEC 19762-3, *Information technology — Automatic identification and data capture (AIDC) techniques — Harmonized vocabulary — Part 3: Radio frequency identification (RFID)*

ISO/IEC 19762-4, *Information technology — Automatic identification and data capture (AIDC) techniques — Harmonized vocabulary — Part 4: General terms relating to radio communications*

ISO/IEC 19762-5, *Information technology — Automatic identification and data capture (AIDC) techniques — Harmonized vocabulary — Part 5: Locating systems*

ISO/IEC 24730-1, *Information technology — Real-time locating systems (RTLS) — Part 1: Application program interface (API)*

Guidelines on Limiting Exposure to Non-Ionizing Radiation, International Commission on Non-Ionizing Radiation Protection (ICNIRP), Munich, 1999

IEC 62369-1 ed1.0, *Evaluation of human exposure to electromagnetic fields from short range devices (SRDs) in various applications over the frequency range 0 GHz to 300 GHz — Part 1: Fields produced by devices used for electronic article surveillance, radio frequency identification and similar systems*

IEEE Std C95.1-2005, *IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz*