
**Information technology —
Telecommunications and information
exchange between systems —
MAC-PHY interface for ISO/IEC 26907**

*Technologies de l'information — Téléinformatique —
Interface MAC-PHY pour l'ISO/CEI 26907*

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**COPYRIGHT PROTECTED DOCUMENT**

© ISO/IEC 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction.....	vi
1 Scope.....	1
2 Conformance	1
3 Normative references.....	1
4 Terms and definitions.....	1
5 Notational conventions	1
6 Abbreviations and acronyms	2
7 Overview.....	2
8 Interface Signal Description	3
8.1 Interface Signal Definitions	4
8.1.1 Control Interface.....	4
8.1.2 Data Interface	5
8.1.3 CCA Interface.....	5
8.1.4 Management Interface.....	5
8.2 PHY Operational State	6
9 Registers	6
9.1 Bit Ordering and Interpretation.....	6
9.2 Register Address Spaces	6
9.3 Static Parameter Definitions	7
9.4 Static Parameter Coding.....	11
9.5 Dynamic Register Definitions	14
9.6 Register Map	16
9.7 Register Set Access Timing	17
9.7.1 Transmit Control Registers	17
9.7.2 Receive Control Registers.....	18
9.8 TONE-NULLING MAP CONTROL	18
10 Frame Structures.....	19
11 Interface Theory of Operation	24
11.1 Overview.....	24
11.1.1 PHY Reset Protocol.....	25
11.1.2 Exit from Sleep State.....	25
11.1.3 Normal Operation	26
11.2 Frame Timing	26
11.3 Ranging Support	27
11.4 Transceiver Delay Definitions	27
11.5 Transceiver Turnaround Times.....	29
11.5.1 RX-TX Turnaround Time	29
11.5.2 TX-RX Turnaround Time	29
11.6 PREAMBLE CONTROL.....	29
11.6.1 Single Frame Transmission and Reception.....	29
11.6.2 Burst Mode Transmission	30
11.6.3 Burst Mode Reception	31
11.7 Transmit Operation	31
11.7.1 Data Bus Ownership	31
11.7.2 Single Frame Transmission Control.....	31

- 11.7.3 Burst Mode Transmission Control.....33
- 11.7.4 Burst Mode Transmit Error Recovery.....34
- 11.8 Receive Operation34
- 11.8.1 Data Bus Ownership.....34
- 11.8.2 Single Frame Reception Control.....34
- 11.8.3 Burst Mode Reception Control.....37
- 11.8.4 Burst Mode Reception Error Recovery37
- 11.8.5 Zero Length Frame Reception.....38
- 11.9 MAC Transmit Abort.....38
- 11.10 MAC Receive Abort.....39
- 11.11 Error Conditions39
- 11.11.1 Transmit Error Conditions39
- 11.11.2 Receive Error Conditions.....40
- 11.12 Clear Channel Assessment41
- 11.12.1 CCA Interface Signals42
- 11.12.2 Operation of the CCA Interface42
- 11.13 Management Interface.....43
- 11.13.1 Management Interface Signals.....43
- 11.13.2 Operation of the Management Interface.....43
- 11.13.3 Examples45
- Annex A (informative) Electrical Specifications.....47**
- A.1 I/O DC Requirements.....47**
- A.1.1 3,3V DC Specification.....47**
- A.1.2 1,8V DC Specification.....47**
- A.1.3 1,2V DC Specification.....47**
- A.2 MAC and PHY Timing Specifications.....48**
- A.2.1 PHY Signal Timing.....48**
- A.2.2 MAC Signal Timing.....49**
- Annex B (informative) PHY Vendor and Version Coding50**
- B.1 PHYID Format and Coding.....50**
- B.2 PHY Version Format and Coding50**

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 26908 was prepared by Ecma International (as ECMA-369) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

This second edition cancels and replaces the first edition (ISO/IEC 26908:2007), which has been technically revised.

Introduction

ISO/IEC 26907 specifies the PHY and MAC for a high rate ultra wideband wireless transceiver.

Implementations of ISO/IEC 26907 may expose the interface between the PHY and MAC as specified herein.

Information technology — Telecommunications and information exchange between systems — MAC-PHY interface for ISO/IEC 26907

1 Scope

This International Standard specifies the interface between implementations of the PHY and MAC as specified in ISO/IEC 26907.

2 Conformance

PHY and MAC implementations of ISO/IEC 26907 conform to this International Standard by implementing the interface specified herein.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 26907:2009, *Information technology — Telecommunications and information exchange between systems — High-rate ultra-wideband PHY and MAC standard (also published by Ecma as Standard ECMA-368)*