

This is a preview - click here to buy the full publication



ISO/IEC 29145-2

Edition 1.0 2014-03

# INTERNATIONAL STANDARD

---

**Information technology – Wireless beacon-enabled energy efficient mesh network (WiBEEM) standard for wireless home network services – Part 2: MAC layer**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE

U

---

ICS 35.200

ISBN 978-2-8322-1449-7

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	5
INTRODUCTION.....	6
1 Scope.....	7
2 Normative reference .....	7
3 Terms, definitions and abbreviations .....	7
3.1 Terms and definitions.....	7
3.2 Abbreviations.....	8
3.3 Conventions.....	9
4 Conformance.....	10
5 Overview of the WiBEEEM technology.....	10
6 MAC layer specifications .....	10
6.1 General.....	10
6.2 MAC layer service specifications.....	10
6.2.1 Service overview .....	10
6.2.2 MAC data service .....	11
6.2.3 MAC management service .....	17
6.2.4 Association primitives .....	17
6.2.5 Disassociation primitives .....	22
6.2.6 Beacon notification primitive .....	24
6.2.7 Primitives for reading PIB attributes.....	27
6.2.8 RAP management primitives.....	28
6.2.9 Primitives for orphan notification.....	31
6.2.10 Primitives for resetting the MAC layer.....	34
6.2.11 Primitives for specifying the receiver enable time .....	35
6.2.12 Primitives for channel scanning .....	37
6.2.13 Communication status primitive .....	39
6.2.14 Primitives for writing MAC PIB attributes.....	41
6.2.15 Primitives for updating the superframe configuration.....	42
6.2.16 Primitives for synchronising with a WRC.....	45
6.2.17 Primitives for requesting data from a WRC .....	47
6.3 MAC frame formats .....	49
6.3.1 General .....	49
6.3.2 General MAC frame format .....	50
6.3.3 Beacon frame format .....	52
6.3.4 MAC command frame format .....	52
Bibliography.....	62
Figure 1 – MAC layer structure .....	11
Figure 2 – Message sequence chart describing the MAC data service .....	16
Figure 3 – Message sequence chart for association.....	22
Figure 4 – Message sequence chart for disassociation .....	24
Figure 5 – Message sequence chart for RAP allocation initiated by a device.....	31
Figure 6 – Message sequence chart for RAP deallocation initiated by a device and the WMC .....	31

Figure 7 – Beacon lost (orphan notification) message sequence chart .....	33
Figure 8 – Message sequence chart for updating the superframe configuration .....	45
Figure 9 – Message sequence chart for synchronising to a WRC in a beacon-enabled WPAN .....	47
Figure 10 – Message sequence chart for requesting data from the WRC .....	49
Figure 11 – General MAC frame format .....	50
Figure 12 – Beacon frame format .....	52
Table 1 – MLDE-DATA.request parameters .....	12
Table 2 – MLDE-DATA.confirm parameters .....	13
Table 3 – MLDE-DATA.indication parameters .....	14
Table 4 – MLDE-ERASE.request parameters .....	15
Table 5 – MLDE-ERASE.confirm parameters .....	16
Table 6 – Summary of the primitives accessed through the MLME-SAP .....	17
Table 7 – MLME-ASSOCIATE.request parameters .....	18
Table 8 – MLME-ASSOCIATE.indication parameters .....	19
Table 9 – MLME-ASSOCIATE.response parameters .....	20
Table 10 – MLME-ASSOCIATE.confirm parameters .....	21
Table 11 – MLME-DISASSOCIATE.request parameters .....	22
Table 12 – MLME-DISASSOCIATE.indication parameters .....	23
Table 13 – MLME-DISASSOCIATE.confirm parameters .....	24
Table 14 – MLME-BEACON-NOTIFY.indication parameters .....	25
Table 15 – Elements of mesh descriptor .....	26
Table 16 – MLME-READ-MIB.request parameters .....	27
Table 17 – MLME-READ-MIB.confirm parameters .....	28
Table 18 – MLME-RAP-MANAGEMENT.request parameters .....	29
Table 19 – MLME-RAP-MANAGEMENT.confirm parameters .....	29
Table 20 – MLME-RAP-MANAGEMENT.indication parameters .....	30
Table 21 – MLME-BEACON-LOST.indication parameters .....	32
Table 22 – MLME-BEACON-LOST.indication parameters .....	33
Table 23 – MLME-RESET.request parameters .....	34
Table 24 – MLME-RESET.confirm parameters .....	35
Table 25 – MLME-RX-ON.request parameters .....	35
Table 26 – MLME-RX-ON.confirm parameters .....	36
Table 27 – MLME-SCAN.request parameters .....	37
Table 28 – MLME-SCAN.confirm parameters .....	39
Table 29 – MLME-COMM-RESULT.indication parameters .....	40
Table 30 – MLME-WRITE-MIB.request parameters .....	41
Table 31 – MLME-WRITE-MIB.confirm parameters .....	42
Table 32 – MLME-START.request parameters .....	43
Table 33 – MLME-START.confirm parameters .....	44
Table 34 – MLME-SYNC.request parameters .....	45
Table 35 – MLME-SYNC-LOSS.indication parameters .....	46

Table 36 – MLME-INDIRECT-COMM.request parameters .....	48
Table 37 – MLME-INDIRECT-COMM.confirm parameters .....	48
Table 38 – MAC command frame .....	53
Table 39 – Association request command .....	53
Table 41 – Association response command .....	54
Table 42 – Association status field .....	55
Table 43 – Disassociation notification command format .....	55
Table 44 – Disassociation reason code .....	56
Table 45 – Data request command format .....	57
Table 46 – Mesh ID conflict notification command format .....	57
Table 47 – Orphan notification command format .....	58
Table 48 – Beacon request command format .....	58
Table 49 – Co-ordinator realignment command format .....	59
Table 50 – CFP request command format .....	60
Table 51 – CFP characteristics field format .....	60
Table 52 – Rate reconfiguration request format .....	60
Table 53 – Data rate .....	61
Table 54 – Rate reconfiguration request command format .....	61

# **INFORMATION TECHNOLOGY – WIRELESS BEACON-ENABLED ENERGY EFFICIENT MESH NETWORK (WIBEEM) STANDARD FOR WIRELESS HOME NETWORK SERVICES –**

## **Part 2: MAC layer**

### **FOREWORD**

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 10) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 29145-2 was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 29145 series, under the general title *Information technology – Wireless beacon-enabled energy efficient mesh network (WiBEEM) for wireless home network services*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

## INTRODUCTION

This International Standard specifies the WiBEEM (Wireless Beacon-enabled Energy Efficient Mesh network) protocol, which provides low-power-consuming mesh network functions by enabling the “beacon mode operation”. WiBEEM is based on IEEE 802.15.4 standard with additional upper layer protocols and a specific usage of the MAC layer protocol. Through the novel use of beacons, WiBEEM technology achieves longer battery life, larger network support, quicker response, enhanced mobility and dynamic reconfiguration of the network topology compared with other protocols such as ZigBee.

In the beacon mode, Beacon information propagates over the entire mesh network nodes during the BOP (Beacon-Only Period) of the superframe structure without any beacon conflicts by utilising a smart beacon scheduling technique in the BOP. It also provides location information about moving devices without spending extra time running a positioning and locating algorithm by using RSSI (Received Signal Strength Indication). These features allow the WiBEEM protocol to be widely used for wireless home network services in the ubiquitous network era.

One of the key features of the WiBEEM protocol is that it has a special time interval called BOP (Beacon-Only Period) in the superframe structure that allows more than two beacons to be transmitted. This unique time period is located at the beginning of the Superframe. Because the BOP does not use the CSMA/CA mechanism, the network will not work properly in the beacon mode unless an appropriate algorithm is applied. This algorithm needs to manage and control multiple beacons in a single superframe. The solution is the Beacon Scheduling method applied in the BOP to avoid collisions among beacons, providing synchronisation among all the nodes of the entire mesh network.

For the network layer, the NAA (Next Address Available) mechanism, which is a short address allocation algorithm, has been adopted to provide an efficient way of utilising the complete 16-bit address space. The NAA algorithm does not limit the maximum number of children nodes that a node of a mesh network can have. Since the number of children nodes is unlimited, the NAA mechanism allows the WiBEEM protocol to be used not only for home network services, but also for community services. WiBEEM can be used where high network expandability through efficient use of short address spaces, device mobility and end-to-end QoS are required.

This part of the standard ISO/IEC 29145 specifies the Medium Access Control (MAC) layer of the WiBEEM protocol.

# INFORMATION TECHNOLOGY – WIRELESS BEACON-ENABLED ENERGY EFFICIENT MESH NETWORK (WiBEEM) STANDARD FOR WIRELESS HOME NETWORK SERVICES –

## Part 2: MAC layer

### 1 Scope

This part of ISO/IEC 29145 specifies the MAC of the WiBEEM (Wireless Beacon-enabled Energy Efficient Mesh network) protocol for wireless home network services that supports a low power-consuming wireless mesh network as well as device mobility and QoS.

### 2 Normative reference

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 29145-1:2014, *Information technology – Wireless beacon-enabled energy efficient mesh network (WiBEEM) for wireless home network services – Part 1: PHY layer*

IEEE 802.15.4:2003, *IEEE Standard for Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 15.4: Wireless Medium Access Control (MAC) and Physical Layer (PHY) Specifications for Low-Rate Wireless Personal Area Networks (LR-WPANs)*