

This is a preview - [click here to buy the full publication](#)



ISO/IEC 29341-18-1

Edition 1.0 2011-08

INTERNATIONAL STANDARD



**Information technology – UPnP device architecture –
Part 18-1: Remote Access Device Control Protocol – Remote Access
Architecture**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

K

ICS 35.200

ISBN 978-2-88912-648-4

CONTENTS

1	Overview and Scope.....	3
1.1	Notation	3
1.2	References.....	4
1.2.1	Informative References	4
1.3	Terms and Abbreviations	5
1.3.1	Abbreviations.....	5
1.3.2	Terms.....	5
2	Introduction.....	7
3	Operational Considerations	7
3.1	Remote Access Environment	7
3.2	Access Networks.....	8
3.2.1	IPv4 Addressing and NAT issues	9
3.2.2	IPv6 Addressing.....	10
3.3	Home Network Environment	10
3.3.1	IPv4 Support in Home Routers	10
3.3.2	IPv6 Support in Home Routers	10
3.4	Support Services in the Public Network.....	10
3.4.1	Server Name Resolution	10
3.4.2	Detecting NAT and NAT Type on Server Side.....	10
4	Remote Access Reference Architecture	11
4.1	Remote Access Architecture Paradigm	11
4.2	Remote Access Components Overview	12
4.3	Remote Access Phases Overview.....	13
4.3.1	Setup Services	13
4.3.2	Operational Services.....	13
4.3.3	Management Service	14
4.4	Remote Access Functionalities	14
4.4.1	Inbound Connection Configuration	14
4.4.2	Remote Access Discovery Agent.....	15
4.4.3	Remote Access Transport Agent	17
5	Interaction Model.....	17
5.1	UPnP RA Setup.....	17
5.2	Configure the RAC for Remote Access to Home Network	18
5.3	Access Home Network Remotely from RAC over the Internet	18
5.4	UPnP RA Connection Use	18
5.5	RADA Synchronization Process	19
5.6	RADA Heartbeat.....	19
5.7	RADA Communication Time-out.....	20
5.8	RADA Administrative Shutdown	20
Annex A	Deployment Scenarios	21
A.1	Intended Deployment Scenarios	21
A.1.1	Remote Access Server in Residential Gateway	21
A.1.2	Remote Access Server in a 3rd Party Device.....	21
A.1.3	Remote Access Server Hosted by a 3rd Party in the Internet	21

Figure 2-1 — UPnP Remote Access.....	7
Figure 3-1 — Remote Access Environment.	8
Figure 3-2 — Access Networks.	9
Figure 4-1 — Remote Access Architecture Paradigm.	11
Figure 4-2 — Remote Access Components Overview.	12
Figure 4-3 — Typical STUN Configuration in Home Networks.....	15
Figure 4-4 — Discovery Information Aggregation.....	16
Figure 4-5 — Discovery Synchronization.....	16
Figure 5-1 — Remote Access Setup.....	17
Figure 5-2 — Configure the RAC for Remote Access to Home Network	18
Figure 5-3 — Access Home Network Remotely from RAC over the Internet	18
Figure 5-4 — UPnP RA Connection Use.....	18
Figure 5-5 — RADA Synchronization Process	19
Figure 5-6 — RADA Heartbeat.....	19
Figure 5-7 — RADA Communication Time-out.....	20
Figure 5-8 — RADA Administrative Shutdown	20
Table 1-1 — Abbreviations.....	5

INFORMATION TECHNOLOGY – UPNP DEVICE ARCHITECTURE –

Part 18-1: Remote Access Device Control Protocol – Remote Access Architecture

FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 10) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 29341-18-1 was prepared by UPnP Forum Steering committee¹, was adopted, under the fast track procedure, by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 29341 series, under the general title *Information technology – UPnP device architecture*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

¹ UPnP Forum Steering committee, UPnP Forum, 3855 SW 153rd Drive, Beaverton, Oregon 97006 USA. See also "Introduction".

[This is a preview - click here to buy the full publication](#)

29341-18-1 © ISO/IEC:2011(E)

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

1 Overview and Scope

This document describes an architecture that provides the infrastructure that allows generic UPnP devices, services and control points deployed in remote physical devices to interact with the corresponding UPnP devices, services and control points physically attached to the home network. The mechanisms defined in this architecture will allow to extend the home network so that it will logically include the remote devices so that all devices will be able to communicate among themselves using the UPnP Forum defined mechanisms, e.g. UDA. The desired behavior of the interactions between the remote device and home devices is envisioned to be similar with the one expected as if all devices are located in the same local area network.

In order to accommodate the above mentioned goals, the Remote Access Architecture will provide means to connect the two segments of the extended home network using established mechanisms. The architecture recognizes that there might be several possible alternative models to “bridge” the two segments and will provide an interface that will allow them to be plugged, while enforcing the same overall behavior of the whole system regardless of the model used.

The architecture does not describes any interfaces to “service” gateways that will enable non-UPnP entities to interact with the UPnP devices, services and control points physically attached to the home network.

1.1 Notation

- In this document, features are described as Required, Recommended, or Optional as follows:

The key words “MUST,” “MUST NOT,” “REQUIRED,” “SHALL,” “SHALL NOT,” “SHOULD,” “SHOULD NOT,” “RECOMMENDED,” “MAY,” and “OPTIONAL” in this specification are to be interpreted as described in [RFC 2119].

In addition, the following keywords are used in this specification:

PROHIBITED – The definition or behavior is an absolute prohibition of this specification. Opposite of **REQUIRED**.

CONDITIONALLY REQUIRED – The definition or behavior depends on a condition. If the specified condition is met, then the definition or behavior is **REQUIRED**, otherwise it is **PROHIBITED**.

CONDITIONALLY OPTIONAL – The definition or behavior depends on a condition. If the specified condition is met, then the definition or behavior is **OPTIONAL**, otherwise it is **PROHIBITED**.

These keywords are thus capitalized when used to unambiguously specify requirements over protocol and application features and behavior that affect the interoperability and security of implementations. When these words are not capitalized, they are meant in their natural-language sense.

- Strings that are to be taken literally are enclosed in “double quotes”.
- Words that are emphasized are printed in *italic*.
- Keywords that are defined by the UPnP Working Committee are printed using the *forum* character style.
- Keywords that are defined by the UPnP Device Architecture are printed using the *arch* character style.
- A double colon delimiter, “::”, signifies a hierarchical parent-child (parent::child) relationship between the two objects separated by the double colon. This delimiter is used in multiple contexts, for example: `Service::Action()`, `Action()::Argument`, `parentProperty::childProperty`.

1.2 References

1.2.1 Informative References

This clause lists the informative references that are provided as information in helping understand this specification:

[DEVICE] – UPnP Device Architecture, version 1.0. Available at: <http://www.upnp.org/specs/arch/UPnP-arch-DeviceArchitecture-v1.0-20080424.pdf>. Latest version available at: <http://www.upnp.org/specs/arch/UPnP-arch-DeviceArchitecture-v1.0.pdf>.

[DEVICE-IPv6] – UPnP Device Architecture, version 1.0., Annex A – IP Version 6 Support. Available at: http://www.upnp.org/resources/documents/AnnexA-IPv6_000.pdf

[ICC] – InboundConnectionConfig:1, UPnP Forum, Available at: <http://www.upnp.org/specs/ra/UPnP-ra-InboundConnectionConfig-v1-Service-20090930.pdf>. Latest version available at: <http://www.upnp.org/specs/ra/UPnP-ra-InboundConnectionConfig-v1-Service.pdf>.

[RAClient] – RAClient:1, UPnP Forum, Available at: <http://www.upnp.org/specs/ra/UPnP-ra-RAClient-v1-Device-20090930.pdf>. Latest version available at: <http://www.upnp.org/specs/ra/UPnP-ra-RAClient-v1-Device.pdf>.

[RADAConfig] – RADAConfig:1, UPnP Forum, Available at: <http://www.upnp.org/specs/ra/UPnP-ra-RADAConfig-v1-Service-20090930.pdf>. Latest version available at: <http://www.upnp.org/specs/ra/UPnP-ra-RADAConfig-v1-Service.pdf>.

[RADASync] – RADASync:1, UPnP Forum, Available at: <http://www.upnp.org/specs/ra/UPnP-ra-RADASync-v1-Service-20090930.pdf>. Latest version available at: <http://www.upnp.org/specs/ra/UPnP-ra-RADASync-v1-Service.pdf>.

[RADiscoveryAgent] – RADiscoveryAgent:1, UPnP Forum, Available at: <http://www.upnp.org/specs/ra/UPnP-ra-RADiscoveryAgent-v1-Device-20090930.pdf>. Latest version available at: <http://www.upnp.org/specs/ra/UPnP-ra-RADiscoveryAgent-v1-Device.pdf>.

[RAServer] – RAServer:1, UPnP Forum, Available at: <http://www.upnp.org/specs/ra/UPnP-ra-RAServer-v1-Device-20090930.pdf>. Latest version available at: <http://www.upnp.org/specs/ra/UPnP-ra-RAServer-v1-Device.pdf>.

[RATAConfig] – RATAConfig:1, UPnP Forum, Available at: <http://www.upnp.org/specs/ra/UPnP-ra-RATAConfig-v1-Service-20090930.pdf>. Latest version available at: <http://www.upnp.org/specs/ra/UPnP-ra-RATAConfig-v1-Service.pdf>.

[IGD] – InternetGatewayDevice:1, UPnP Forum, November, 2001 Available at: http://www.upnp.org/standardizeddcpes/documents/UPnP_IGD_1.0.zip.

[RFC 1889] – IETF RFC 1889, RTP: A Transport Protocol for Real-Time Applications, H. Schulzrinne, S. Casner, R. Frederick, V. Jacobson, January 1996. Available at: <http://www.ietf.org/rfc/rfc1889.txt>.

[RFC 1918] – IETF RFC 1918, *Address Allocation for Private Internets*, Y. Rekhter, et. Al, February 1996 Available at: <http://www.ietf.org/rfc/rfc1918.txt>

[RFC 2119] – IETF RFC 2119, Key words for use in RFCs to Indicate Requirement Levels, S. Bradner, March 1997. Available at: <http://www.ietf.org/rfcs/rfc2119.txt>.

[RFC 2131] – IETF RFC 2131, *Dynamic Host Configuration Protocol*, R. Droms, March 1997 Available at: <http://www.ietf.org/rfc/rfc2131.txt>

[RFC 2516] – IETF RFC 2516, *A Method for Transmitting PPP Over Ethernet (PPPoE)*, L. Mamakos, et. Al, February 1999 Available at: <http://www.ietf.org/rfc/rfc2516.txt>

[RFC 3056] – IETF RFC 3056, *Connection of IPv6 Domains via IPv4 Clouds*, B. Carpenter, K. Moore, February 2001 Available at: <http://www.ietf.org/rfc/rfc3056.txt>

[RFC 3489] – IETF RFC 3489, *STUN - Simple Traversal of User Datagram Protocol (UDP) Through Network Address Translators (NATs)*, J. Rosenberg, et. Al, March 2003 Available at: <http://www.ietf.org/rfc/rfc3489.txt>

[RFC 3550] – IETF RFC 3550, *RTP: A Transport Protocol for Real-Time Applications*, H. Schulzrinne, et. Al, July 2003 Available at: <http://www.ietf.org/rfc/rfc3550.txt>

[RFC 4380] – IETF RFC 4380, *Teredo: Tunneling IPv6 over UDP through Network Address Translations (NATs)*, C. Huitema, February 2006 Available at: <http://www.ietf.org/rfc/rfc4380.txt>

[RFC 3986] – IETF RFC 3986, *Uniform Resource Identifier (URI): Generic Syntax*, Tim Berners-Lee, et. Al, January 2005. Available at: <http://www.ietf.org/rfc/rfc3986.txt>