

INTERNATIONAL STANDARD

ISO/IEC 9574

Second edition
1992-12-15

Information technology — Provision of the OSI connection-mode network service by packet mode terminal equipment to an integrated services digital network (ISDN)

*Technologies de l'information — Fourniture du service de réseau OSI en
mode connexion par un terminal en mode paquet raccordé à un réseau
numérique avec intégration de service (RNIS)*



Reference number
ISO/IEC 9574:1992(E)

Contents

1 Scope.....	1
2 Normative references	2
3 Definitions.....	3
4 Abbreviations.....	5
5 Overview	5
6 Provision of the CONS in systems attached at the S/T reference point	6
7 Provision of the CONS in systems attached at the R reference point	16
Annex	
A Bibliography.....	19

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 9574 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in collaboration with the CCITT. The identical text is published as CCITT Recommendation X.612

This second edition cancels and replaces the first edition (ISO 9574:1989), of which it constitutes a technical revision.

Annex A of this International Standard is for information only.

INTERNATIONAL STANDARD**CCITT RECOMMENDATION****INFORMATION TECHNOLOGY –
PROVISION OF THE OSI CONNECTION-MODE NETWORK
SERVICE BY PACKET-MODE TERMINAL EQUIPMENT
CONNECTED TO AN INTEGRATED SERVICES DIGITAL
NETWORK (ISDN)****1 Scope**

This Recommendation | International Standard specifies the method of providing the OSI Connection-mode Network Service (CONS) by packet mode terminal equipment connected to an Integrated Services Digital Network (ISDN) in accordance with the procedures described in Recommendation X.31. This is done by specifying the mapping of the CONS primitives and parameters to and from the elements of the protocols used by two types of packet mode terminal equipment:

- a) an X.25 DTE (TE2) connected to an R reference point and accessing an ISDN; and
- b) a packet mode ISDN terminal (TE1) operating ISO/IEC 8208 packet layer protocol (PLP) and connected to an ISDN at either the S or T reference point.

This Recommendation | International Standard is applicable:

- a) when operating according to Recommendation X.31, either a TE1 or a TE2 is connected to a packet handler in an ISDN or an access unit to a packet-switched data network via an ISDN;
- b) when using an ISDN circuit-switched channel, either TE1s and/or TE2/TAs are connected directly to each other (i.e. the terminals operate in DTE/DTE mode).

This Recommendation | International Standard does not address TE2s using TAs (at the R reference point) when using an ISDN circuit-switched channel with the terminals operating in DTE/DTE mode (see Recommendation X.613 | ISO/IEC 10588).

NOTES

1 The definitions of TE1, TE2 and TA equipment, and R, S, and T reference points are given in Recommendation I.411.

2 This Recommendation | International Standard applies to a TE1 or TE2/TA (i.e. an OSI End System) regardless of whether it is a physically separate system or embedded in other equipment such as a PBX.

This Recommendation | International Standard addresses the provision of the CONS using Virtual Calls as described in Recommendation X.25. It does not address the use of X.25 Permanent Virtual Circuits. The extension of this Recommendation | International Standard to include the use of X.25 PVCs is for further study.

NOTE – This Recommendation | International Standard uses numbers to identify layers, rather than their names. This is done to align the terminology of this document with the terminology of the related ISDN Recommendations, and does not imply any change in the functionality of the layers from that defined in the reference model of open systems interconnection.

2 Normative references

The following CCITT Recommendations and ISO/IEC International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision. Parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent editions of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The CCITT Secretariat maintains a list of currently valid CCITT Recommendations.

2.1 Identical Recommendations | International Standards

- CCITT Recommendation X.213 (1992) | ISO/IEC 8348: 1992, *Information technology – Network service definition for Open Systems Interconnection*

2.2 Paired Recommendations | International Standards equivalent in technical content

- CCITT Recommendation X.200 (1988), *Reference model of open systems interconnection for CCITT applications.*
ISO 7498:1984, Information processing systems – Open Systems Interconnection – Basic Reference Model.
- CCITT Recommendation X.210 (1988), *Open systems interconnection layer service definition conventions.*
ISO/TR 8509:1987, Information processing systems – Open Systems Interconnection – Service conventions.
- CCITT Recommendation X.223 (1988), *Use of X.25 to provide the OSI connection-mode network service for CCITT applications.*
ISO 8878:1987, Information processing systems – Data communications – Use of X.25 to provide the OSI connection-mode network service.

2.3 Additional references

- CCITT Recommendation I.231 (1988), *Circuit-mode bearer service categories.*
- CCITT Recommendation I.232 (1988), *Packet-mode bearer service categories.*
- CCITT Recommendation I.430 (1988), *Basic User-Network Interface Layer 1 Specification.*
- CCITT Recommendation I.431 (1988), *Primary Rate User-Network Interface Layer 1 Specification.*
- CCITT Recommendation Q.921 (I.441) (1988), *ISDN User-Network Interface Data Link Layer Specification.*
- CCITT Recommendation Q.931 (I.451) (1988), *ISDN User-Network Interface Layer 3 Specification for Basic Call Control.*
- CCITT Recommendation V.25 bis (1988), *Automatic Answering Equipment and/or Parallel Automatic Calling Equipment on the General Switched Telephone Network Including Procedures for Disabling of Echo Control Devices for Both Manually and Automatically Established Calls.*
- CCITT Recommendation X.21 (1988), *Interface Between Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE) for Synchronous Operation on Public Data Networks.*
- CCITT Recommendation X.21 bis (1988), *Use on Public Data Networks of Data Terminal Equipment (DTE) which is Designed for Interfacing to Synchronous V-series Modems.*

- CCITT Recommendation X.25 (1988), *Interface between data terminal equipment (DTE) and data circuit-terminating equipment (DCE) for terminals operating in the packet mode and connected to public data networks by dedicated circuit.*
- CCITT Recommendation X.30 (I.462) (1988), *Support of X.21, X.21 bis and X.20 bis based data terminal equipments (DTEs) by an integrated services digital network (ISDN).*
- CCITT Recommendation X.31 (I.462) (1988), *Support of Packet Mode Terminal Equipment by an ISDN.*
- CCITT Recommendation X.32 (1988), *Interface between data terminal equipment (DTE) and data circuit-terminating equipment (DCE) for terminals operating in the packet mode and accessing a packet switched public data network through a public switched telephone network or an ISDN or a circuit switched public data network.*
- ISO 7776:1986, *Information processing systems – Data communications – High-level data link control procedures – Description of the X.25 LAPB-compatible DTE data link procedures.*
- ISO/IEC 8208:1990, *Information technology – Data communications – X.25 Packet Layer Protocol for Data Terminal Equipment.*