

This is a preview - [click here to buy the full publication](#)



ISO/IEC TR 11801-9905

Edition 1.0 2018-02

TECHNICAL REPORT

**Information technology – Generic cabling for customer premises –
Part 9905: Guidelines for the use of installed cabling to support 25GBASE-T
application**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 35.200

ISBN978-2-8322-5373-1

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references	8
3 Terms, definitions and abbreviations	8
4 Cabling channel specifications for 25 GBASE-T.....	9
4.1 General.....	9
4.2 25GBASE-T application specifications	9
4.2.1 Return loss	9
4.2.2 Insertion loss/attenuation.....	10
4.2.3 NEXT.....	11
4.2.4 Attenuation to crosstalk ratio at the near-end (ACR-N)	13
4.2.5 Attenuation to crosstalk ratio at the far-end (ACR-F).....	13
4.2.6 Propagation delay.....	15
4.2.7 Delay skew	15
4.2.8 Unbalance attenuation and coupling attenuation	15
4.2.9 Alien crosstalk	16
4.3 Associated risk of 25GBASE-T operation over installed cabling	17
4.4 Characterization of balanced channels using Category 7 _A components	17
4.4.1 General	17
4.4.2 Selection of channels for qualification.....	18
4.4.3 Return loss	18
4.4.4 Insertion loss.....	19
4.4.5 Near-end crosstalk loss (NEXT).....	19
4.4.6 Attenuation to crosstalk loss ratio near-end (ACR-N).....	21
4.4.7 Attenuation to crosstalk ratio far-end (ACR-F)	22
4.4.8 Alien (exogenous) crosstalk.....	24
4.4.9 Propagation delay.....	25
4.4.10 Delay skew	25
4.4.11 Coupling attenuation.....	25
4.4.12 Alien crosstalk and coupling attenuation	26
4.5 Characterization of balanced channels using Category 7 components.....	26
4.5.1 General	26
4.5.2 Selection of channels for qualification.....	27
4.5.3 Return loss	27
4.5.4 Insertion loss.....	28
4.5.5 Near-end crosstalk loss (NEXT).....	28
4.5.6 Attenuation to crosstalk loss ratio near-end (ACR-N).....	30
4.5.7 Attenuation to crosstalk ratio far-end (ACR-F)	31
4.5.8 Alien (exogenous) crosstalk.....	33
4.5.9 Propagation delay.....	34
4.5.10 Delay skew	34
4.5.11 Coupling attenuation.....	34
4.5.12 Alien crosstalk and coupling attenuation	35
4.6 Characterization of balanced channels using Category 6 _A components	35
4.6.1 General	35
4.6.2 Selection of channels for qualification.....	36

4.6.3	Test specifications for channels made out of Category 6 _A components	36
5	Guidance for mitigation procedures to improve the cabling of existing installations	36
5.1	General.....	36
5.2	Mitigation procedures related to internal noise	36
5.3	Mitigation procedures related to exogenous noise (alien crosstalk)	36
6	Guidance for cabling for new installations.....	37
	Bibliography.....	38
Table 1	– Return loss for a channel	9
Table 2	–Return loss values for a channel at key frequencies	10
Table 3	– Insertion loss for a channel	10
Table 4	– Insertion loss values for a channel at key frequencies	11
Table 5	– NEXT for a channel.....	11
Table 6	– NEXT values for a channel at key frequencies.....	12
Table 7	– PS NEXT for a channel	12
Table 8	– PS NEXT values for a channel at key frequencies	13
Table 9	– ACR-F for a channel.....	13
Table 10	– ACR-F values for a channel at key frequencies	14
Table 11	– PS ACR -F for a channel	14
Table 12	– PS ACR-F values for a channel at key frequencies.....	14
Table 13	– Propagation delay for a channel	15
Table 14	– Propagation delay values for a channel at key frequencies.....	15
Table 15	– Delay skew for a channel	15
Table 16	– PS ANEXT for a channel	16
Table 17	– PS ANEXT values for a channel at key frequencies	16
Table 18	– PS AACR-F for a channel.....	17
Table 19	– PS AACR-F values for a channel at key frequencies	17
Table 20	– Risk of 25GBASE-T operation over installed cabling channels.....	17
Table 21	– Formulae for return loss limits for a channel	18
Table 22	– Return loss limits for a channel at key frequencies	18
Table 23	– Formula for insertion loss limits for a channel.....	19
Table 24	– Insertion loss limits for a channel at key frequencies	19
Table 25	– Formulae for pair-to-pair NEXT limits for a channel	19
Table 26	– Pair-to-pair NEXT limits for a channel at key frequencies	20
Table 27	– Formulae for PS NEXT limits for a channel.....	20
Table 28	–PS NEXT limits for a channel at key frequencies	20
Table 29	– ACR-N limits for a channel at key frequencies	21
Table 30	– PS ACR-N limits for a channel at key frequencies	22
Table 31	– Formulae for ACR-F limits for a channel.....	22
Table 32	– ACR-F limits for a channel at key frequencies	23
Table 33	– Formulae for PS ACR-F limits for a channel	23
Table 34	– PS ACR-F limits for a channel at key frequencies.....	23
Table 35	– Formulae for PS ANEXT limits for a channel	24
Table 36	– PS ANEXT limits for a channel at key frequencies	24

Table 37 – Formula for PS AACR-F limits for a channel	24
Table 38 – PS AACR-F limits for a channel at key frequencies	25
Table 39 – Formula for propagation delay limits for a channel.....	25
Table 40 – Propagation delay limits for a channel at key frequencies.....	25
Table 41 – Formula for coupling attenuation limits for a channel	26
Table 42 – Coupling attenuation limits for a channel at key frequencies.....	26
Table 43 – Alien crosstalk and coupling attenuation.....	26
Table 44 – Formulae for return loss limits for a channel	27
Table 45 – Return loss limits for a channel at key frequencies	27
Table 46 – Formula for insertion loss limits for a channel.....	28
Table 47 – Insertion loss limits for a channel at key frequencies	28
Table 48 – Formulae for pair-to-pair NEXT limits for a channel	28
Table 49 – Pair-to-pair NEXT limits for a channel at key frequencies	29
Table 50 – Formulae for PS NEXT limits for a channel.....	29
Table 51 – PS NEXT limits for a channel at key frequencies	29
Table 52 – ACR-N limits for a channel at key frequencies	30
Table 53- PS ACR-N limits for a channel at key frequencies	31
Table 54 – Formulae for ACR-F limits for a channel	31
Table 55 – ACR-F limits for a channel at key frequencies	32
Table 56 – Formulae for PS ACR-F limits for a channel	32
Table 57 – PS ACR-F limits for a channel at key frequencies.....	32
Table 58 – Formulae for PS ANEXT limits for a channel	33
Table 59 – PS ANEXT limits for a channel at key frequencies	33
Table 60 – Formula for PS AACR-F limits for a channel	33
Table 61 – PS AACR-F limits for a channel at key frequencies	34
Table 62 – Formula for propagation delay limits for a channel.....	34
Table 63 – Propagation delay limits for a channel at key frequencies.....	34
Table 64 – Formula for coupling attenuation limits for a channel	35
Table 65 – Coupling attenuation limits for a channel at key frequencies.....	35
Table 66 – Alien crosstalk and coupling attenuation for shielded channels.....	35

INFORMATION TECHNOLOGY – GENERIC CABLING FOR CUSTOMER PREMISES –

Part 9905: Guidelines for the use of installed cabling to support 25GBASE-T application

FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 10) Attention is drawn to the possibility that some of the elements of this ISO/IEC publication may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

The main task of the joint technical committee is to prepare International Standards. However, the joint technical committee may propose the publication of a Technical Report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

ISO/IEC TR 11801-9905, which is a Technical Report, was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 11801 series, under the general title *Information technology — Generic cabling for customer premises*, can be found on the IEC website.

This Technical Report has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

This Technical Report is to be read in conjunction with ISO/IEC/IEEE 8802.3:2017/AMD3.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

INTRODUCTION

This document provides guidance to determine whether and which installed channels will support 25GBASE-T. It takes into account the design goals for 25GBASE-T equipment such as:

- a) the frequency signal range up to 1 250 MHz;
- b) the support of two-connector channels up to 30 m in length.

The requirements of 25GBASE-T are fully defined in ISO/IEC/IEEE 8802-3:2017/AMD3.

Installed two-connector channels which are characterized up to 1 250 MHz and support all the requirements of the ISO/IEC/IEEE 8802-3:2017/AMD3 link segment are expected to support the 25GBASE-T application.

Characterization of channels using Category 7_A components is described in 4.4.

Characterization of channels using Category 7 components is described in 4.5.

Characterization of channels using Category 6_A components is described in 4.6.

This document also provides mitigation procedures to improve the performance of installed channels to the point where the 25GBASE-T application is supported. Additionally, this document recommends the use of Class I and Class II channels to support 25GBASE-T in new installations.

Class I and Class II channels according to ISO/IEC 11801-1 will support 25GBASE-T without mitigation.

Component requirements are not provided in this document and should not be inferred from the channel limits provided.

INFORMATION TECHNOLOGY – GENERIC CABLING FOR CUSTOMER PREMISES –

Part 9905: Guidelines for the use of installed cabling to support 25GBASE-T application

1 Scope

This part of ISO/IEC 11801, which is a Technical Report,

- a) provides guidance on how to select and assess installed channels which conform to ISO/IEC 11801-1, and clarify if they also support ISO/IEC/IEEE 8802-3:2017/AMD3 for 25GBASE-T;
- b) specifies the methods to assess whether installed channels constructed with Category 7_A, 7, or 6_A components meet the 25GBASE-T requirements;
- c) provides guidance to identify which channels are likely to meet the 25GBASE-T requirements to avoid unnecessary testing;
- d) provides mitigation techniques to improve the performance of installed channels to meet the 25GBASE-T requirements;
- e) provides cabling recommendations for new installations.

NOTE 1 The channel transmission performance specified in this document is derived from the 25GBASE-T requirements in ISO/IEC/IEEE 8802-3:2017/AMD3.

NOTE 2 This document does not re-specify component or channel definitions of ISO/IEC 11801-1.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 11801-1, *Information technology – Generic cabling systems – Part 1: General requirements*

ISO/IEC/IEEE 8802-3:2017/AMD3, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Standard for Ethernet – Amendment 3: Physical layers and management parameters for 25 Gb/s and 40 Gb/s operation, types 25GBASE-T and 40GBASE-T*